

### 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b> Trade name	: 922-138/320 180L
Product code	: 00000002050003711
Use of the	of the substance or mixture and uses advised against : Spraying
Substance/Mixture	hardener

#### 1.3 Details of the supplier of the safety data sheet

Company: BASF Coatings GmbH Postfach 6123 48136 Münster Deutschland

### Contact address:

BASF plc 4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG United Kingdom

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



### 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

#### 1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory	H335: May cause respiratory irritation.



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

system

### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H226	Flammable liquid and vapor.
		H317	May cause an allergic skin reaction.
		H332	Harmful if inhaled.
		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Statements		: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261	Avoid breathing mist or vapors.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Response:	
	P303 + P30	61 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P304 + P34	40 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
	P370 + P3	78 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.



### 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Hazardous ingredients which must be listed on the label: Hexamethylen-1,6-diisocyanat Homopolymer

1-methoxy-2-propylacetate

n-Butyl acetate

xylene

#### **Additional Labeling**

EUH204 Contains isocyanates. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : organic solvent



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

### Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
Hexamethylen-1,6-diisocyanat	28182-81-2	Acute Tox. 4;	>= 25 - < 50
Homopolymer		H332	
	01-2119485796-17	Skin Sens. 1;	
		H317	
		STOT SE 3; H335	
		(Respiratory	
		system)	
1-methoxy-2-propylacetate	108-65-6	Flam. Liq. 3; H226	>= 20 - < 25
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
	UK-20-	system)	



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

	9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000		
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0-	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 15 - < 20



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

	0000		
xylene	1330-20-7	Flam. Liq. 3; H226	>= 7 - < 10
	215-535-7	Acute Tox. 4;	
	601-022-00-9	H332	
	UK-20- 2749242067-7-	Acute Tox. 4; H312	
	0000	Skin Irrit. 2; H315	
	UK-20-	Eye Irrit. 2; H319	
	9702550300-0- 0000	STOT SE 3; H335	
	UK-20- 0537843089-5-	(Respiratory system)	
	0000	STOT RE 2; H373	
	UK-20- 9642318150-0- 0000	(Kidney, Liver, Central nervous system)	
		Asp. Tox. 1; H304	
		Aquatic	



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

		Chronic 3; H412	
ethylbenzene	100-41-4	Flam. Liq. 2; H225	>= 1 - < 2
	202-849-4	Acute Tox. 4;	
	601-023-00-4	H332	
	UK-20-	STOT RE 2; H373	
	9702550300-0-	(Auditory system)	
	0000	Asp. Tox. 1; H304	
	UK-20-	Aquatic	
	0537843089-5- 0000	Chronic 3; H412	
isobutyl acetate	110-19-0	Flam. Liq. 2; H225	>= 1 - < 2
	203-745-1	STOT SE 3; H336	
	607-026-00-7	(Central nervous	
	UK-20-	system)	
	0537843089-5-		
	0000		
	UK-20-		
	9642318150-0-		



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003	
		711	Date of first issue: 25.04.2025

0000	
0000	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice	<ul> <li>First aid personnel should pay attention to their own safety.</li> <li>If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).</li> <li>Immediately remove contaminated clothing.</li> <li>In all cases of doubt, or when symptoms persist, seek medical attention.</li> <li>Move out of dangerous area.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
If inhaled	If symptoms persist, call a physician. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration.



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

In case of skin contact	:	If symptoms persist, call a physician.
		Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
		Do NOT use solvents or thinners.
In case of eye contact	:	If symptoms persist, call a physician.
		In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If swallowed	:	If symptoms persist, call a physician.
		Do NOT induce vomiting.
		Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Sym	ptoms	:	Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Risk	S	:	May cause an allergic skin reaction.
			Harmful if inhaled.
			May cause respiratory irritation.
			May cause drowsiness or dizziness.
4.3 Indic	ation of any immediate m	ned	lical attention and special treatment needed
Trea	itment	:	No known specific antidote. Treat symptomatically.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing	:	Water spray jet
media		



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

		Dry powder Alcohol-resistant foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
<b>500</b> ···· · · · · ·		
5.2 Special hazards arising from		Fire will produce dense black smoke containing
fighting	•	hazardous combustion products (see section 10).
5.2. Advice for firefielders		
5.3 Advice for firefighters Special protective	:	Appropriate breathing apparatus may be required.
equipment for fire-fighters	•	
Further information	:	In the event of fire, cool tanks with water spray.
	•	
		Fire residues and contaminated fire extinguishing water



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Avoid breathing vapours.
		Keep away from sources of ignition.
		Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
		For non-emergency personnel:
		For emergency responders:
		Use personal protective equipment.
		Ensure adequate ventilation, especially in confined areas.



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

### 6.2 Environmental precautions

Environmental precautions :	Do not allow uncontrolled discharge of product into the environment.
	Avoid subsoil penetration.
	If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain and collect spillage with non-combustible
		absorbent materials, e.g. sand, earth, vermiculite,
		diatomaceous earth. Place in a suitable container. The
		contaminated area should be cleaned up immediately
		with a suitable decontaminant. One possible
		(flammable) decontaminant comprises (by volume):
		ethanol or isopropyl alcohol (50 parts); water (45 parts);
		concentrated ammonia solution (5 parts). A non-
		flammable alternative is: sodium carbonate (5 parts);
		water (95 parts). Add the same decontaminant to the
		remnants and let stand for several days until no further



### 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling	Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

application area. For personal protection see section 8. Comply with the health and safety at work laws.

		When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
		The workplace should be equipped with an emergency shower and eye-rinsing facility.
		Avoid contact with the skin, eyes and clothing.
		Handle in accordance with good industrial hygiene and safety practice.
		Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that



## 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures: Remove contaminated clothing immediately and dispose<br/>of safely. Wash hands before breaks and at the end of<br/>workday. Keep away from food, drink and animal<br/>feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on<br/>storage conditions: Keep away from heat. Avoid direct sunlight. Close<br/>containers carefully once opened and store them<br/>upright in order to prevent any leakage. No smoking. No<br/>admission for unauthorised personnel. Always keep in<br/>containers of same material as the original one. Observe<br/>label precautions. Store protected against freezing. Keep<br/>in a dry, cool and well-ventilated place.



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Advice on common storage	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage	:	5.00 - 35.00 °C
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)
		Suitable material: Stainless steel 1.4301 (V2)
		Suitable material: Stove-lacquer R 78433, Stove-lacquer EHD0022, Stove-lacquer RDL 50, Stove-lacquer C222A/C221A, Stove-lacquer 79/14/3 (Müller/CH), Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X
		Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP)



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

### 7.3 Specific end use(s)

- Specific use(s)
- : Please refer to the technical leaflet for further information.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Hexamethylen- 1,6-diisocyanat Homopolymer	28182-81-2	TWA	0.02 mg/m3 (NCO)	GB EH40	
	Further information: Capable of causing occupational asthma.				
		STEL	0.07 mg/m3 (NCO)	GB EH40	
	Further information: Capable of causing occupational asthma.			hma.	



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

1-methoxy-2- propylacetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
	Further info	l rmation: Can be ab	 sorbed through the skin. 1	he assigned
			there are concerns that d	-
	absorption v	vill lead to systemic	c toxicity.	
		STEL	100 ppm	GB EH40
			548 mg/m3	
	Further information: Can be absorbed through the skin. The assigned			
	substances a	are those for which	there are concerns that d	ermal
	absorption will lead to systemic toxicity.			
		STEL 100 ppm 2000/39/		
			550 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
		TWA	50 ppm	2000/39/EC
			275 mg/m3	
	Further information: Identifies the possibility of significant uptake			



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

	through the skin, Indicative			
n-Butyl acetate	123-86-4	TWA	150 ppm	GB EH40
			724 mg/m3	
		STEL	200 ppm	GB EH40
			966 mg/m3	
		STEL	150 ppm	2019/1831/
			723 mg/m3	EU
	Further information: Indicative			
		TWA 50 ppm 2019/18		
			241 mg/m3	EU
	Further information: Indicative			
xylene	1330-20-7	TWA	50 ppm	GB EH40
			220 mg/m3	
	Further infor	mation: Can be ab	sorbed through the skin.	The assigned
	substances are those for which there are concerns that dermal			



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

	absorption will lead to systemic toxicity.				
	STEL 100 ppm GB EH			GB EH40	
			441 mg/m3		
	Further info	rmation: Can be ab	sorbed through the skin.	The assigned	
	substances a	are those for which	there are concerns that d	ermal	
	absorption v	vill lead to systemi	c toxicity.		
	TWA         50 ppm         2000/39/EC				
			221 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the skin, Indicative				
		STEL	100 ppm	2000/39/EC	
			442 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the skin, Indicative				
ethylbenzene	100-41-4	TWA	100 ppm	GB EH40	
			441 mg/m3		



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.						
		STEL 125 ppm GB EH40					
		552 mg/m3					
	Further infor	mation: Can be ab	sorbed through the skin. T	he assigned			
	substances a	ire those for which	there are concerns that d	ermal			
	absorption v	vill lead to systemic	c toxicity.				
		TWA	100 ppm	2000/39/EC			
			442 mg/m3				
	Further information: Identifies the possibility of significant uptake						
	through the	skin, Indicative					
		STEL	200 ppm	2000/39/EC			
			884 mg/m3				
	Further information: Identifies the possibility of significant uptake						
	through the skin, Indicative						
isobutyl acetate	110-19-0	TWA	150 ppm	GB EH40			



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

		724 mg/m3			
	STEL	187 ppm	GB EH40		
		903 mg/m3			
	TWA	50 ppm	2019/1831/		
		241 mg/m3	EU		
Further i	Further information: Indicative				
	STEL	150 ppm	2019/1831/		
		723 mg/m3	EU		
Further i	Further information: Indicative				

### **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylen-1,6- diisocyanat Homopolymer	28182-81-2	isocyanate- derived diamine (Isocyanates): 1 μmol/mol creatinine	At the end of the period of exposure	GB EH40 BAT



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

		(Urine)		
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

### 8.2 Exposure controls

Engineering measures Ensure adequate ventilation.		
Personal protective equipmer	nt	
Eye/face protection	:	Safety glasses with side-shields conforming to EN166
		Required when there is a risk of eye contact.
Hand protection		
Remarks :	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on



### 922-138/320 180L

VersionRevision Da1.025.04.2025

Revision Date: SDS Number: 25.04.2025 0000000205 711

SDS Number:Date of last issue: -00000002050003Date of first issue: 25.04.2025

information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

synthetic fibres.

Respiratory protection	:	Suitable respiratory equipment:
		full face mask with AB2P3 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Persons with a history of allergies, asthma, recurrent or chronic respiratory disease must not be employed in any process in which this product is used. Persons using this product should undergo lung function tests at regular intervals.
		Respiratory protective equipment should be worn by spray booth operatives.
		Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily



### 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	pungent
рН	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
		115.00 - 195.00 °C
Flash point	÷	23 °C
		Method: ISO 3679
Upper explosion limit / Upper	:	not determined



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

flammability limit		
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	6.4000 hPa (20 °C)
		not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.022 g/cm3 (20 °C)
Solubility(ies) Water solubility Partition coefficient: n- octanol/water Autoignition temperature	::	not determined not applicable for mixtures > 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	not determined (40 °C) 7.3 mm2/s (23 °C)
Flow time	:	> 30 s



### 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

		Cross section: 3 mm
Explosive properties :	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
<b>9.2 Other information</b> Flammability (liquids) :	:	Flammable liquid and vapour.
Self-heating substances :	:	The substance or mixture is not classified as self heating.
Metal corrosion rate :	:	Not corrosive to metals.
Particle size :	:	The substance / product is marketed or used in a non solid or granular form.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

10.4 Conditions to avoid		
Conditions to avoid		Avoid direct sunlight.
		Protect from frost.
		Heat, flames and sparks.
		Heat.
10.5 Incompatible materials		
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity Harmful if inhaled.



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Product:		
Acute inhalation toxicity	:	Acute toxicity estimate: 18.88 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method

 Skin corrosion/irritation

 Based on available data, the classification criteria are not met.

 Components:

 n-Butyl acetate:

 Result
 : Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.



### 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

#### Product:

No aspiration toxicity classification



### 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

#### Hexamethylen-1,6-diisocyanat Homopolymer:

Partition coefficient: n- : log Pow: 9.81 (25 °C) octanol/water

#### 1-methoxy-2-propylacetate:

Partition coefficient: n-	:	log Pow: 1.2 (20 °C)
octanol/water		рН: 6.8

Method: OECD Test Guideline 117

GLP: yes

#### n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

octanol/water	log Pow: 2.3 (25 °C)			
	рН: 7			
	Method: OECD Test Guideline 117			
	GLP: yes			
xylene:				
Partition coefficient: n- :	log Pow: 3.12 - 3.20 (25 °C)			
octanol/water	GLP: no			
	Remarks: Information taken from reference works and the literature.			
ethylbenzene:				
	Pow: 4,170 (20 °C)			
octanol/water	log Pow: 3.6 (20 °C)			
	рН: 7.8			
	GLP: yes			



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

isobutyl acetate:		
Partition coefficient: n-	:	log Pow: 2.3 (25 °C)
octanol/water		рН: 7
		Method: OECD Test Guideline 117
		GLP: yes
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB as	sses	ssment
Product:		
Assessment	:	This substance/mixture contains no con

ent : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Product:



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Endocrine disrupting	:	This substance/mixture does not contain components
potential		considered to have endocrine disrupting properties for
		environment according to UK REACH Article 57(f).

## **SECTION 13: Disposal considerations**

13.1 Waste treatment methods		
Product		Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

## **SECTION 14:** Transport information

#### 14.1 UN number

ADN	: UN 1866
ADR	: UN 1866
RID	: UN 1866
IMDG	: UN 1866
ΙΑΤΑ	: UN 1866

### 14.2 UN proper shipping name

ADN	: RESIN SOLUTION
ADR	: RESIN SOLUTION
RID	: RESIN SOLUTION
IMDG	: RESIN SOLUTION
ΙΑΤΑ	: RESIN SOLUTION



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

## 14.3 Transport hazard class(es)

			Class	Subsidiary risks
ADN		:	3	
ADR		:	3	
RID		:	3	
IMDG		:	3	
ΙΑΤΑ		:	3	
14.4 Packing grou	up			
ADN				
Packing grou	qu	:	III	
Classification	n Code	:	F1	
Hazard Ident Number	tification	:	30	
Labels		:	3	



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

#### ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	Ш



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	Ш
Labels	:	Flammable Liquids
Labels IATA (Passenger)	:	Flammable Liquids
		Flammable Liquids
IATA (Passenger) Packing instruction	:	
IATA (Passenger) Packing instruction (passenger aircraft)	:	355
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ)	:	355 Y344 III

## 14.5 Environmental hazards



## 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000002050003 711	Date of first issue: 25.04.2025

## ADN

Environmentally hazardous	:	no
ADR		
Environmentally hazardous	:	no
RID		
Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



## 922-138/320 180L

VersionRevision Date:SDS Number:Date of last issue: -1.025.04.202500000002050003<br/>711Date of first issue: 25.04.2025

## **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

: Conditions of restriction for the following entries should be considered:

Number on list 3, 20

Number on list 3

UK REACH Candidate list of substances of very high : Not applicable concern (SVHC) for Authorisation



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

The Persistent Organic Polluta (retained Regulation (EU) 2019 for Great Britain)			
Regulation (EC) on substances ozone layer	: Not applicable		
UK REACH List of substances so authorisation (Annex XIV)	UK REACH List of substances subject to authorisation (Annex XIV)		
	P5c		
Control of Major Accident Haz Regulations 2015 (COMAH)	ards P5c	FLAMMABLE LIQUIDS	
Volatile organic : compounds		'EU of 24 November 2010 on is (integrated pollution prevention and	
	Volatile organic cor	mpounds (VOC) content: 50.66 %	



## 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

Volatile organic compounds (VOC) content: 517.74 g/l

VOC content excluding water

## Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped

#### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS



# 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

### **SECTION 16: Other information**

Full text of H-Statements		
H225	:	Highly flammable liquid and vapor.
H226	:	Flammable liquid and vapor.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated
		exposure.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## 922-138/320 180L

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency: EC-Number - European Community number: ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-



## 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information Other information	: For multi-pack systems all components. Restricted to professio	s observe material safety data sheets of nal users.
Classification of the mixt	ure:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not



# 922-138/320 180L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000002050003 711	Date of first issue: 25.04.2025

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN