

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	000000000503829 91	Date of first issue: 25.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	80-M 589K 0,5L Jeansblau 0,5L Plastic bottle
Product code	:	00000000050382991
Unique Formula Identifier (UFI)	:	SCX5-U0PE-000Q-1SGG

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Spraying Basecoat product
------------------------------	---	------------------------------

#### 1.3 Details of the supplier of the safety data sheet

**Company:**  
BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**  
BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

Long-term (chronic) aquatic hazard, Category 2      H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms	:	
Signal Word	:	Warning
Hazard Statements	:	H317      May cause an allergic skin reaction. H319      Causes serious eye irritation. H411      Toxic to aquatic life with long lasting effects.
Precautionary Statements	:	<b>Prevention:</b> P261      Avoid breathing mist or vapors. P273      Avoid release to the environment. P280      Wear protective gloves/ eye protection/ face protection.  <b>Response:</b> P333 + P313      If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313      If eye irritation persists: Get medical advice/ attention. P391      Collect spillage.

Hazardous ingredients which must be listed on the label:

| 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version 3.1      Revision Date: 17.12.2025      SDS Number: 0000000000503829      Date of last issue: 23.08.2025  
Date of first issue: 25.03.2024  
91

Chemical nature : polyurethane  
saturated polyester resin  
pigment  
organic solvent  
Water

### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	$\geq 5 - < 7$
2,4,7,9-Tetramethyldec-5-yne-4,7-diol	126-86-3 204-809-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	$\geq 2 - < 2.5$
3-(3-Isodecyloxypropylamino)propylamine	72162-46-0 276-432-0 UK-20-0537843089-5-0000	Acute Tox. 3; H301 Skin Corr. 1A; H314 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	$\geq 0.5 - < 1$
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 UK-20-0537843089-5-0000 UK-20-9642318150-	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314	$\geq 0.1 - < 0.2$

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version 3.1      Revision Date: 17.12.2025      SDS Number: 0000000000503829 91      Date of last issue: 23.08.2025      Date of first issue: 25.03.2024

	0-0000	Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	
Substances with a workplace exposure limit :			
copper phthalocyanine blue	147-14-8 205-685-1 01-2119458771-32		>= 15 - < 20
		specific concentration limit STOT SE 3; H335 >= 5 %	

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. Never give anything by mouth to an unconscious person.
- If inhaled : If symptoms persist, call a physician. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

If swallowed : If symptoms persist, call a physician.  
Do NOT induce vomiting.  
Rinse mouth.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Dry powder  
Foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	000000000503829 91	Date of first issue: 25.03.2024

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Cool containers/tanks with water spray.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

#### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.  
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5 - 40 °C

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version 3.1      Revision Date: 17.12.2025      SDS Number: 0000000000503829      Date of last issue: 23.08.2025  
Date of first issue: 25.03.2024  
91

Packaging material : Suitable material: Stainless steel 1.4301 (V2), Polypropylene, Polyethylenetherephthalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
copper phthalocyanine blue	147-14-8	TWA (Dusts and mists)	1 mg/m <sup>3</sup> (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m <sup>3</sup> (Copper)	GB EH40
2-butoxyethanol	111-76-2	TWA	25 ppm 123 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	50 ppm 246 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
2-dimethylaminoethanol	108-01-0	TWA	2 ppm 7.4 mg/m <sup>3</sup>	GB EH40
		STEL	6 ppm 22 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version 3.1      Revision Date: 17.12.2025      SDS Number: 0000000000503829      Date of last issue: 23.08.2025  
Date of first issue: 25.03.2024  
91

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm  
Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Request information on glove permeation properties from the glove supplier.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
Preventive skin protection  
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)  
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

of permeation time according to EN ISO 374-1):  
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres. chemical-resistant disposable coveralls

Respiratory protection : Suitable respiratory equipment:  
half-mask with A1P2 class combination filter  
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective measures : Do not breathe vapour/spray.  
Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: blue
Odor	: No data available
pH	: 7.1 - 7.8

substance/mixture is non-polar/aprotic

Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: > 70 °C Method: ISO 3679
Upper explosion limit / Upper flammability limit	: not determined

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

---

Lower explosion limit / Lower flammability limit : > 35 g/m<sup>3</sup>

Vapor pressure : not determined (20 °C)  
not determined (50 °C)

Relative vapor density : Lighter than air.

Density : 1.085 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : not determined  
Partition coefficient: n-octanol/water : not applicable for mixtures  
Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, kinematic : not determined (40 °C)  
196.5 mm<sup>2</sup>/s (23 °C)

Flow time : > 60 s at 23 °C  
Cross section: 5 mm  
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Flammability (liquids) : Combustible liquid.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reactions when stored and handled according to instructions.

#### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost.  
Heat, flames and sparks.  
Avoid direct sunlight.  
Heat.

#### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

##### Components:

| 2-butoxyethanol:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

Acute oral toxicity : LD50 (guinea pig): 1,200 mg/kg

### **2-dimethylaminoethanol:**

Acute oral toxicity : LD50 (Rat): 1,183 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 1,219 mg/kg

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration toxicity**

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **3-(3-Isodecyloxypropylamino)propylamine:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

##### Components:

##### **2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81 (25 °C)  
GLP: no

##### **2,4,7,9-Tetramethyldec-5-yne-4,7-diol:**

Partition coefficient: n-octanol/water : log Pow: 2.64

##### **3-(3-Isodecyloxypropylamino)propylamine:**

Partition coefficient: n-octanol/water : log Pow: 2.7 (23 °C)  
pH: 7.9 - 8.3  
Method: OECD Test Guideline 107  
GLP: no

##### **2-dimethylaminoethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.55 (23 °C)

##### **copper phthalocyanine blue:**

Partition coefficient: n-octanol/water : log Pow: -1.0 (23 °C)

#### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 3082

ADR : UN 3082

RID : UN 3082

IMDG : UN 3082

IATA : UN 3082

### 14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(3-(3-Isodecyloxypropylamino)propylamine)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version 3.1      Revision Date: 17.12.2025      SDS Number: 0000000000503829      Date of last issue: 23.08.2025  
Date of first issue: 25.03.2024  
91

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(3-(3-Isodecyloxypropylamino)propylamine)

**RID** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(3-(3-Isodecyloxypropylamino)propylamine)

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(3-(3-Isodecyloxypropylamino)propylamine)

**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(3-(3-Isodecyloxypropylamino)propylamine)

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 9	
<b>ADR</b>	: 9	
<b>RID</b>	: 9	
<b>IMDG</b>	: 9	
<b>IATA</b>	: 9	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9

**ADR**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)

**RID**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9

**IMDG**  
Packing group : III

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

Labels : 9  
EmS Code : F-A, S-F

### IATA (Cargo)

Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous dangerous goods

### IATA (Passenger)

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous dangerous goods

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : yes

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA (Passenger)

Environmentally hazardous : yes

#### IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829 91	Date of first issue: 25.03.2024

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations E2 2015 (COMAH) ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 6.7 %

Volatile organic compounds (VOC) content: 159.16 g/l  
VOC content excluding water

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:	d
Limit value for maximum VOC content as specified in Annex IIB:	420 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	419 g/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829	Date of first issue: 25.03.2024
		91	

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

### SECTION 16: Other information

#### Full text of H-Statements

H226	: Flammable liquid and vapor.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	0000000000503829	Date of first issue: 25.03.2024
		91	

Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

### Classification of the mixture:

Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

### Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 80-M 589K 0,5L Jeansblau 0,5L Plastic bottle

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.1	17.12.2025	000000000503829 91	Date of first issue: 25.03.2024

---

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN