

# Safety data sheet

Page: 1/17

---

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

---

## 1. Identification

### Product identifier

## **929-91 0.5L HS FAST HARDENER G2**

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: hardener

### Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH  
Postfach 6123  
48136 Muenster  
Deutschland

Telephone: +49/2501/143688

E-mail address: product-safety-coatings@basf.com

### Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## 2. Hazards Identification

### Classification of the substance or mixture

According to UN GHS criteria

---

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

---

Skin Corr./Irrit. 2  
Eye Dam./Irrit. 2A  
Asp. Tox. 1  
Skin Sens. 1  
STOT SE 3 (May cause drowsiness and dizziness.)  
STOT SE 3 (irritating to respiratory system)  
Aquatic Acute 3  
Flam. Liq. 3  
STOT RE 2  
Acute Tox. 4 (Inhalation - vapour)  
Carc. 2

For the classifications not written out in full in this section the full text can be found in section 16.

## Label elements

Globally Harmonized System, UN (GHS)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.

Precautionary Statements (Prevention):

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P201	Obtain special instructions before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P260	Do not breathe dust or mist.
P202	Do not handle until all safety precautions have been read and understood.
P240	Ground and bond container and receiving equipment.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.

**Precautionary Statements (Response):**

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P331	Do NOT induce vomiting.
P314	Get medical advice/attention if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.

**Precautionary Statements (Storage):**

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

**Precautionary Statements (Disposal):**

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

**Other hazards**According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

### 3. Composition/Information on Ingredients

#### Substances

Not applicable

#### Mixtures

##### Chemical nature

organic solvent

##### Hazardous ingredients (GHS)

According to UN GHS criteria

Hexamethylen-1,6-diisocyanat Homopolymer

Content (W/W):  $\geq 30\%$  -  $< 50\%$ 

CAS Number: 28182-81-2

EC-Number: 500-060-2

REACH registration number: 01-

2119485796-17

Acute Tox. 4 (Inhalation - dust)

Acute Tox. 4 (Inhalation - vapour)

Skin Sens. 1

STOT SE 3 (irr. to respiratory syst.)

H332, H317, H335

n-Butyl acetate

Content (W/W):  $\geq 20\%$  -  $< 25\%$ 

CAS Number: 123-86-4

EC-Number: 204-658-1

INDEX-Number: 607-025-00-1

Flam. Liq. 3

STOT SE 3 (drowsiness and dizziness)

Aquatic Acute 3

H226, H336, H402

EUH066

4-Methylpentan-2-one

Content (W/W):  $\geq 10\%$  -  $< 12,5\%$ 

CAS Number: 108-10-1

EC-Number: 203-550-1

INDEX-Number: 606-004-00-4

Asp. Tox. 2

Flam. Liq. 2

Acute Tox. 4 (Inhalation - vapour)

Acute Tox. 5 (oral)

Eye Irrit. 2A

Carc. 2

STOT SE 3 (drowsiness and dizziness)

STOT SE 3 (irr. to respiratory syst.)

H225, H319, H332, H303, H305, H336, H335,

H351

EUH066

Isobutyl acetate

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

Content (W/W): $\geq 10\%$ - $< 12,5\%$	Flam. Liq. 2
CAS Number: 110-19-0	STOT SE 3 (drowsiness and dizziness)
EC-Number: 203-745-1	Aquatic Acute 3
INDEX-Number: 607-026-00-7	H225, H336, H402
	EUH066

## Xylene

Content (W/W): $\geq 7\%$ - $< 10\%$	Asp. Tox. 1
CAS Number: 1330-20-7	Flam. Liq. 3
EC-Number: 215-535-7	Acute Tox. 5 (Inhalation - vapour)
INDEX-Number: 601-022-00-9	Acute Tox. 5 (oral)
	Skin Irrit. 2
	Eye Irrit. 2B
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Chronic 3
	STOT RE (Central nervous system, Liver, Kidney) 2
	Aquatic Acute 2
	H226, H320, H315, H304, H335, H373, H303 + H333, H412, H401

## 2-Methoxy-1-methylethyl acetate

Content (W/W): $\geq 2,5\%$ - $< 3\%$	Flam. Liq. 3
CAS Number: 108-65-6	STOT SE 3 (drowsiness and dizziness)
EC-Number: 203-603-9	H226, H336
INDEX-Number: 607-195-00-7	

## Ethylbenzene

Content (W/W): $\geq 1\%$ - $< 2\%$	Asp. Tox. 1
CAS Number: 100-41-4	Flam. Liq. 2
EC-Number: 202-849-4	Acute Tox. 4 (Inhalation - vapour)
INDEX-Number: 601-023-00-4	Acute Tox. 5 (oral)
	STOT RE (Auditory organ) 2
	Aquatic Acute 2
	Aquatic Chronic 3
	H225, H332, H303, H304, H373, H412, H401

## Benzoic acid

Content (W/W): $\geq 1\%$ - $< 2\%$	Acute Tox. 5 (oral)
CAS Number: 65-85-0	Skin Corr./Irrit. 2
EC-Number: 200-618-2	Eye Dam./Irrit. 1
	STOT RE (Lung) 1 (by inhalation)
	H318, H315, H303, H372

## p-Toluenesulphonyl isocyanate

Content (W/W): $\geq 0,2\%$ - $< 0,3\%$	Acute Tox. 5 (oral)
CAS Number: 4083-64-1	Skin Irrit. 2
EC-Number: 223-810-8	Eye Irrit. 2A
REACH registration number: 01-2119980050-47	STOT SE 3 (irr. to respiratory syst.)
INDEX-Number: 615-012-00-7	Resp. Sens. 1
	Aquatic Acute 3
	H319, H315, H303, H334, H335, H402
	EUH014
	EUH204
	<u>Specific concentration limit:</u>
	Skin Corr./Irrit. 2: $\geq 5\%$
	STOT SE 3, irr. to respiratory syst.: $\geq 5\%$
	Eye Dam./Irrit. 2: $\geq 5\%$

**Dibutyltin dilaurate**

Content (W/W): $\geq 0,1\%$ - $< 0,2\%$	Acute Tox. 5 (oral)
CAS Number: 77-58-7	Eye Irrit. 2A
EC-Number: 201-039-8	Skin Sens. 1
INDEX-Number: 050-030-00-3	Muta. 2
	Repr. 1B (fertility)
	Repr. 1B (unborn child)
	STOT SE (Thymus gland) 1
	STOT RE (Immune system) 1
	Aquatic Acute 1
	Aquatic Chronic 1
	M-factor acute: 1
	M-factor chronic: 1
	H319, H303, H317, H341, H360, H370, H372, H400, H410

For the classifications not written out in full in this section the full text can be found in section 16.

---

## 4. First-Aid Measures

### Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

#### If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

#### On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

### **Most important symptoms and effects, both acute and delayed**

Symptoms: Eye irritation, aspiration pneumonia, allergic symptoms, dazed state, irritation of respiratory tract, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Antidote: No known specific antidote.

---

## **5. Fire-Fighting Measures**

### **Extinguishing media**

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### **Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

### **Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## **6. Accidental Release Measures**

### **Personal precautions, protective equipment and emergency procedures**

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

### **Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### **Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13). Ensure adequate ventilation.

---

## **7. Handling and Storage**

### **Precautions for safe handling**

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

### **Conditions for safe storage, including any incompatibilities**

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability:



Storage temperature: 5,00 - 35,00 °C

### Specific end use(s)

Please refer to the technical leaflet for further information.

---

## 8. Exposure Controls/Personal Protection

### Control parameters

#### Components with occupational exposure limits

100-41-4: Ethylbenzene  
108-10-1: 4-Methylpentan-2-one  
108-65-6: 2-Methoxy-1-methylethyl acetate  
110-19-0: Isobutyl acetate  
123-86-4: n-Butyl acetate  
1330-20-7: Xylene

### Exposure controls

#### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. full face mask with AB2P3 class combination filter

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Eye protection:

Eye protection not required.

Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

#### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

## 9. Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	of acetate	
Melting point:		
	not determined	
onset of boiling:	135 °C	(calculated)
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m <sup>3</sup>	
Flash point:	> 23 °C	(ISO 3679)
Auto-ignition temperature:	> 200,00 °C	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:		
	substance/mixture is non-polar/aprotic	
Viscosity, kinematic:		
	(40 °C)	
	No data available.	
	6,0 mm <sup>2</sup> /s	
	(23 °C)	
Solubility in water:	immiscible	
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures	
Vapour pressure:	6,00 hPa	(calculated)
	(20 °C)	
	(50 °C)	
	not determined	
Density:	0,970 g/cm <sup>3</sup>	
	(20 °C)	
Relative vapour density (air):	Heavier than air.	

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosives

Explosion hazard: not explosive

##### Oxidizing properties

Fire promoting properties: not fire-propagating

##### Flammable solids

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready specified in paragraph 33.2.4.4 of UN manual of tests and criteria. combustible solids))

##### Self-heating substances and mixtures

Self heating ability: It is not a material capable of spontaneous heating

**Other safety characteristics**

Miscibility with water:

immiscible

Flow time:

&lt; 30 s

(23 °C)

(DIN EN ISO 2431; 3 mm)

**10. Stability and Reactivity****Reactivity**

No hazardous reactions if stored and handled as prescribed/indicated.

**Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

**Possibility of hazardous reactions**

Vapours may form ignitable mixture with air.

**Conditions to avoid**

Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

**Incompatible materials**

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

**Hazardous decomposition products**

:

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

**11. Toxicological Information****Information on toxicological effects**Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of

consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Of moderate toxicity after short-term inhalation.

*Information on: 4-Methylpentan-2-one*

*Experimental/calculated data:*

*LC50 rat (by inhalation): 11,6 mg/l 4 h (similar to OECD guideline 403)*

*The vapour was tested.*

*Information on: Hexamethylen-1,6-diisocyanat Homopolymer*

*Experimental/calculated data:*

*LC50 rat (by inhalation): 1,500 mg/l 4,0 h (OECD Guideline 403)*

*An aerosol was tested.*

#### Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes irritation.

#### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

#### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

Indication of possible carcinogenic effect in animal tests.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

#### Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:  
Repeated exposure may affect certain organs.

#### Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

#### Other relevant toxicity information

Based on the properties of the isocyanate components and considering toxicological data on similar product, this product may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.

---

## 12. Ecological Information

### Toxicity

Assessment of aquatic toxicity:  
Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):  
Biological degradability of hazardous substances mentioned in section 3:

*Information on: Dibutyltin dilaurate*

*Elimination information:*

*23 % BOD of the ThOD (39 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (anaerobic, activated sludge, domestic)*

*Information on: Ethylbenzene*

*Elimination information:*

*70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).*

*Information on: Isobutyl acetate*

*Elimination information:*

*74 % BOD of the ThOD (10 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, domestic sewage, non-adapted)*

*Information on: n-Butyl acetate*

*Elimination information:*

---

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

*80 % BOD of the ThOD (5 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, municipal sewage treatment plant effluent)*

*Information on: Xylene*

*Elimination information:*

*87,8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: p-Toluenesulphonyl isocyanate*

*Elimination information:*

*86 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, activated sludge, domestic, non-adapted)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### **Bioaccumulative potential**

Bioaccumulation potential:

No data available.

### **Mobility in soil**

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

---

## **13. Disposal Considerations**

### **Waste treatment methods**

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Residues in empty containers should be neutralised with decontaminant (see section 6).

---

## **14. Transport Information**

### **Land transport**

ADR

---

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

UN number or ID number: UN1263  
UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: Tunnel code: D/E

#### RID

UN number or ID number: UN1263  
UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

#### **Inland waterway transport**

##### ADN

UN number or ID number: UN1263  
UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

#### Transport in inland waterway vessel

Not evaluated

#### **Sea transport**

##### IMDG

UN number or ID number: UN 1263  
UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: Marine pollutant: NO  
EmS: F-E; S-E

#### **Air transport**

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

IATA/ICAO

UN number or ID number: UN 1263  
UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: No Mark as dangerous for the environment is needed  
Special precautions for user: None known

### Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

## 15. Regulatory Information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

## 16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Asp. Tox.	Aspiration hazard
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Flam. Liq.	Flammable liquids
STOT RE	Specific target organ toxicity — repeated exposure
Acute Tox.	Acute toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Skin Irrit.	Skin irritation
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Resp. Sens.	Respiratory sensitization
Muta.	Germ cell mutagenicity
Repr.	Reproductive toxicity
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H303	May be harmful if swallowed.



---

 Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.06.2024

Version: 8.0

Product: **929-91 0.5L HS FAST HARDENER G2**

(ID no. 50411435/SDS\_GEN\_00/EN)

Date of print 25.06.2024

H305	May be harmful if swallowed and enters airways.
H351	Suspected of causing cancer.
H320	Causes eye irritation.
H315	Causes skin irritation.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
H303 + H333	May be harmful if swallowed or if inhaled.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.
H318	Causes serious eye damage.
H372	Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation).
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H360	May damage fertility. May damage the unborn child.
H370	Causes damage to organs (Thymus gland).
H372	Causes damage to organs (Immune system) through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH014	Reacts violently with water.
EUH204	Contains isocyanates. May produce an allergic reaction.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

 Vertical lines in the left hand margin indicate an amendment from the previous version.