According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 98-M 319 0.5L RUBY RED G2 0,5L Metal can

Product code : 00000000050411913

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture

Basecoat product

1.3 Details of the supplier of the safety data sheet

Company: Contact address:

BASF Coatings GmbH BASF plc

Postfach 6123 4th and 5th Floors, 2 Stockport Exchange 48136 Münster Railway Road, Stockport, SK1 3GG

Deutschland United Kingdom

Telephone: +44 161 475 3000

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single

exposure, Category 3, Central

H336: May cause drowsiness or dizziness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

nervous system

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: 3.0 10.03.2025

SDS Number: 0000000000050411

Date of last issue: 07.01.2025

913

Date of first issue: 20.10.2023

Precautionary Statements Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Hazardous ingredients which must be listed on the label:

butan-2-ol

propylene glycol monoethyl ether

2,4,7,9-Tetramethyldec-5-yne-4,7-diol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

polyurethane

pigment

Components

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Chemical name CAS-No. Classification Concentratio n (% w/w) EC-No. Index-No. Registration number 2-butoxyethanol 111-76-2 >= 20 - < 25 Acute Tox. 4; H302 203-905-0 Acute Tox. 4; 603-014-00-0 H332 UK-20-Skin Irrit. 2; H315 9702550300-0-Eye Irrit. 2; H319 0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

butan-2-ol	78-92-2	Flam. Liq. 3; H226	>= 12.5 - < 15
	201-158-5	Eye Irrit. 2; H319	
	603-127-00-5	STOT SE 3; H336	
	UK-20- 0537843089-5- 0000	(Central nervous system) STOT SE 3; H335	
	UK-20- 9642318150-0- 0000	(Respiratory system)	
propylene glycol monoethyl ether	1569-02-4	Flam. Liq. 3; H226	>= 10 - < 12.5
	216-374-5	STOT SE 3; H336	
	603-177-00-8	(Central nervous	
	01-2119462792-32	system)	
2,4,7,9-Tetramethyldec-5-yne-4,7-	126-86-3	Eye Dam. 1; H318	>= 3 - < 5
diol	204-809-1	Skin Sens. 1B;	
	UK-20-	H317	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

	9702550300-0- 0000	Aquatic Chronic 3; H412	
	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		
2-dimethylaminoethanol	108-01-0	Flam. Liq. 3; H226	>= 0.5 - < 1
	203-542-8	Acute Tox. 4;	
	603-047-00-0	H302	
	UK-20- 0537843089-5-	Acute Tox. 3; H331	
	0000	Acute Tox. 4;	
	UK-20-	H312	
	9642318150-0-	Skin Corr. 1B;	
	0000	H314	
		Eye Dam. 1; H318	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

		STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 5 %	
Substances with a workplace ex	posure limit :		
aluminium oxide	1344-28-1 215-691-6 UK-20- 9702550300-0- 0000		>= 12.5 - < 15

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

	UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	
diiron trioxide	1309-37-1 215-168-2 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	>= 10 - < 12.5

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own

safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek

medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.

If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : If symptoms persist, call a physician.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date:

SDS Number:

Date of last issue: 07.01.2025

3.0 10.03.2025

00000000050411 913

Date of first issue: 20.10.2023

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Do NOT use solvents or thinners.

In case of eye contact

: Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : If symptoms persist, call a physician.

Do NOT induce vomiting.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Symptoms : Information, i.e. additional information on symptoms

and effects may be included in the GHS labeling phrases

available in Section 2 and in the Toxicological

assessments available in Section 11.

Risks : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing : Water spray jet

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

media Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing

fighting hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.

equipment for fire-fighters

Further information : In the event of fire, cool tanks with water spray.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7

and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

areas.

6.2 Environmental precautions

Environmental precautions: Do not allow uncontrolled discharge of product into the

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

section 13).

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the

exposure limits.

The workplace should be equipped with an emergency

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date:

SDS Number: 0000000000050411

Date of last issue: 07.01.2025

3.0 10.03.2025

913

Date of first issue: 20.10.2023

shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion

: Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form

explosive mixtures with air.

Hygiene measures

: Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions

: Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a

dry, cool and well-ventilated place.

Advice on common storage: Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic

reactions.

Packaging material : Suitable material: Low density polyethylene (LDPE),

Polyethylenetherephtalate (PET), Polypropylene, Stainless steel 1.4301 (V2), Carbon steel (Iron), High density polyethylene (HDPE), tinned carbon steel

(Tinplate)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further

information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
2-butoxyethanol	111-76-2	TWA	25 ppm	GB EH40	
			123 mg/m3		
	Further information: Can be absorbed through the skin. The assigned				
	substances are those for which there are concerns that dermal				
	absorption will lead to systemic toxicity.				
		STEL	50 ppm	GB EH40	
			246 mg/m3		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

	substances a	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 98 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
butan-2-ol	78-92-2	TWA	100 ppm 308 mg/m3	GB EH40	
		STEL	150 ppm 462 mg/m3	GB EH40	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

aluminium oxide	1344-28-1	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
diiron trioxide	1309-37-1	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
2- dimethylaminoet hanol	108-01-0	TWA	2 ppm 7.4 mg/m3	GB EH40
		STEL	6 ppm 22 mg/m3	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove

certified according to EN ISO 374-1 is suitable: e.g.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 Date of first issue: 20.10.2023

913 Date of first issue: 20.10.2023

nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 Date of first issue: 20.10.2023

913 Date of first issue: 20.10.2023

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant

synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits,

appropriate certified respirators must be worn.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Color : red

Odor : of glycol

pH : 6.0 - 9.0

Concentration: 500.00000 g/l

Melting point/ range : not determined

Boiling point/boiling range : not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 913 Date of first issue: 20.10.2023

515

Flash point : 36 °C

Method: ISO 3679

Evaporation rate : not determined

Upper explosion limit / Upper flammability limit

: not determined

Lower explosion limit /

Lower flammability limit

: > 35 g/m

Vapor pressure : (20 °C)

not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date:

SDS Number:

Date of last issue: 07.01.2025

3.0 10.03.2025

00000000050411 913

Date of first issue: 20.10.2023

(50 °C)

not determined

Relative vapor density : Heavier than air.

Density : 1.140 g/cm3 (20 °C)

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition : No decomposition if stored and handled as

temperature prescribed/indicated.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 544.9 mm2/s (23 °C)

(40 °C)

not determined

Flow time : 80 s at 23 °C

Cross section: 6 mm

Method: ISO 2431

Explosive properties : Not explosive

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 Date of first issue: 20.10.2023

913 Date of first issue: 20.10.2023

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 (guinea pig): 1,200 mg/kg

2-dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1,183 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6.1 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Exposure time: 4 h

Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 1,219 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: n- : log Pow: 0.81 (25 °C)

octanol/water

GLP: no

butan-2-ol:

Partition coefficient: n- : log Pow: 0.61

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

octanol/water GLP: no

Remarks: Information taken from reference works and

the literature.

propylene glycol monoethyl ether:

Partition coefficient: n- : log Pow: 0 (20 °C)

octanol/water

pH: 7

2,4,7,9-Tetramethyldec-5-yne-4,7-diol:

Partition coefficient: n- : log Pow: 2.64

octanol/water

2-dimethylaminoethanol:

Partition coefficient: n- : log Pow: -0.55 (23 °C)

octanol/water

12.4 Mobility in soil

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for

environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface

waters/groundwater.

Observe national and local legal requirements.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Contaminated packaging : Containers which are not properly emptied must be

disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed

of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 913 Date of first issue: 20.10.2023

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

IMDG : PAINT

IATA : PAINT

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3

ADR : 3

RID : 3

IMDG : 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

IATA : 3

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

SDS Number: Date of last issue: 07.01.2025 Version **Revision Date:**

3.0 10.03.2025 00000000050411 Date of first issue: 20.10.2023

913

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411 Date of first issue: 20.10.2023

913 Date of first issue: 20.10.2023

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355

(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable liquid

14.5 Environmental hazards

ADN

Environmentally : no

hazardous

ADR

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Environmentally : no

hazardous

RID

Environmentally : no

hazardous

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Date of last issue: 07.01.2025 Version Revision Date: SDS Number:

3.0 10.03.2025 00000000050411

Date of first issue: 20.10.2023 913

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered:

Number on list 3

UK REACH Candidate list of substances of very high :

concern (SVHC) for Authorisation

Not applicable

: Not applicable

The Persistent Organic Pollutants Regulations

(retained Regulation (EU) 2019/1021 as amended

for Great Britain)

Regulation (EC) on substances that deplete the

: Not applicable

ozone layer

UK REACH List of substances subject to : Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

authorisation (Annex XIV)

Control of Major Accident Hazards P5c FLAMMABLE LIQUIDS

Regulations 2015 (COMAH)

Volatile organic : Volatile organic compounds (VOC) content: 545 g/l

compounds

Directive 2010/75/EU of 24 November 2010 on

industrial emissions (integrated pollution prevention and

control)

Volatile organic compounds (VOC) content: 47.52 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

(requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

Limit value for maximum VOC content as specified in Annex IIB: 420 g/l VOC content of the ready-for-use product according to ISO 11890-2: 419 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H336 : May cause drowsiness or dizziness.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Skin Corr. : Skin corrosion

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitization

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a

first list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours

2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data

sheets of all components.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

Restricted to professional users.

Classification of the mixture:		Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	
STOT SE 3	H336	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



98-M 319 0.5L RUBY RED G2 0,5L Metal can

Version Revision Date: SDS Number: Date of last issue: 07.01.2025

3.0 10.03.2025 00000000050411

913 Date of first issue: 20.10.2023

GB/EN