

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 00000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums  
Product code : 00000000050414588

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying  
Coatings and related products

#### 1.3 Details of the supplier of the safety data sheet

**Company:**

BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

---

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

---

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry




## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                    |                                 |
|---------|----------------|--------------------|---------------------------------|
| Version | Revision Date: | SDS Number:        | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 000000000050414588 | Date of first issue: 22.03.2024 |

|  |  |
|--|--|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapor.                      |
| Skin sensitization, Category 1   | H317: May cause an allergic skin reaction.             |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects. |

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

|                          |   |   |
|--------------------------|---|---|
| Hazard pictograms        | : |     |
| Signal Word              | : | Warning   |
| Hazard Statements        | : | H226 Flammable liquid and vapor.<br>H317 May cause an allergic skin reaction.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H411 Toxic to aquatic life with long lasting effects.   |
| Precautionary Statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P261 Avoid breathing mist or vapors.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><b>Response:</b><br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.<br>P391 Collect spillage. |

Hazardous ingredients which must be listed on the label:

n-Butyl acetate  
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 0000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

xylene  
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : acrylic resin  
organic solvent  
fillers

#### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| n-Butyl acetate  | 123-86-4<br>204-658-1<br>607-025-00-1                 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)   | >= 15 - < 20             |
| Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0) | 64742-95-6<br>918-668-5                               | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411 | >= 10 - < 12.5           |
| xylene   | 1330-20-7<br>215-535-7<br>601-022-00-9                | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319   | >= 7 - < 10              |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 0000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

|  |                                       |   |                  |
|--|---------------------------------------|---|------------------|
|  |                                       | STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>(Kidney, Liver, Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412 |                  |
| propylbenzene  | 103-65-1<br>203-132-9                 | Flam. Liq. 3; H226<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2; H411   | $\geq 5 - < 7$   |
| 2-heptanone  | 110-43-0<br>203-767-1<br>606-024-00-3 | Flam. Liq. 3; H226<br>Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>STOT SE 3; H336<br>(Central nervous system)   | $\geq 3 - < 5$   |
| 1-methoxy-2-propylacetate  | 108-65-6<br>203-603-9<br>607-195-00-7 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)   | $\geq 2.5 - < 3$ |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5<br>915-687-0             | Skin Sens. 1A; H317<br>Repr. 2; H361f<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410   | $\geq 2 - < 2.5$ |
| ethylbenzene   | 100-41-4<br>202-849-4<br>601-023-00-4 | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>(Auditory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412                      | $\geq 1 - < 2$   |
| Substances with a workplace exposure limit :   |                                       |   |                  |
| talc   | 14807-96-6<br>238-877-9               |   | $\geq 15 - < 20$ |

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). In all cases of doubt, or when symptoms persist, seek medical attention.  
First aid personnel should pay attention to their own safety.  
Immediately remove contaminated clothing.  
Move out of dangerous area.  
Never give anything by mouth to an unconscious person.
- If inhaled : If symptoms persist, call a physician.  
  
If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Do NOT use solvents or thinners.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If symptoms persist, call a physician.
- If swallowed : If symptoms persist, call a physician.  
Do NOT induce vomiting.  
Rinse mouth.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
- Risks : When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.  
Risk of product entering the lungs on vomiting after ingestion.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry powder  
Carbon dioxide (CO<sub>2</sub>)  
Water spray  
Foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.  
For non-emergency personnel:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapors or spray mist.  
Handle in accordance with good industrial hygiene and safety practice.  
Avoid contact with the skin, eyes and clothing.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
Smoking, eating and drinking are forbidden in application areas. For personal protection see section 8. Comply with the health and safety at work laws.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 00000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

Advice on protection against fire and explosion : Do not return residues to the storage containers. Provide good ventilation of working area (local exhaust ventilation if necessary).  
Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

Hygiene measures : The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.  
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components      | CAS-No.  | Value type (Form of exposure) | Control parameters               | Basis   |
|-----------------|----------|-------------------------------|----------------------------------|---------|
| n-Butyl acetate | 123-86-4 | TWA                           | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40 |
|                 |          | STEL                          | 200 ppm                          | GB EH40 |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

|             |  |                       |                                  |                  |
|-------------|--|-----------------------|----------------------------------|------------------|
|             |  |                       | 966 mg/m <sup>3</sup>            |                  |
|             |  | STEL                  | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|             | Further information: Indicative  |                       |                                  |                  |
|             |  | TWA                   | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|             | Further information: Indicative  |                       |                                  |                  |
| talc        | 14807-96-6   | TWA (Respirable dust) | 1 mg/m <sup>3</sup>              | GB EH40          |
| xylene      | 1330-20-7  | TWA                   | 50 ppm<br>220 mg/m <sup>3</sup>  | GB EH40          |
|             | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |                  |
|             |  | STEL                  | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40          |
|             | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |                  |
|             |  | TWA                   | 50 ppm<br>221 mg/m <sup>3</sup>  | 2000/39/EC       |
|             | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                       |                                  |                  |
|             |  | STEL                  | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC       |
|             | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                       |                                  |                  |
| 2-heptanone | 110-43-0   | STEL                  | 100 ppm<br>475 mg/m <sup>3</sup> | GB EH40          |
|             | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |                  |
|             |  | TWA                   | 50 ppm<br>237 mg/m <sup>3</sup>  | GB EH40          |
|             | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |                  |
|             |  | TWA                   | 50 ppm<br>238 mg/m <sup>3</sup>  | 2000/39/EC       |
|             | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                       |                                  |                  |
|             |  | STEL                  | 100 ppm<br>475 mg/m <sup>3</sup> | 2000/39/EC       |
|             | Further information: Identifies the possibility of significant uptake through the  |                       |                                  |                  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

|                           |  |      |                                  |            |
|---------------------------|--|------|----------------------------------|------------|
|                           | skin, Indicative   |      |                                  |            |
| 1-methoxy-2-propylacetate | 108-65-6   | TWA  | 50 ppm<br>274 mg/m <sup>3</sup>  | GB EH40    |
|                           | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                           |  | STEL | 100 ppm<br>548 mg/m <sup>3</sup> | GB EH40    |
|                           | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                           |  | STEL | 100 ppm<br>550 mg/m <sup>3</sup> | 2000/39/EC |
|                           | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
|                           |  | TWA  | 50 ppm<br>275 mg/m <sup>3</sup>  | 2000/39/EC |
|                           | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
| ethylbenzene              | 100-41-4   | TWA  | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40    |
|                           | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                           |  | STEL | 125 ppm<br>552 mg/m <sup>3</sup> | GB EH40    |
|                           | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                           |  | TWA  | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC |
|                           | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
|                           |  | STEL | 200 ppm<br>884 mg/m <sup>3</sup> | 2000/39/EC |
|                           | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |

### Biological occupational exposure limits

| Substance name | CAS-No.   | Control parameters   | Sampling time | Basis          |
|----------------|-----------|--|---------------|----------------|
| xylene         | 1330-20-7 | methyl hippuric acid: 650 Millimoles per mole creatinine (Urine) | After shift   | GB EH40<br>BAT |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145 | Date of first issue: 22.03.2024 |
|         |                | 88               |                                 |

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm  
Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Request information on glove permeation properties from the glove supplier.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
Preventive skin protection  
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)  
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):  
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Anti-static protective clothing  
Personnel should wear antistatic, flame-retardant clothing

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

---

|                        |   |  |
|------------------------|---|--|
| Respiratory protection | : | made of natural fibres and/or heat-resistant synthetic fibres.<br>Suitable respiratory equipment:<br>half-mask with A2P2 class combination filter<br>In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.<br>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.                   |
| Protective measures    | : | Do not breathe vapour/spray.<br>Eye wash fountains and safety showers must be easily accessible.<br><br>If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.<br><br>Avoid contact with the skin, eyes and clothing.<br>Handle in accordance with good industrial hygiene and safety practice. |

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|                               |   |  |
|-------------------------------|---|--|
| Physical state                | : | liquid                                 |
| Appearance                    | : | liquid                                 |
| Color                         | : | various                                |
| Odor                          | : | hydrocarbon-like                       |
| pH                            | : | substance/mixture is non-polar/aprotic |
| Melting point/freezing point  | : | not determined                         |
| Boiling point/boiling range   | : | not determined                         |
| Flash point                   | : | > 23 °C<br>Method: ISO 3679            |
| Flammability                  | : | Flammable liquid and vapour.           |
| Sustained combustibility      | : | Sustains combustibility: yes           |
| Upper explosion limit / Upper | : | not determined                         |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

flammability limit

Lower explosion limit / Lower flammability limit : > 35 g/m<sup>3</sup>

Vapor pressure : not determined (20 °C)  
not determined (50 °C)

Density : 1.000 g/cm<sup>3</sup> (20 °C)

Solubility(ies)

Water solubility : not determined  
Partition coefficient: n-octanol/water : not applicable for mixtures  
Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)  
411.6 mm<sup>2</sup>/s (23 °C)

Flow time : > 60 s at 23 °C  
Cross section: 6 mm  
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 00000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.  
Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

### Components:

#### **2-heptanone:**

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

### Components:

#### **n-Butyl acetate:**

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)  
log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

##### **Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):**

Partition coefficient: n-octanol/water : log Pow: 3.17  
GLP: no

##### **xylene:**

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)  
GLP: no  
Remarks: Information taken from reference works and the literature.

##### **propylbenzene:**

Partition coefficient: n-octanol/water : log Pow: 3.52 (25 °C)

##### **2-heptanone:**

Partition coefficient: n-octanol/water : log Pow: 2.26 (30 °C)  
pH: 7  
Method: Regulation (EC) No. 440/2008, Annex, A.8  
GLP: yes

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

### 1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)  
pH: 6.8  
Method: OECD Test Guideline 117  
GLP: yes

### Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n-octanol/water : log Pow: 2.3 - 2.8 (25 °C)  
pH: 7  
Method: OECD Test Guideline 107

### ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)  
log Pow: 3.6 (20 °C)  
pH: 7.8  
GLP: yes

### talc:

Partition coefficient: n-octanol/water : log Pow: -9.4 (25 °C)  
pH: 7  
GLP: no

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

### Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 00000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

Additional ecological information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

### SECTION 14: Transport information

#### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADN : PAINT  
ADR : PAINT  
RID : PAINT  
IMDG : PAINT  
(REACTION MASS OF PENTAMETHYL-PIPERIDYL SEBACATE, SOLVENT NAPHTHA)  
IATA : PAINT

#### 14.3 Transport hazard class(es)

|     | Class | Subsidiary risks |
|-----|-------|------------------|
| ADN | : 3   |                  |
| ADR | : 3   |                  |
| RID | : 3   |                  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 0000000000504145      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024  
88

**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable liquid

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : yes

**ADR**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000050414588      Date of last issue: 13.08.2024  
Date of first issue: 22.03.2024

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable  
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable  
Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable  
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

P5c

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

E2

ENVIRONMENTAL HAZARDS

34

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 0000000000504145<br>88 | Date of first issue: 22.03.2024 |

environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Volatile organic compounds (VOC) content: 420 g/l  
VOC content excluding water

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 48 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

d

Limit value for maximum VOC content as specified in Annex IIB:

420 g/l

VOC content of the ready-for-use product according to ISO 11890-2:

419 g/l

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

## SECTION 16: Other information

### Full text of H-Statements

|       |  |
|-------|--|
| H225  | : Highly flammable liquid and vapor.                       |
| H226  | : Flammable liquid and vapor.                              |
| H302  | : Harmful if swallowed.                                    |
| H304  | : May be fatal if swallowed and enters airways.            |
| H312  | : Harmful in contact with skin.                            |
| H315  | : Causes skin irritation.                                  |
| H317  | : May cause an allergic skin reaction.                     |
| H319  | : Causes serious eye irritation.                           |
| H332  | : Harmful if inhaled.                                      |
| H335  | : May cause respiratory irritation.                        |
| H336  | : May cause drowsiness or dizziness.                       |
| H361f | : Suspected of damaging fertility.                         |
| H373  | : May cause damage to organs through prolonged or repeated |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

H400 : exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization;

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

Version 2.0      Revision Date: 13.03.2026      SDS Number: 0000000000504145      Date of last issue: 13.08.2024  
88      Date of first issue: 22.03.2024

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Skin Sens. 1      | H317 |
| STOT SE 3         | H335 |
| STOT SE 3         | H336 |
| Aquatic Chronic 2 | H411 |

### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## GLASURIT MISCHLACK AD22-29-1>5 10L Steel drums

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 13.08.2024  |
| 2.0     | 13.03.2026     | 000000000504145<br>88 | Date of first issue: 22.03.2024 |

---