

90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: 90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes
Product code	: 0000000050482919
1.2 Relevant identified uses of t	he substance or mixture and uses advised against
Use of the	: Spraying
Substance/Mixture	Basecoat product
1.3 Details of the supplier of the	safety data sheet
<u>Company:</u> BASF Coatings GmbH	Contact address:
Postfach 6123	BASF plc 4th and 5th Floors, 2 Stockport Exchange
48136 Münster	Railway Road, Stockport, SK1 3GG
Deutschland	United Kingdom

Telephone: +44 161 475 3000



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H226	Flammable liquid and vapor.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H318	Causes serious eye damage.
Precautionary Statements	:	Prevention : P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

smoking.

P261	Avoid breathing mist or vapors.				
P264	Wash skin thoroughly after handling.				
P280	/ear protective gloves/ protective clothing/ ye protection/ face protection/ hearing rotection.				
Response:					
P305 + P35	51 + P338 + P310 IF IN EYES: Rinse cautiously				
	with water for several minutes. Remove				
	contact lenses, if present and easy to do.				
	Continue rinsing. Immediately call a POISON				
	CENTER/ doctor.				
P370 + P37	78 In case of fire: Use dry sand, dry chemical				

or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

2,4,7,9-Tetramethyldec-5-yne-4,7-diol



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : polyurethane

pigment

organic solvent

fillers

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

	Registration number		
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 UK-20- 9702550300-0- 0000	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 25 - < 50
	UK-20- 0537843089-5- 0000 UK-20-		
	9642318150-0- 0000		
butan-2-ol	78-92-2 201-158-5	Flam. Liq. 3; H226 Eye Irrit. 2; H319	>= 10 - < 12.5



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

	603-127-00-5 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	
2,4,7,9-Tetramethyldec-5-yne-4,7- diol	126-86-3 204-809-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 3 - < 5



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

2-dimethylaminoethanol	108-01-0	Flam. Liq. 3; H226	>= 0.5 - < 1
	203-542-8	Acute Tox. 4;	
	603-047-00-0	H302	
	UK-20-	Acute Tox. 3; H331	
	0537843089-5- 0000	Acute Tox. 4;	
	UK-20-	H312	
	9642318150-0-	Skin Corr. 1B;	
	0000	H314	
		Eye Dam. 1; H318	
		STOT SE 3; H335	
		(Respiratory	
		system)	
		specific concentration	
		limit	



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

		STOT SE 3; H335 >= 5 %	
Substances with a workplace expos	sure limit :		
Barium sulfate	7727-43-7		>= 1 - < 2
	231-784-4		
	UK-20-		
	0537843089-5-		
	0000		
	UK-20-		
	9642318150-0-		
	0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

safety.

	If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. Never give anything by mouth to an unconscious person.
If inhaled :	If symptoms persist, call a physician. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact :	



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Do NOT use solvents or thinners.

In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
		Call a physician immediately.
		If easy to do, remove contact lens, if worn.
If swallowed	:	If symptoms persist, call a physician.
		Do NOT induce vomiting.
		Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Information, i.e. additional information on symptoms	
		and effects may be included in the GHS labeling phrases	
		available in Section 2 and in the Toxicological	



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

assessments available in Section 11.

Risks

: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote. Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing	:	Water spray jet
media		Dry powder
		Alcohol-resistant foam
		Carbon dioxide (CO2)



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Unsuitable extinguishing	:	High volume water jet
media		

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire :	Fire will produce dense black smoke containing
fighting	hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Further information	:	In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

This must not be discharged into drains.

SECTION 6: Accidental release measures 6.1 Personal precautions, protective equipment and emergency procedures Personal precautions : Avoid breathing vapours. Keep away from sources of ignition. Advice on product handling can be found in sections 7 and 8 of this safety data sheet. For non-emergency personnel: For emergency responders: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

6.2 Environmental precautions

Environmental precautions :	Do not allow uncontrolled discharge of product into the environment.
	Avoid subsoil penetration.
	If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Ensure adequate ventilation.
		Contain spillage soak up with pon-comb

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling :	Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
	The workplace should be equipped with an emergency shower and eye-rinsing facility.



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.
	Do not breathe vapors or spray mist.
Advice on protection : against fire and explosion	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
Hygiene measures :	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

7.2 Conditions for safe storage, including any incompatibilities

Further information on : storage conditions	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Advice on common storage :	 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material :	Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene, Carbon steel (Iron), tinned carbon steel (Tinplate)
7.3 Specific end use(s) Specific use(s) :	Please refer to the technical leaflet for further



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	25 ppm	GB EH40
			123 mg/m3	
	Further information: Can be absorbed through the skin. The assigned			
	substances are those for which there are concerns that dermal			
	absorption will lead to systemic toxicity.			
		STEL	50 ppm	GB EH40
			246 mg/m3	
	Further information: Can be absorbed through the skin. The assigned			



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

		are those for which will lead to systemi	there are concerns that o c toxicity.	dermal
		TWA	20 ppm	2000/39/EC
			98 mg/m3	
	Further info	rmation: Identifies	the possibility of significa	nt uptake
	through the	skin, Indicative		
		STEL	50 ppm	2000/39/EC
			246 mg/m3	
	Further info	rmation: Identifies	the possibility of significa	nt uptake
	through the	skin, Indicative		
butan-2-ol	78-92-2	TWA	100 ppm	GB EH40
			308 mg/m3	
		STEL	150 ppm	GB EH40
			462 mg/m3	
Barium sulfate	7727-43-7	TWA (inhalable	10 mg/m3	GB EH40



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

		dust)		
		TWA (Respirable dust)	4 mg/m3	GB EH40
2- dimethylaminoet hanol	108-01-0	TWA	2 ppm 7.4 mg/m3	GB EH40
		STEL	6 ppm 22 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

 8.2 Exposure controls Engineering measures Ensure adequate ventilation. Personal protective equipment Eye/face protection : 	
Hand protection	Required when there is a risk of eye contact.
Remarks :	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

		indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short- term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Skin and body protection	:	Anti-static protective clothing
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

respirators.

	In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures :	Do not breathe vapour/spray.
	Eye wash fountains and safety showers must be easily accessible.
	If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	blue
Odor	:	of glycol



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

рН	:	6.0 - 9.0 Concentration: 500.00000 g/l
Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	45 °C Method: ISO 3679
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	
		not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	0.986 g/cm3 (20 °C)
Solubility(ies) Water solubility Partition coefficient: n- octanol/water Autoignition temperature	:	not determined not applicable for mixtures > 200 °C



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	not determined (40 °C)
		621.6 mm2/s (23 °C)
Flow time	:	> 90 s at 23 °C Cross section: 6 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
9.2 Other information		
Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Toxic if inhaled.		
Product:		
Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method

Components:

2-butoxyethanol:



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Acute oral toxicity	:	LD50 (guinea pig): 1,200 mg/kg		
2-dimethylaminoethanol:				
Acute oral toxicity	:	LD50 (Rat): 1,183 mg/kg		
Acute inhalation toxicity	:	LC50 (Rat): 6.1 mg/l Exposure time: 4 h		
Acute dermal toxicity	:	Test atmosphere: vapor LD50 (Rabbit): 1,219 mg/kg		
Skin corrosion/irritation Causes skin irritation.				
Serious eye damage/eye irritation Causes serious eye damage.				
Respiratory or skin sensitization				
Skin sensitization				
May cause an allergic skin reaction.				



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Partition coefficient: n- octanol/water	:	log Pow: 0.81 (25 °C) GLP: no
butan-2-ol: Partition coefficient: n- octanol/water	:	log Pow: 0.61 GLP: no Remarks: Information taken from reference works and the literature.
2,4,7,9-Tetramethyldec-5-yn	e-4	.7-diol:
Partition coefficient: n- octanol/water		
2-dimethylaminoethanol: Partition coefficient: n- octanol/water	:	log Pow: -0.55 (23 °C)
Barium sulfate:		



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Partition coefficient: n- : octanol/water	Pow: 4.26 log Pow: 0.63
12.4 Mobility in soil No data available	
12.5 Results of PBT and vPvB asse	essment
<u>Product:</u> Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6 Other adverse effects Product: Endocrine disrupting : potential	This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

ADR	:	UN 1263	
RID	:	UN 1263	
IMDG	:	UN 1263	
ΙΑΤΑ	:	UN 1263	
14.2 UN proper shipping name			
ADN	:	PAINT	
ADR	:	PAINT	
RID	:	PAINT	
IMDG	:	PAINT	
ΙΑΤΑ	:	PAINT	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
ΙΑΤΑ	:	3

14.4 Packing group

ADN

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

ADR



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	Ш
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	Ш
Labels	:	3



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	Ш
Labels	:	Flammable Liquids
IATA (Passenger)		
Packing instruction (passenger aircraft)	:	355
Packing instruction (LQ)	:	Y344
Packing group	:	Ш
Labels	:	Flammable liquid

14.5 Environmental hazards



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

ADN

	Environmentally hazardous	:	no
	ADR		
	Environmentally hazardous	:	no
	RID		
	Environmentally hazardous	:	no
	IMDG		
	Marine pollutant	:	no
14.6	6 Special precautions for user		
	Remarks	:	ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3
	The transport classification(c)	oro	vided barein are for informational purposes only, and solely based

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered:
		Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Regulation (EC) on substances ozone layer	that deplete the	: Not applicable
UK REACH List of substances so authorisation (Annex XIV)	ubject to	: Not applicable
Control of Major Accident Haz Regulations 2015 (COMAH)	ards P5c	FLAMMABLE LIQUIDS
Volatile organic : compounds	Volatile organic com	pounds (VOC) content: 537 g/l
		U of 24 November 2010 on (integrated pollution prevention and

Volatile organic compounds (VOC) content: 53.71 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

(requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	d
Limit value for maximum VOC content as specified in Annex IIB:	420 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	419 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements		
H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road;



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative



90-A 527 0,2L saphirblau 6x0,033KG Fibreboard boxes

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	25.04.2025	00000000050482 919	Date of first issue: 28.07.2024

Further information Other information	: For multi-pack syster all components.	ns observe material safety data sheets of	
Restricted to professional users.			
Classification of the mix	ture:	Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN