

Safety data sheet

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.07.2024 Version: 10.1 Date / Previous version: 11.06.2024 Previous version: 10.0 Product: **100-E 463 0,125L pearl violet fine**

(ID no. 50531313/SDS_GEN_GB/EN)

Date of print 29.07.2024

Page: 1/16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

100-E 463 0,125L pearl violet fine

UFI: 0WYS-R1EK-7008-F5HE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Basecoat product

1.3. Details of the supplier of the safety data sheet

<u>Company:</u> BASF Coatings GmbH Postfach 6123 48136 Muenster Deutschland <u>Contact address:</u> BASF plc 4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG UNITED KINGDOM

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

No need for classification according to GHS criteria for this product.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Labeling of special preparations (GHS): EUH208: May produce an allergic reaction. Contains: 2-methylisothiazolinone EUH210: Safety data sheet available on request.

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

acrylic resin, polyether, Water, organic solvent, pigment, polyurethane

Hazardous ingredients (GHS)

2-butoxyethanol

Content (W/W): >= 7 % - < 10 % CAS Number: 111-76-2 EC-Number: 203-905-0 REACH registration number: 01-2119475108-36 INDEX-Number: 603-014-00-0 Acute Tox. 4 (Inhalation - vapour) Acute Tox. 4 (oral) Skin Irrit. 2 Eye Irrit. 2 H319, H315, H302 + H332

2-dimethylaminoethanol

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.07.2024 Version: 10.1 Date / Previous version: 11.06.2024 Previous version: 10.0 Product: 100-E 463 0,125L pearl violet fine (ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024 Content (W/W): >= 0.1 % - < 0.2 % Flam. Liq. 3 CAS Number: 108-01-0 Acute Tox. 3 (Inhalation - vapour) EC-Number: 203-542-8 Acute Tox. 4 (oral) Acute Tox. 4 (dermal) **REACH registration number: 01-**2119492298-24 Skin Corr. 1B Eye Dam. 1 INDEX-Number: 603-047-00-0 STOT SE 3 (irr. to respiratory syst.) H226, H331, H335, H314, H302 + H312 Specific concentration limit: STOT SE 3, irr. to respiratory syst.: >= 5 % 2-methylisothiazolinone Content (W/W): > 0 % - < 0.1 % Acute Tox. 2 (Inhalation - dust) CAS Number: 2682-20-4 Acute Tox. 2 (Inhalation - vapour) EC-Number: 220-239-6 Acute Tox. 3 (oral) Acute Tox. 3 (dermal) Eye Dam./Irrit. 1 Aquatic Acute 1 Aquatic Chronic 1 Skin Corr./Irrit. 1B Skin Sens. 1A M-factor acute: 10 H314, H311, H330, H301, H317, H410 EUH071 Specific concentration limit: Skin Sens. 1A: >= 0.001500 %

Page: 3/16

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 4/16

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: allergic symptoms, No data available.

4.3. Indication of any immediate medical attention and special treatment needed Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

5.3. Advice for fire-fighters

Special protective equipment: Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 5/16

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eyerinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: glass, High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Stainless steel 1.4301 (V2) Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability: Storage temperature: 5 - 40 °C

7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Page: 6/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.07.2024 Version: 10.1 Date / Previous version: 11.06.2024 Previous version: 10.0 Product: **100-E 463 0,125L pearl violet fine**

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Components with occupational exposure limits

108-01-0: 2-dimethylaminoethanol TWA value 7.4 mg/m3; 2 ppm (WEL/EH 40 (UK)) STEL value 22 mg/m3; 6 ppm (WEL/EH 40 (UK)) Ceiling limit value/factor: 15 min 111-76-2: 2-butoxyethanol Skin Designation (WEL/EH 40 (UK)) The substance can be absorbed through the skin. TWA value 123 mg/m3 ; 25 ppm (WEL/EH 40 (UK)) Skin Designation (OEL (EU)) The substance can be absorbed through the skin. STEL value 246 mg/m3 ; 50 ppm (OEL (EU)) indicative TWA value 98 mg/m3 ; 20 ppm (OEL (EU)) indicative STEL value 246 mg/m3 ; 50 ppm (WEL/EH 40 (UK)) Ceiling limit value/factor: 15 min

Components with biological limit values

111-76-2: 2-butoxyethanol UKEH40BMGV Determinant: butoxyacetic acid Biological Specimen: Creatinine in urine Sampling time: End of shift Concentration: 240 mmol/mol

Components with PNEC

108-01-0: 2-dimethylaminoethanol freshwater: 0.066 mg/l

freshwater: 0.066 mg/l marine water: 0.004 mg/l intermittent release: 0.661 mg/l sediment (freshwater): 0.246 mg/kg sediment (marine water): 0.015 mg/kg soil: 0.01 mg/kg STP: 10 mg/l oral (secondary poisoning): No PNEC oral derived, as accumulation in organisms is not to be expected.

111-76-2: 2-butoxyethanol

freshwater: 8.8 mg/l marine water: 0.88 mg/l intermittent release: 9.1 mg/l sediment (freshwater): 34.6 mg/kg sediment (marine water): 3.46 mg/kg soil: 2.33 mg/kg STP: 463 mg/l

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 7/16

oral (secondary poisoning): 20 mg/kg

Components with DNEL

108-01-0: 2-dimethylaminoethanol

worker: Long-term exposure - systemic and local effects, Inhalation: 1.76 mg/m3 worker: Short-term exposure - systemic effects, Inhalation: 5.28 mg/m3

worker: Short-term exposure - systemic effects, Inhalation: 5.28 mg/m3 worker: Short-term exposure - local effects, Inhalation: 13.53 mg/m3 worker: Long-term exposure - systemic effects, dermal: 0.25 mg/kg worker: Short-term exposure - systemic effects, dermal: 1.2 mg/kg worker: Short-term exposure - local effects, dermal: 0.1 mg/cm2 consumer: Long-term exposure- systemic effects, Inhalation: 0.43 mg/m3 consumer: Long-term exposure- systemic effects, oral: 0.148 mg/kg

111-76-2: 2-butoxyethanol

worker: Long-term exposure- systemic effects, Inhalation: 98 mg/m3, 20 ppm worker: Short-term exposure - systemic effects, Inhalation: 1091 mg/m3 worker: Short-term exposure - local effects, Inhalation: 246 mg/m3 consumer: Long-term exposure- systemic effects, oral: 6.3 mg/kg consumer: Short-term exposure - systemic effects, oral: 26.7 mg/kg consumer: Long-term exposure- systemic effects, Inhalation: 59 mg/m3 consumer: Short-term exposure - systemic effects, Inhalation: 426 mg/m3 consumer: Short-term exposure - local effects, Inhalation: 147 mg/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter

Hand protection:

Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Eye protection:

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 8/16

Eye protection not required.

Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

<u>Environmental exposure controls</u> For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form: Colour: Odour: pH value: Melting point:	liquid violet of glycol 7.0 - 9.0			
	not determined			
onset of boiling:	not determined			
Flash point: Flammability: Lower explosion limit: Ignition temperature:	 > 70 °C Combustible liquid. 36 g/m3 > 200.00 °C 	(ISO 3679)		
Vapour pressure:	(20 °C)			
	not determined			
	(50 °C)			
	not determined			
Density:	1.168 g/cm3 (20 °C)			
Relative vapour density				
	Lighter than air.			
Partitioning coefficient n-octanol/water (log Kow):				
Thermal decomposition: Viscosity, kinematic:	not applicable for mixtures No decomposition if stored and handle 621.6 mm2/s (23 °C)	ed as prescribed/indicated.		
	(40 °C) No data available.			

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 9/16

Explosion hazard: not explosive Fire promoting properties: not fire-propagating

9.2. Other information

Burning rate:	The material doesn't meet the criteria specified in paragraph 33.2.4.4 of UN manual of tests and criteria.	(UN Test N.1 (ready combustible solids))
Self heating ability:	It is not a material capable of spontaneous heating	
Miscibility with water:		
	miscible	
Flow time:	> 90 s (23 °C)	(DIN EN ISO 2431; 6 mm)

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Based on available data, the classification criteria are not met.

Irritation

Assessment of irritating effects: Based on available data, the classification criteria are not met.

Respiratory/Skin sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single: Based on available data, the classification criteria are not met.

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Page: 11/16

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential: No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Waste kev:

08 01 11^m waste paint and varnish containing organic solvents or other hazardous substances

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN proper shipping name: Transport hazard class(es): Packing group:	Not classified as a dangerous good under transport regulations Not applicable Not applicable Not applicable Not applicable
	1.1
Environmental hazards: Special precautions for	Not applicable None known
user	

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for	None known
user	

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Packing group: Not applicable Environmental hazards: Not applicable Special precautions for None known user:

<u>Transport in inland waterway vessel</u> Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulationsUN number or ID number:Not applicableUN proper shipping name:Not applicableTransport hazard class(es):Not applicablePacking group:Not applicableEnvironmental hazards:Not applicableSpecial precautions forNone knownuserNote applicable

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulationsUN number or ID number:Not applicableUN proper shipping name:Not applicableTransport hazard class(es):Not applicablePacking group:Not applicableEnvironmental hazards:Not applicableSpecial precautions forNone knownuserNone known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

Page: 13/16

Page: 14/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.07.2024 Version: 10.1 Date / Previous version: 11.06.2024 Previous version: 10.0 Product: 100-E 463 0,125L pearl violet fine

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

220.0 g/l

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control) 7.1 % VOC content: organic solvents VOC content: 7.2 % calculated VOC content:

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	d
Limit value for maximum VOC content as specified in Annex IIB:	420 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	249 g/l

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Page: 15/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 28.07.2024 Version: 10.1 Date / Previous version: 11.06.2024 Previous version: 10.0 Product: **100-E 463 0,125L pearl violet fine**

> (ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3: Acute Tox. Acute toxicity Skin Irrit. Skin irritation Eye Irrit. Eve irritation Flam. Liq. Flammable liquids Skin Corr. Skin corrosion Eve Dam. Serious eye damage STOT SE Specific target organ toxicity - single exposure Eve Dam./Irrit. Serious eye damage/eye irritation Aquatic Acute Hazardous to the aquatic environment - acute Aquatic Chronic Hazardous to the aquatic environment - chronic Skin Corr./Irrit. Skin corrosion/irritation Skin Sens. Skin sensitization H319 Causes serious eye irritation. Causes skin irritation. H315 H302 + H332 Harmful if swallowed or if inhaled. Flammable liquid and vapour. H226 H331 Toxic if inhaled. H335 May cause respiratory irritation. H314 Causes severe skin burns and eve damage. Harmful if swallowed or in contact with skin. H302 + H312Toxic in contact with skin. H311 H330 Fatal if inhaled. H301 Toxic if swallowed. May cause an allergic skin reaction. H317 Very toxic to aquatic life with long lasting effects. H410 Corrosive to the respiratory tract. EUH071

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value, MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a

(ID no. 50531313/SDS_GEN_GB/EN) Date of print 29.07.2024

Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.