

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 100-IC 550 0,5L Interieur Additiv 0,5L Steel drums
Product code : 000000000050609397
Unique Formula Identifier (UFI) : YW37-F0QH-G00J-U6QY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying
Basecoat product

1.3 Details of the supplier of the safety data sheet

Company:
BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:
BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000
E-mail address: product-safety-coatings@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4
Skin sensitization, Category 1

H332: Harmful if inhaled.
H317: May cause an allergic skin reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P280 Wear protective gloves.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous ingredients which must be listed on the label:

HDI-Oligomer(Trimer)
HDI-polymer
HDI-Homopolymer
IPDI Homopolymer
1,6-hexamethylene diisocyanate

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : polyisocyanate
organic solvent

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|-----------------------|---|---|--------------------------|
| HDI-Oligomer(Trimer) | 28182-81-2 01-2119485796-17 | Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) | >= 25 - < 50 |
| 2-butoxyethyl acetate | 112-07-2 203-933-3 607-038-00-2 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 | >= 15 - < 20 |
| HDI-polymer | 666723-27-9 | Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 | >= 15 - < 20 |
| HDI-Homopolymer | 28182-81-2 500-060-2 UK-20-9642318150-0-0000 | Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) | >= 15 - < 20 |
| IPDI Homopolymer | 53880-05-0 500-125-5 | Acute Tox. 4; H332 Skin Sens. 1; H317 | >= 10 - < 12.5 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

| | | | |
|---------------------------------|--|--|------------------|
| | 01-2119980716-25 | STOT SE 3; H335 (Respiratory system) | |
| n-Butyl acetate | 123-86-4 204-658-1 607-025-00-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Flam. Liq. 3; H226 STOT SE 3; H335 (Central nervous system) | $\geq 2.5 - < 3$ |
| 2-(2-butoxyethoxy)ethyl acetate | 124-17-4 204-685-9 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Eye Irrit. 2; H319 | $\geq 2 - < 2.5$ |
| cyclohexyldimethylamine | 98-94-2 202-715-5 UK-20-0537843089-5-0000 | Flam. Liq. 3; H226 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 | $\geq 0.5 - < 1$ |
| 1,6-hexamethylene diisocyanate | 822-06-0 212-485-8 615-011-00-1 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) specific concentration limit Resp. Sens. 1; H334 $\geq 0.5 \%$ Skin Sens. 1; H317 $\geq 0.5 \%$ | < 0.1 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- | | |
|-------------------------|--|
| General advice | : First aid personnel should pay attention to their own safety. Never give anything by mouth to an unconscious person. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. |
| If inhaled | : If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician. |
| In case of skin contact | : Call a physician immediately. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. |
| In case of eye contact | : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn. |
| If swallowed | : Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
| Risks | : May cause an allergic skin reaction. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

Harmful if inhaled.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Hazardous combustion products : Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Avoid subsoil penetration.
Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such cir-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

cumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Open drum carefully as content may be under pressure.
Do not breathe vapors or spray mist.
Protect from moisture.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure release. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

Advice on common storage : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

Packaging material : Suitable material: Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-----------------------|------------|--|---------------------|------------|
| HDI-Oligomer(Trimer) | 28182-81-2 | TWA | 0.02 mg/m3 (NCO) | GB EH40 |
| | | Further information: Capable of causing occupational asthma. | | |
| | | STEL | 0.07 mg/m3 (NCO) | GB EH40 |
| | | Further information: Capable of causing occupational asthma. | | |
| 2-butoxyethyl acetate | 112-07-2 | TWA | 20 ppm 133 mg/m3 | GB EH40 |
| | | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | STEL | 50 ppm 332 mg/m3 | GB EH40 |
| | | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | STEL | 50 ppm 333 mg/m3 | 2000/39/EC |
| | | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | |
| | | TWA | 20 ppm 133 mg/m3 | 2000/39/EC |
| | | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | |
| HDI-Homopolymer | 28182-81-2 | TWA | 0.02 mg/m3 (NCO) | GB EH40 |
| | | Further information: Capable of causing occupational asthma. | | |
| | | STEL | 0.07 mg/m3 (NCO) | GB EH40 |
| | | Further information: Capable of causing occupational asthma. | | |
| n-Butyl acetate | 123-86-4 | TWA | 150 ppm | GB EH40 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

| | | | | |
|--|----------|------|----------------------------------|------------------|
| | | | 724 mg/m ³ | |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| 1,6-hexamethylene diisocyanate | 822-06-0 | TWA | 0.02 mg/m ³ (NCO) | GB EH40 |
| Further information: Capable of causing occupational asthma. | | | | |
| | | STEL | 0.07 mg/m ³ (NCO) | GB EH40 |
| Further information: Capable of causing occupational asthma. | | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|--------------------------------|------------|---|--------------------------------------|----------------|
| HDI-Oligomer(Trimer) | 28182-81-2 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |
| HDI-Homopolymer | 28182-81-2 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |
| 1,6-hexamethylene diisocyanate | 822-06-0 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.
Safety glasses with side-shields conforming to EN166

Hand protection

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

- Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm
Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Request information on glove permeation properties from the glove supplier.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Preventive skin protection
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
- Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres. chemical-resistant disposable coveralls
- Respiratory protection : Suitable respiratory equipment:
full face mask with AB2P3 class combination filter
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Protective measures : Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 | Date of first issue: 29.09.2023 |
| | | 97 | |

Respiratory protective equipment should be worn by spray booth operatives.

Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|---|
| Appearance | : | liquid |
| Color | : | colorless |
| Odor | : | of glycol |
| pH | : | substance/mixture reacts with water |
| Melting point/freezing point | : | not determined |
| Boiling point/boiling range | : | 180.00 - 190.00 °C |
| Flash point | : | > 66 °C Method: ISO 3679 |
| Evaporation rate | : | not determined |
| Upper explosion limit / Upper flammability limit | : | not determined |
| Lower explosion limit / Lower flammability limit | : | > 35.0 g/m ³ |
| Vapor pressure | : | 2.0000 hPa (20 °C) 9.0000 hPa (50 °C) |
| Density | : | 1.084 g/cm ³ (20 °C) |
| Solubility(ies) | | |
| Water solubility | : | not determined |
| Partition coefficient: n-octanol/water | : | not applicable for mixtures |
| Autoignition temperature | : | > 200 °C |
| Decomposition temperature | : | No decomposition if stored and handled as prescribed/indicated. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : not determined (40 °C)
269.0 mm²/s (23 °C)

Flow time : > 40 s at 23 °C
Cross section: 6 mm
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Combustible liquid.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Avoid direct contact with water.
Heat, flames and sparks.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

10.6 Hazardous decomposition products

Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
Isocyanates

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 11.64 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

HDI-Oligomer(Trimer):

Partition coefficient: n- : log Pow: 9.81 (25 °C)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

octanol/water

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)
pH: 7
Method: OECD Test Guideline 107
GLP: no

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)
log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

2-(2-butoxyethoxy)ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.7 (23 °C)
pH: 6.4
Method: OECD Test Guideline 117
GLP: no

cyclohexyldimethylamine:

Partition coefficient: n-octanol/water : log Pow: 2.01 (25 °C)
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).
- Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
- Contaminated packaging : Residues in empty containers should be neutralised with decontaminant (see section 6). Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Volatile organic compounds (VOC) content: 236 g/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 22.31 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

| | |
|------|--|
| H226 | : Flammable liquid and vapor. |
| H301 | : Toxic if swallowed. |
| H302 | : Harmful if swallowed. |
| H311 | : Toxic in contact with skin. |
| H312 | : Harmful in contact with skin. |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H330 | : Fatal if inhaled. |
| H331 | : Toxic if inhaled. |
| H332 | : Harmful if inhaled. |
| H334 | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H412 | : Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 0000000000506093 Date of last issue: 15.04.2025
Date of first issue: 29.09.2023
97

| | | |
|---------------------|---|--|
| Acute Tox. | : | Acute toxicity |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Eye Dam. | : | Serious eye damage |
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Resp. Sens. | : | Respiratory sensitization |
| Skin Corr. | : | Skin corrosion |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitization |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2019/1831/EU | : | Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 BAT | : | UK. Biological monitoring guidance values |
| 2000/39/EC / TWA | : | Limit Value - eight hours |
| 2000/39/EC / STEL | : | Short term exposure limit |
| 2019/1831/EU / TWA | : | Limit Value - eight hours |
| 2019/1831/EU / STEL | : | Short term exposure limit |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

100-IC 550 0,5L Interieur Additiv 0,5L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 15.04.2025 |
| 3.1 | 17.12.2025 | 0000000000506093 97 | Date of first issue: 29.09.2023 |

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

| | |
|--------------|------|
| Acute Tox. 4 | H332 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H335 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN