

# Safety data sheet

Page: 1/17

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## 100 Line ready mix AH10-02-5<5

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monocoat product

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH  
Postfach 6123  
48136 Muenster  
Deutschland

Contact address:

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

For the classifications not written out in full in this section the full text can be found in section 16.

## 2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Warning

Hazard Statement:

H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P264	Wash contaminated body parts thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

EUH208: May produce an allergic reaction. Contains: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

## 2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

#### Chemical nature

acrylic resin, fillers, Water, organic solvent, polyurethane

#### Hazardous ingredients (GHS)

##### | 2-butoxyethanol

Content (W/W):  $\geq 5\%$  -  $< 7\%$   
 CAS Number: 111-76-2  
 EC-Number: 203-905-0  
 REACH registration number: 01-2119475108-36  
 INDEX-Number: 603-014-00-0

Acute Tox. 4 (Inhalation - vapour)  
 Acute Tox. 4 (oral)  
 Skin Irrit. 2  
 Eye Irrit. 2  
 H319, H315, H302 + H332

##### | 1-pentanol

Content (W/W):  $\geq 1\%$  -  $< 2\%$   
 CAS Number: 71-41-0  
 EC-Number: 200-752-1  
 REACH registration number: 01-2119491284-34  
 INDEX-Number: 603-200-00-1

Flam. Liq. 3  
 Acute Tox. 4 (Inhalation - vapour)  
 Skin Irrit. 2  
 Eye Dam. 1  
 STOT SE 3 (irr. to respiratory syst.)  
 Aquatic Chronic 2  
 H226, H318, H315, H332, H335, H411

##### | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

Content (W/W):  $\geq 0.3\%$  -  $< 0.5\%$   
 CAS Number: 126-86-3  
 EC-Number: 204-809-1  
 REACH registration number: 01-2119954390-39

Eye Dam. 1  
 Skin Sens. 1B  
 Aquatic Chronic 3  
 H318, H317, H412

##### | 3-(3-Isodecyloxypropylamino)propylamine

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

Content (W/W): > 0 % - < 0.1 %	Acute Tox. 3 (oral)
CAS Number: 72162-46-0	Aquatic Acute 1
EC-Number: 276-432-0	Aquatic Chronic 1
	Skin Corr./Irrit. 1A
	M-factor chronic: 10
	H314, H301, H410

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, allergic symptoms, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Antidote: No known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

Unsuitable extinguishing media for safety reasons:  
water jet

### **5.2. Special hazards arising from the substance or mixture**

Advice: Hazardous decomposition products formed under fire conditions.

### **5.3. Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## **SECTION 6: Accidental Release Measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

### **6.4. Reference to other sections**

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## **SECTION 7: Handling and Storage**

### **7.1. Precautions for safe handling**

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Stove-lacquer R 78433, Stove-lacquer EHD0022

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

### 7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

#### Components with occupational exposure limits

111-76-2: 2-butoxyethanol

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

TWA value 123 mg/m<sup>3</sup> ; 25 ppm (WEL/EH 40 (UK))

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 246 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

TWA value 98 mg/m<sup>3</sup> ; 20 ppm (OEL (EU))

indicative

STEL value 246 mg/m<sup>3</sup> ; 50 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

#### Components with biological limit values

111-76-2: 2-butoxyethanol

UKEH40BMGV

Determinant: butoxyacetic acid

Biological Specimen: Creatinine in urine

Sampling time: End of shift

Concentration: 240 mmol/mol

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

### Components with PNEC

#### 71-41-0: 1-pentanol

freshwater: 0.0059 mg/l  
 marine water: 0.00059 mg/l  
 intermittent release: 2.6 mg/l  
 sediment (freshwater): 0.025 mg/kg  
 sediment (marine water): 0.0025 mg/kg  
 soil: 0.00153 mg/kg  
 STP: 37 mg/l

#### 111-76-2: 2-butoxyethanol

freshwater: 8.8 mg/l  
 marine water: 0.88 mg/l  
 intermittent release: 9.1 mg/l  
 sediment (freshwater): 34.6 mg/kg  
 sediment (marine water): 3.46 mg/kg  
 soil: 2.33 mg/kg  
 STP: 463 mg/l  
 oral (secondary poisoning): 20 mg/kg

#### 126-86-3: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

freshwater: 0.04 mg/l  
 marine water: 0.004 mg/l  
 intermittent release: 0.4 mg/l  
 STP: 7 mg/l  
 sediment (freshwater): 0.32 mg/kg  
 sediment (marine water): 0.032 mg/kg  
 soil: 0.028 mg/kg  
 oral (secondary poisoning):  
 No PNEC value available.

### Components with DNEL

#### 71-41-0: 1-pentanol

worker: Long-term exposure - local effects, Inhalation: 73.16 mg/m<sup>3</sup>  
 worker: Short-term exposure - local effects, Inhalation: 292 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, oral: 12.5 mg/kg  
 consumer: Long-term exposure - local effects, Inhalation: 13 mg/m<sup>3</sup>  
 consumer: Short-term exposure - local effects, Inhalation: 218 mg/m<sup>3</sup>

#### 111-76-2: 2-butoxyethanol

worker: Long-term exposure- systemic effects, Inhalation: 98 mg/m<sup>3</sup>, 20 ppm  
 worker: Short-term exposure - systemic effects, Inhalation: 1091 mg/m<sup>3</sup>  
 worker: Short-term exposure - local effects, Inhalation: 246 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, oral: 6.3 mg/kg  
 consumer: Short-term exposure - systemic effects, oral: 26.7 mg/kg  
 consumer: Long-term exposure- systemic effects, Inhalation: 59 mg/m<sup>3</sup>  
 consumer: Short-term exposure - systemic effects, Inhalation: 426 mg/m<sup>3</sup>  
 consumer: Short-term exposure - local effects, Inhalation: 147 mg/m<sup>3</sup>

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

126-86-3: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

worker: Long-term exposure- systemic effects, Inhalation: 2.86 mg/m<sup>3</sup>

worker: Long-term exposure- systemic effects, dermal: 0.812 mg/kg

consumer: Long-term exposure- systemic effects, Inhalation: 0.505 mg/m<sup>3</sup>

consumer: Long-term exposure- systemic effects, dermal: 0.29 mg/kg

consumer: Long-term exposure- systemic effects, oral: 0.29 mg/kg

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

### General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

---



BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Form:	liquid
Colour:	various
Odour:	of glycol
pH value:	7.0 - 9.0
Melting point:	not determined
onset of boiling:	not determined
Flash point:	> 61 °C
Flammability:	Combustible liquid.
Lower explosion limit:	36 g/m <sup>3</sup>
Ignition temperature:	> 200 °C
Vapour pressure:	(20 °C) not determined
	(50 °C) not determined
Density:	1.000 g/cm <sup>3</sup> (20 °C)
Relative vapour density (air):	Lighter than air.
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, kinematic:	36.0 mm <sup>2</sup> /s (23 °C)
	(40 °C) No data available.
Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating

### 9.2. Other information

Burning rate:	The material doesn't meet the criteria (UN Test N.1 (ready specified in paragraph 33.2.4.4 of UN manual of tests and criteria. combustible solids))
Self heating ability:	It is not a material capable of spontaneous heating
Miscibility with water:	No data available.
Flow time:	> 30 s (23 °C) (DIN EN ISO 2431; 4 mm)

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

### 10.4. Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

### 10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

### 10.6. Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## SECTION 11: Toxicological Information

### 11.1. Information on toxicological effects

#### Acute toxicity

Assessment of acute toxicity:

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Based on available data, the classification criteria are not met.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

### Irritation

Assessment of irritating effects:

Not irritating to the skin. Eye contact causes irritation.

### Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

### Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

### Aspiration hazard

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

No aspiration hazard expected.

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

### 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Biological degradability of hazardous substances mentioned in section 3:

| *Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

| *Elimination information:*

| *< 10 % CO<sub>2</sub> formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge, domestic)*

| *25.4 % DOC reduction (57 d) (OECD Guideline 302 A) (aerobic, activated sludge, domestic)*

### 12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

### 12.5. Results of PBT and vPvB assessment

| According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

### 12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.  
Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## SECTION 14: Transport Information

### Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

### Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

UN proper shipping name: Not applicable  
Transport hazard class(es): Not applicable  
Packing group: Not applicable  
Environmental hazards: Not applicable  
Special precautions for user: None known

#### Transport in inland waterway vessel

Not evaluated

#### Sea transport

##### IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable  
UN proper shipping name: Not applicable  
Transport hazard class(es): Not applicable  
Packing group: Not applicable  
Environmental hazards: Not applicable  
Special precautions for user: None known

#### Air transport

##### IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable  
UN proper shipping name: Not applicable  
Transport hazard class(es): Not applicable  
Packing group: Not applicable  
Environmental hazards: Not applicable  
Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

## **SECTION 15: Regulatory Information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 6.9 % organic solvents

VOC content: 6.9 % calculated

VOC content: 250.0 g/l

#### Prohibitions, Restrictions and Authorizations

UK REACH SI, Annex XVII, Marketing and Use Restrictions

Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: no

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

### **15.2. Chemical Safety Assessment**

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

---

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

## SECTION 16: Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Eye Dam./Irrit.	Serious eye damage/eye irritation
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Acute Tox.	Acute toxicity
Skin Irrit.	Skin irritation
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Eye Dam.	Serious eye damage
STOT SE	Specific target organ toxicity — single exposure
Skin Sens.	Skin sensitization
Aquatic Acute	Hazardous to the aquatic environment - acute
Skin Corr./Irrit.	Skin corrosion/irritation
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H315	Causes skin irritation.
H302 + H332	Harmful if swallowed or if inhaled.
H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H301	Toxic if swallowed.
H410	Very toxic to aquatic life with long lasting effects.

### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.



---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2024

Version: 7.0

Date / Previous version: 09.12.2023

Previous version: 6.0

Product: **100 Line ready mix AH10-02-5<5**

(ID no. 50694508/SDS\_GEN\_GB/EN)

Date of print 05.04.2024

---

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.