

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 00000000050719382 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 523-15F 1L 1L Steel drums
Product code : 00000000050719382
Unique Formula Identifier (UFI) : W3H0-M7SJ-Q00E-SFWJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying
Clearcoat product

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000
E-mail address: product-safety-coatings@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 0000000000507193 | Date of first issue: 18.10.2023 |
| | | 82 | |

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P273 Avoid release to the environment.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)

1-methoxy-2-propylacetate

isobutyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|--|---|--------------------------|
| n-Butyl acetate | 123-86-4 204-658-1 607-025-00-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) | $\geq 50 - < 75$ |
| Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0) | 64742-95-6 918-668-5 UK-20-0537843089-5-0000 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | $\geq 15 - < 20$ |
| 1-methoxy-2-propylacetate | 108-65-6 203-603-9 607-195-00-7 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) | $\geq 5 - < 7$ |
| isobutyl acetate | 110-19-0 203-745-1 607-026-00-7 UK-20-0537843089- | Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) | $\geq 3 - < 5$ |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

| | | | |
|--|---------------------------------------|--|--|
| | 5-0000 UK-20-9642318150- 0-0000 | | |
|--|---------------------------------------|--|--|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.
- If inhaled : If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician or poison control center immediately.
- In case of skin contact : Do NOT use solvents or thinners.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If symptoms persist, call a physician.
- If swallowed : Rinse mouth with water.
Do not induce vomiting due to aspiration hazard.
Keep at rest.
If swallowed, call a poison control center or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

Risks : in Section 2 and in the Toxicological assessments available in Section 11.
: May be fatal if swallowed and enters airways.
: May cause drowsiness or dizziness.
: Repeated exposure may cause skin dryness or cracking.

: When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
: Risk of product entering the lungs on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
: Dry powder
: Foam
: Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
: Cool containers/tanks with water spray.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|-----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 000000000507193 | Date of first issue: 18.10.2023 |
| | | 82 | |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Avoid subsoil penetration.
Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

- exposure limits.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Do not breathe vapors or spray mist.
- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.
- The relevant fire protection measures should be noted. Use explosion-proof equipment.
- Hygiene measures : Remove contaminated clothing immediately and dispose of safely.
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

7.3 Specific end use(s)

- Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-----------------|----------|-------------------------------|--------------------|---------|
| n-Butyl acetate | 123-86-4 | TWA | 150 ppm | GB EH40 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

| | | | | |
|--|----------|------|----------------------------------|------------------|
| | | | 724 mg/m ³ | |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| 1-methoxy-2-propylacetate | 108-65-6 | TWA | 50 ppm 274 mg/m ³ | GB EH40 |
| Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | | |
| | | STEL | 100 ppm 548 mg/m ³ | GB EH40 |
| Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | | |
| | | STEL | 100 ppm 550 mg/m ³ | 2000/39/EC |
| Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | | |
| | | TWA | 50 ppm 275 mg/m ³ | 2000/39/EC |
| Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | | |
| isobutyl acetate | 110-19-0 | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | STEL | 187 ppm 903 mg/m ³ | GB EH40 |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| Further information: Indicative | | | | |

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Hand protection

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

- Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm
Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Request information on glove permeation properties from the glove supplier.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Preventive skin protection
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
- Skin and body protection : Anti-static protective clothing
Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
- Respiratory protection : Suitable respiratory equipment:
half-mask with A1P2 class combination filter
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Protective measures : Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 0000000000507193 | Date of first issue: 18.10.2023 |

82

workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|---|
| Appearance | : | liquid |
| Color | : | colorless |
| Odor | : | of glycol |
| pH | : | substance/mixture is non-polar/aprotic |
| Melting point/freezing point | : | not determined |
| Boiling point/boiling range | : | 114.00 - 185.00 °C |
| Flash point | : | 25 °C Method: ISO 3679 |
| Upper explosion limit / Upper flammability limit | : | not determined |
| Lower explosion limit / Lower flammability limit | : | > 35.0 g/m ³ |
| Vapor pressure | : | 12.0000 hPa (20 °C) not determined (50 °C) |
| Density | : | 0.867 g/cm ³ (20 °C) |
| Solubility(ies) | : | |
| Water solubility | : | not determined |
| Partition coefficient: n-octanol/water | : | not applicable for mixtures |
| Autoignition temperature | : | > 200 °C |
| Decomposition temperature | : | No decomposition if stored and handled as prescribed/indicated. |
| Viscosity | : | |
| Viscosity, kinematic | : | 6.0 mm ² /s (23 °C) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 0000000000507193 82 | Date of first issue: 18.10.2023 |

Flow time : not determined (40 °C)
: < 30 s at 23 °C
Cross section: 3 mm
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

isobutyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)
log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-octanol/water : log Pow: 3.17
GLP: no

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: yes

isobutyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-----|-------|------------------|
| ADN | : 3 | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable liquid

14.5 Environmental hazards

ADN
Environmentally hazardous : no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 0000000000507193 82 | Date of first issue: 18.10.2023 |

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: Number on list 3, 20

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|-----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 000000000507193 | Date of first issue: 18.10.2023 |
| | | 82 | |

alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 99.1 %

Volatile organic compounds (VOC) content: 859.19 g/l
VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

| | |
|------|--|
| H225 | : Highly flammable liquid and vapor. |
| H226 | : Flammable liquid and vapor. |
| H304 | : May be fatal if swallowed and enters airways. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H411 | : Toxic to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|-----------------|--|
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Flam. Liq. | : Flammable liquids |
| STOT SE | : Specific target organ toxicity - single exposure |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

Version 3.1 Revision Date: 17.12.2025 SDS Number: 000000000507193 Date of last issue: 23.08.2025
Date of first issue: 18.10.2023
82

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

523-15F 1L 1L Steel drums

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 23.08.2025 |
| 3.1 | 17.12.2025 | 000000000507193 82 | Date of first issue: 18.10.2023 |

Restricted to professional users.

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| STOT SE 3 | H336 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN