

P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: P-A-914 1L 1L Steel drums			
Product code	: 0000000050734454			
1.2 Relevant identified uses of t Use of the	e substance or mixture and uses advised aga : Spraying	iinst		
Substance/Mixture Coatings and related products				
1.3 Details of the supplier of the safety data sheet				
Company: BASF Coatings GmbH	<u>Contact address:</u> BASF plc			
Postfach 6123	4th and 5th Floors, 2	Stockport Exchange		
48136 Münster	Railway Road, Stockp			
Deutschland	United Kingdom			

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3, Central	H336: May cause drowsiness or dizziness.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

nervous system

Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H226 H304	Flammable liquid and vapor. May be fatal if swallowed and enters airways.
			2/50



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements	Prevention : P210	on: Keep away from heat, hot surfaces, sparks open flames and other ignition sources. No smoking.	
	P260	Do not breathe mist or vapors.	
	P264	Wash skin thoroughly after handling.	
	Respons P301 + P	se: 2310 IF SWALLOWED: Immediately call a	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate

xylene

isobutyl acetate

ethylbenzene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Chemical nature

: polyolefin

organic solvent

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
n-Butyl acetate	123-86-4	Flam. Liq. 3; H226	>= 25 - < 50
	204-658-1	STOT SE 3; H336	
	607-025-00-1	(Central nervous	
	UK-20-	system)	
	9702550300-0-		
	0000		
	UK-20-		
	0537843089-5-		



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	0000		
	UK-20- 9642318150-0- 0000		
xylene	1330-20-7	Flam. Liq. 3; H226	>= 20 - < 25
	215-535-7 601-022-00-9	Acute Tox. 4; H332	
	UK-20- 2749242067-7- 0000	Acute Tox. 4; H312 Skin Irrit. 2; H315	
	UK-20- 9702550300-0- 0000	Eye Irrit. 2; H319 STOT SE 3; H335	
	UK-20- 0537843089-5-	(Respiratory system)	
	0000	STOT RE 2; H373	
	UK-20- 9642318150-0-	(Kidney, Liver, Central nervous	



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	0000	system)	
		Asp. Tox. 1; H304	
		Aquatic	
		Chronic 3; H412	
isobutyl acetate	110-19-0	Flam. Liq. 2; H225	>= 15 - < 20
	203-745-1	STOT SE 3; H336	
	607-026-00-7	(Central nervous	
	UK-20-	system)	
	0537843089-5-		
	0000		
	UK-20-		
	9642318150-0-		
	0000		
ethylbenzene	100-41-4	Flam. Liq. 2; H225	>= 3 - < 5
	202-849-4	Acute Tox. 4;	
	601-023-00-4	H332	
	UK-20-	STOT RE 2; H373	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	9702550300-0- 0000 UK-20- 0537843089-5- 0000	(Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
chlorobenzene	108-90-7 203-628-5 602-033-00-1 UK-20- 0537843089-5- 0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 1; H410	>= 0.5 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	: First aid personnel should pay attention to their own
	safety.
	Immediately remove contaminated clothing.

9 / 50



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident. Never give anything by mouth to an unconscious person. Keep patient warm and at rest.
If inhaled :	If breathed in, move person into fresh air.
	Call a physician or poison control center immediately.
	If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact :	If symptoms persist, call a physician.
	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
	Do NOT use solvents or thinners.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

In case of eye contact :	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
	Call a physician immediately.
	If easy to do, remove contact lens, if worn.
If swallowed :	Do not induce vomiting due to aspiration hazard.
	Keep at rest.
	If symptoms persist, call a physician or Poison Control Center immediately.
	Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Information, i.e. additional information on symptoms	
		and effects may be included in the GHS labeling phrases	
		available in Section 2 and in the Toxicological	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

assessments available in Section 11.

Risks :	:	May be fatal if swallowed and enters airways.
		Causes skin irritation.
		Causes serious eye irritation.
		May cause respiratory irritation.
		May cause drowsiness or dizziness.
		May cause damage to organs through prolonged or repeated exposure.
		When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
		Risk of product entering the lungs on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Treatment	:	No known specific antidote.
		Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing	:	Water spray jet
media		Dry powder
		Alcohol-resistant foam
		Carbon dioxide (CO2)

Unsuitable extinguishing : High volume water jet media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire :	Fire will produce dense black smoke containing
fighting	hazardous combustion products (see section 10).



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

5.3	Advice	for	firefighters
0.0	AUVICE	101	menginera

Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Further information	:	In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Avoid breathing vapours.	
		Keep away from sources of ignition.	
		Advice on product handling can be found in sections 7	
		and 8 of this safety data sheet.	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

For non-emergency personnel: For emergency responders: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Ensure adequate ventilation.	
-------------------------	---	------------------------------	--

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling :	Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
	The workplace should be equipped with an emergency shower and eye-rinsing facility.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.
	Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	 Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Hygiene measures	:	Remove contaminated clothing immediately and dispose
		of safely. Wash hands before breaks and at the end of
		workday. Keep away from food, drink and animal
		feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on	:	Avoid direct sunlight. Close containers carefully once
storage conditions		opened and store them upright in order to prevent any
		leakage. No smoking. No admission for unauthorised
		personnel. Always keep in containers of same material
		as the original one. Observe label precautions. Keep in a
		dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

7.3 Specific end use(s)

Specific use(s)

: Please refer to the technical leaflet for further information.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/ EU
	Further info	mation: Indicative		
		TWA	50 ppm 241 mg/m3	2019/1831/ EU



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	Further info	Further information: Indicative					
xylene	1330-20-7	1330-20-7 TWA 50 ppm GB EH40					
			220 mg/m3				
	Further info	rmation: Can be ab	sorbed through the skin. 1	he assigned			
	substances a	are those for which	there are concerns that d	ermal			
	absorption v	vill lead to systemi	c toxicity.				
		STEL 100 ppm GB EH40					
			441 mg/m3				
	Further info	Further information: Can be absorbed through the skin. The assigned					
	substances a	substances are those for which there are concerns that dermal					
	absorption v	absorption will lead to systemic toxicity.					
		TWA	50 ppm	2000/39/EC			
			221 mg/m3				
	Further info	Further information: Identifies the possibility of significant uptake					
	through the	through the skin, Indicative					
		STEL	100 ppm	2000/39/EC			



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

			442 mg/m3	
		nformation: Identifies the possibility of significant uptake he skin, Indicative		
isobutyl acetate	110-19-0	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	187 ppm 903 mg/m3	GB EH40
		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
		STEL	150 ppm 723 mg/m3	2019/1831/ EU
	Further info	rther information: Indicative		
ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	125 ppm 552 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
chlorobenzene	108-90-7	TWA	1 ppm	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

		4.7 mg/m3				
Further inf	Further information: Can be absorbed through the skin. The assigned					
substances	are those for which	there are concerns that o	dermal			
absorption	will lead to system	c toxicity.				
	STEL	3 ppm	GB EH40			
		14 mg/m3				
Further inf	Further information: Can be absorbed through the skin. The assigned					
substances	substances are those for which there are concerns that dermal					
absorption	absorption will lead to systemic toxicity.					
	STEL	15 ppm	2006/15/EC			
		70 mg/m3				
Further inf	Further information: Indicative					
	TWA	5 ppm	2006/15/EC			
		23 mg/m3				
Further inf	ormation: Indicative	2				



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
chlorobenzene	108-90-7	4-chlorocatechol: 5 mol/mol creatinine (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection

: Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.



P-A-914 1L 1L Steel drums

Version Revision Date: SDS Number: 3.0 04.02.2025 00000000050734 454

Date of last issue: 20.01.2025 0734 Date of first issue: 11.10.2023

Hand protection

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

		time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Skin and body protection	:	Anti-static protective clothing
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily accessible.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	of acetate
рН	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined

.. . .

27 / 50



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Flash point	: 23 °C
	Method: ISO 3679
Evaporation rate	: not determined
Lower explosion limit /	: > 35 g/m3
Lower flammability limit	-
Vapor pressure	:
	not determined
Relative vapor density	: Heavier than air.



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Density	:	0.894 g/cm3 (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n- octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	6.0 mm2/s (23 °C)



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

not determined

- Flow time : < 30 s at 23 °C Cross section: 3 mm
 - Method: ISO 2431
- Explosive properties : Not explosive
- Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information	
	E 1.

- Flammability (liquids) : Flammable liquid and vapour.
- Self-heating substances : The substance or mixture is not classified as self heating.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoi	d
-------------------------	---

Conditions to avoid

: Avoid direct sunlight.

Heat, flames and sparks.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

10.5 Incompatible materials

Materials to avoid

: Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
Skin corrosion/irritation Causes skin irritation.		
Components:		
n-Butyl acetate:		
Result	:	Repeated exposure may cause skin dryness or cracking.
I		
	• •, ,•	
Serious eye damage/eye Causes serious eye irritatio		on
Respiratory or skin sensi		n
Skin sensitization	11120110	
Not classified due to lack o	of data.	
Respiratory sensitization Not classified due to lack o		
Germ cell mutagenicity Not classified due to lack o	of data	
Carcinogenicity	n aala.	
Not classified due to lack of	of data.	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Reproductive toxicity Not classified due to lack of data. STOT-single exposure May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-	:	Pow: 200 (25 °C)
octanol/water		log Pow: 2.3 (25 °C)
		рН: 7
		Method: OECD Test Guideline 117



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	GLP: yes
xylene:	
	log Pow: 3.12 - 3.20 (25 °C)
octanol/water	GLP: no
	Remarks: Information taken from reference works and the literature.
isobutyl acetate:	
	log Pow: 2.3 (25 °C)
octanol/water	рН: 7
	Method: OECD Test Guideline 117
	GLP: yes
ethylbenzene:	
Partition coefficient: n- :	Pow: 4,170 (20 °C)



Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

	octanol/water	log Pow: 3.6 (20 °C) pH: 7.8 GLP: yes
	chlorobenzene: Partition coefficient: n- : octanol/water	log Pow: 2.84 (25 °C) Remarks: Information taken from reference works and the literature.
	I I Mobility in soil No data available	
12.5	5 Results of PBT and vPvB asses	ssment
	<u>Product:</u> Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

12.6 Other adverse effects		
Product:		
Endocrine disrupting	:	This substance/mixture does not contain components
potential		considered to have endocrine disrupting properties for
		environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product		Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

SECTION 14: Transport information

14.1 UN number		
ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
ΙΑΤΑ	:	PAINT



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	3	
ADR	:	3	
RID	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADN			
Packing group	:	III	
Classification Cod	e :	F1	
Hazard Identificat Number	ion :	30	
Labels	:	3	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	III



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels		Elammable Liquide
Laveis	:	Flammable Liquids
IATA (Passenger)	:	
		355
IATA (Passenger) Packing instruction	:	
IATA (Passenger) Packing instruction (passenger aircraft)	:	355
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ)	:	355 Y344 III

14.5 Environmental hazards



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

ADN

Environmentally hazardous	:	no
ADR		
Environmentally hazardous	:	no
RID		
Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered:
		Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

UK REACH List of substances su authorisation (Annex XIV)	KREACH List of substances subject to thorisation (Annex XIV)		: Not applicable
		P5c	
Control of Major Accident Haza Regulations 2015 (COMAH)	ards	P5c	FLAMMABLE LIQUIDS
Volatile organic : compounds			U of 24 November 2010 on (integrated pollution prevention and
	Volatile orga	nic com	pounds (VOC) content: 89.09 %
	Volatile orga	nic com	pounds (VOC) content: 796.46 g/l
	VOC content	exclud	ing water

Other regulations:



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements		
H225	: Highly flammable liquid and vapor.	
H226	: Flammable liquid and vapor.	
H304	: May be fatal if swallowed and enters airways.	



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviati	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	For multi-pack systems observe material safety data
		sheets of all components.
		Restricted to professional users.

Classification of the mixtu	Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method



P-A-914 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	04.02.2025	00000000050734 454	Date of first issue: 11.10.2023

STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN