

P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: P-U-17 1L 1L Metal can		
Product code	: 0000000050734748		
1.2 Relevant identified uses of Use of the Substance/Mixture	 the substance or mixture and uses advised against Spraying Coatings and related products 		
1.3 Details of the supplier of the safety data sheetContact address:Company:Contact address:BASF Coatings GmbHBASF plcPostfach 61234th and 5th Floors, 2 Stockport Exchange48136 MünsterRailway Road, Stockport, SK1 3GGDeutschlandUnited Kingdom			

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H226	Flammable liquid and vapor.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H318	Causes serious eye damage.
		H373	May cause damage to organs through prolonged or repeated exposure.
		H412	Harmful to aquatic life with long lasting effects.



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Precautionary Statements	Prevention P210	n: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe mist or vapors.
	P264	Wash skin thoroughly after handling.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Response	:
	P305 + P3	 51 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
	P370 + P3	78 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Hazardous ingredients which must be listed on the label: Epoxy resin base Bisphenol-A MG <700

Ceramic materials and wares

xylene

n-butanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The product may be a skin sensitizer. It is also a skin irritant and repeated contact may increase this effect.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature	: Epoxy resin derivative
	fillers
	epoxy resin
	pigment
	inorganic compounds



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

organic solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration	Classification	Concentratio n (% w/w)
	number		
Epoxy resin base Bisphenol-A MG	25068-38-6	Skin Irrit. 2; H315	>= 15 - < 20
<700	500-033-5	Eye Irrit. 2; H319	
	603-074-00-8	Skin Sens. 1;	
	01-2119456619-26	H317	
		Aquatic	
		Chronic 2; H411	
		specific	
		concentration	



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

		limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	
Ceramic materials and wares	66402-68-4 266-340-9 UK-20- 0537843089-5- 0000	Eye Dam. 1; H318	>= 12.5 - < 15
xylene	1330-20-7 215-535-7 601-022-00-9 UK-20- 2749242067-7-	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 10 - < 12.5



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	0000	Skin Irrit. 2; H315	
	UK-20-	Eye Irrit. 2; H319	
	9702550300-0- 0000	STOT SE 3; H335	
	UK-20- 0537843089-5-	(Respiratory system)	
	0000	STOT RE 2; H373	
	UK-20- 9642318150-0- 0000	(Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
n-butanol	71-36-3 200-751-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315	>= 3 - < 5
	603-004-00-6	Eye Dam. 1; H318	
	UK-20-	STOT SE 3; H335	
	9702550300-0-	(Respiratory	



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	0000	system)	
	UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	STOT SE 3; H336 (Central nervous system)	
1-methoxypropan-2-ol	107-98-2 203-539-1 603-064-00-3 UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0000 UK-20- 0537843089-5-	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	0000		
	UK-20- 9642318150-0- 0000		
ethylbenzene	100-41-4	Flam. Liq. 2; H225	>= 2 - < 2.5
	202-849-4	Acute Tox. 4; H332	
	601-023-00-4	STOT RE 2; H373	
	UK-20- 9702550300-0- 0000	(Auditory system) Asp. Tox. 1; H304	
	UK-20- 0537843089-5- 0000	Aquatic Chronic 3; H412	
isobutyl alcohol	78-83-1	Flam. Liq. 3; H226	>= 1 - < 2
	201-148-0	Skin Irrit. 2; H315	
	603-108-00-1	Eye Dam. 1; H318	
	UK-20- 9702550300-0-	STOT SE 3; H335	



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	(Respiratory system) STOT SE 3; H336 (Central nervous system)	
Substances with a workplace expos	sure limit :	I	
Titanium dioxide	13463-67-7 236-675-5 UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5-		>= 7 - < 10



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	0000 UK-20- 9642318150-0- 0000	
talc	14807-96-6 238-877-9 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000	>= 7 - < 10
Limestone	1317-65-3 215-279-6 UK-20- 9702550300-0- 0000	>= 5 - < 7



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	UK-20- 0537843089-5- 0000	
Silicon dioxide	7631-86-9 231-545-4 01-2119379499-16	>= 3 - < 5
Silica, amorphous, fumed, cryst free	112945-52-5 UK-20- 9702550300-0- 0000	>= 1 - < 2

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	:	First aid personnel should pay attention to their own
		safety.
		If the patient is likely to become unconscious, place and
		transport in stable sideways position (recovery position).



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. Never give anything by mouth to an unconscious person.
If inhaled :	If symptoms persist, call a physician.
	If breathed in, move person into fresh air.
	If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact :	In case of skin contact avoid direct exposure to sunlight or other UV radiation since this would increase sensitisation of the skin.
	If symptoms persist, call a physician.
	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
	Do NOT use solvents or thinners.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

In case of eye contact :		Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
		Call a physician immediately.
		If easy to do, remove contact lens, if worn.
		In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.
If swallowed	:	If symptoms persist, call a physician.
		Do NOT induce vomiting.
		Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Information, i.e. additional information on symptoms
		and effects may be included in the GHS labeling phrases



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

available in Section 2 and in the Toxicological assessments available in Section 11.

Risks

: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Symptoms: After contact with bodyfluids in the
	gastrointestinal tract, the product can hydrolyse and
	form additional methanol. Therefore, carefully observe if
	you experience any signs/symptoms of methanol
	intoxication, taking into account the period of latency of
	several days.
	Treat symptomatically.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media				
Suitable extinguishing	:	Water spray jet		
media		Dry powder		
		Alcohol-resistant foam		
		Carbon dioxide (CO2)		
Unsuitable extinguishing media	:	High volume water jet		
5.2 Special hazards arising from the substance or mixture				
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).		
5.3 Advice for firefighters				
Special protective equipment for fire-fighters		Appropriate breathing apparatus may be required.		



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Further information	:	In the event of fire, cool tanks with water spray.
		Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective	e equipment and emergency procedures
Personal precautions :	Avoid breathing vapours.
	Keep away from sources of ignition.
	Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
	For non-emergency personnel:
	For emergency responders:



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up		Ensure adequate ventilation.
		Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see
		section 13).



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

		The workplace should be equipped with an emergency shower and eye-rinsing facility.
		Avoid contact with the skin, eyes and clothing.
		Handle in accordance with good industrial hygiene and safety practice.
		Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Advice on common storage	:	Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.
		Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage temperature	:	5 - 35 °C



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Packaging material	: Suitable material: Stainless steel 1.4301 (V2), Carbon
	steel (Iron), tinned carbon steel (Tinplate)
7.3 Specific end use(s)	
Specific use(s)	: Please refer to the technical leaflet for further
	information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal				



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	absorption will lead to systemic toxicity.						
		STEL 100 ppm GB EH					
			441 mg/m3				
	Further infor	mation: Can be ab	sorbed through the skin. 1	he assigned			
	substances a	re those for which	there are concerns that d	ermal			
	absorption w	vill lead to systemic	c toxicity.				
		TWA	50 ppm	2000/39/EC			
			221 mg/m3				
	Further infor	mation: Identifies	the possibility of significar	nt uptake			
	through the	skin, Indicative					
		STEL	100 ppm	2000/39/EC			
			442 mg/m3				
	Further information: Identifies the possibility of significant uptake						
	through the skin, Indicative						
Titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40			



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

		TWA (Respirable dust)	4 mg/m3	GB EH40
talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m3 (Silica)	GB EH40
n-butanol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.						
1- methoxypropan- 2-ol	107-98-2	STEL	150 ppm 560 mg/m3	GB EH40			
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.						
	TWA 100 ppm GB EH40 375 mg/m3 375 mg/m3						
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.						
	STEL 150 ppm 2000/39/EC 568 mg/m3 568 mg/m3						
	Further information: Identifies the possibility of significant uptake through the skin, Indicative						



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

		TWA	100 ppm	2000/39/EC		
			375 mg/m3			
	Further infor	mation: Identifies	the possibility of significar	nt uptake		
	through the	skin, Indicative				
ethylbenzene	100-41-4	TWA	100 ppm	GB EH40		
			441 mg/m3			
	Further infor	Further information: Can be absorbed through the skin. The assigned				
	substances a	ire those for which	there are concerns that d	ermal		
	absorption v	vill lead to systemic	c toxicity.			
		STEL 125 ppm GB EH40				
			552 mg/m3			
	Further info	rmation: Can be ab	sorbed through the skin. 1	The assigned		
	substances a	re those for which	there are concerns that d	ermal		
	absorption v	absorption will lead to systemic toxicity.				
		TWA	100 ppm	2000/39/EC		
			442 mg/m3			
	Further infor	mation: Identifies	the possibility of significar	nt uptake		



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

	through the skin, Indicative			
		STEL	200 ppm	2000/39/EC
			884 mg/m3	
	Further info	mation: Identifies	the possibility of significar	nt uptake
	through the	skin, Indicative		
isobutyl alcohol	78-83-1	STEL	75 ppm	GB EH40
			231 mg/m3	
		TWA	50 ppm	GB EH40
			154 mg/m3	
Silica,	112945-52-	TWA (inhalable	6 mg/m3	GB EH40
amorphous,	5	dust)	(Silica)	
fumed, cryst free				
				00.51140
		TWA	2.4 mg/m3	GB EH40
		(Respirable dust)	(Silica)	



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection	:	Tightly fitting safety goggles (splash goggles) (e.g. EN
		166)

Required when there is a risk of eye contact.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove
		certified according to EN ISO 374-1 is suitable: e.g. butyl



P-U-17 1L 1L Metal can

Version Revision Date: 4.0 15.04.2025

SDS Number: 000000000050734 748 Date of last issue: 20.02.2025 Date of first issue: 03.05.2024

rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Skin and body protection	:	Chemical resistant apron
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily accessible.
		If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
		Avoid contact with the skin, eyes and clothing.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

•	Appearance	:	liquid
	Color	:	gray
	Odor	:	alcohol-like
	рН	:	substance/mixture is non-soluble (in water)
	Melting point/ range	:	not determined
	Boiling point/boiling range	:	not determined
	Flash point	:	> 23 °C Method: ISO 3679
	Evaporation rate	:	not determined
	Lower explosion limit / Lower flammability limit	:	> 35 g/m3
	Vapor pressure	:	not determined (20 °C)



Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

		not determined (50 °C)		
Relative vapor density	:	Heavier than air.		
Relative density	:	1.558 (20 °C)		
Density	:	1.558 g/cm3 (20 °C)		
Solubility(ies) Water solubility Partition coefficient: n- octanol/water Autoignition temperature	: :	not determined not applicable for mixtures > 200 °C		
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.		
Viscosity Viscosity, kinematic	:	411.6 mm2/s (23 °C) 110 mm2/s (40 °C)		
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431		
Explosive properties	:	Not explosive		
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.		
33 / 52				



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

9.2 Other information

Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Protect from frost.

Ultraviolet rays

34 / 52



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Heat, flames and sparks.

Heat.

10.5 Incompatible materials

Materials to avoid	:	Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.
		Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Acute inhalation toxicity		Acute toxicity estimate: > 20 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye irritation Causes serious eye damage. Respiratory or skin sensitization Skin sensitization May cause an allergic skin reaction. Respiratory sensitization Based on available data, the classification criteria are not met. Germ cell mutagenicity

Based on available data, the classification criteria are not met.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Carcinogenicity Based on available data, the classification criteria are not met. **Reproductive toxicity** Based on available data, the classification criteria are not met. **STOT-single exposure** Based on available data, the classification criteria are not met. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration toxicity Based on available data, the classification criteria are not met. **SECTION 12: Ecological information** 12.1 Toxicity No data available 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential **Components:** xylene: Partition coefficient: n-: log Pow: 3.12 - 3.20 (25 °C) octanol/water GLP: no Remarks: Information taken from reference works and



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

the literature.

n-butanol:	
	log Pow: 1 (25 °C)
octanol/water	Method: OECD Test Guideline 117
	GLP: yes
1-methoxypropan-2-ol:	
	log Pow: -0.43 (25 °C)
octanol/water	GLP: no
	Remarks: Information taken from reference works and the literature.
ethylbenzene:	
	Pow: 4,170 (20 °C)
octanol/water	log Pow: 3.6 (20 °C)



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

pH:	7.8
GLP	: yes

isobutyl alcohol:

Partition coefficient: n-	:	Pow: 10 (25 °C)
octanol/water		log Pow: 1 (25 °C)
		Method: OECD Test Guideline 117
		GLP: yes

Titanium dioxide: Partition coefficient: n- octanol/water	:	Remarks: Not applicable
talc: Partition coefficient: n- octanol/water	:	log Pow: -9.4 (25 °C) pH: 7 GLP: no



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Silicon dioxide: Partition coefficient: n- : Remarks: Not applicable octanol/water
Silica, amorphous, fumed, crystfree:
Partition coefficient: n- : Remarks: Not applicable octanol/water
12.4 Mobility in soil No data available
12.5 Results of PBT and vPvB assessment
Product:
Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6 Other adverse offects

12.6 Other adverse effects

Product:



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Endocrine disrupting	:	This substance/mixture does not contain components
potential		considered to have endocrine disrupting properties for
		environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

SECTION 14: Transport information

14.1 UN number		
ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT

IATA

: PAINT



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
ΙΑΤΑ	: 3	
14.4 Packing group		
ADN		
Packing group	: 111	
Classification Code	: F1	
Hazard Identification Number	: 30	
Labels	: 3	



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	Ш



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids
Labels IATA (Passenger)	:	Flammable Liquids
	-	Flammable Liquids
IATA (Passenger) Packing instruction	:	
IATA (Passenger) Packing instruction (passenger aircraft)	:	355
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ)	:	355 Y344 III

14.5 Environmental hazards



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

ADN

	Environmentally hazardous	:	no
	ADR		
	Environmentally hazardous	:	no
	RID		
	Environmentally hazardous	:	no
	IMDG		
	Marine pollutant	:	no
14.0	6 Special precautions for use	r	
	Remarks	:	ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3
	The transport classification(s)	pro	ovided herein are for informational purposes only, and solely b

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered:
		Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the	:	Not applicable



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

ozone layer	
UK REACH List of substances so authorisation (Annex XIV)	ubject to : Not applicable
	P5c
Control of Major Accident Haz Regulations 2015 (COMAH)	ards P5c FLAMMABLE LIQUIDS
Volatile organic : compounds	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
	Volatile organic compounds (VOC) content: 23.19 %
	Volatile organic compounds (VOC) content: 361.30 g/l
	VOC content excluding water



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	С
Limit value for maximum VOC content as specified in Annex IIB:	540 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	459 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

Full text of H-Statements		
H225	:	Highly flammable liquid and vapor.
H226	:	Flammable liquid and vapor.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**



P-U-17 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2025
4.0	15.04.2025	00000000050734 748	Date of first issue: 03.05.2024

Further information Other information	: For multi-pack systems all components. Restricted to profession	s observe material safety data sheets of nal users.
Classification of the mixtu	re:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN