According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : P-P-11 5L 5L Steel jerricans

Product code : 00000000050735049

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture

Thinner

1.3 Details of the supplier of the safety data sheet

Company: Contact address:

BASF Coatings GmbH Postfach 6123 48136 Münster Deutschland BASF plc 4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG

United Kingdom

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single

exposure, Category 3, Central

nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single

exposure, Category 3, Respiratory

H335: May cause respiratory irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

system

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting

Category 3 effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :









Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision

2.0

Revision Date: 05.02.2025

SDS Number: 0000000000050735

Date of last issue: 10.05.2024

049

Date of first issue: 09.05.2023

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting

effects.

Precautionary Statements Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove

contact lenses, if present and easy to do.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Continue rinsing. Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label: Naphtha (petroleum), hydrotreated light, Kp > 140oC

Hydrocarbons, C9, aromatics

isobutyl alcohol

n-butanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

•		I	
Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
Naphtha	64742-52-5	Flam. Liq. 3; H226	>= 25 - < 50
(petroleum),hydrotreated light, Kp > 140oC	265-155-0	STOT SE 3; H336	
	649-465-00-7	(Central nervous	
	01-2119471843-32	system)	
		Asp. Tox. 1; H304	
		Aquatic	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

		Chronic 3; H412	
Hydrocarbons, C9, aromatics	64742-95-6	Flam. Liq. 3; H226	>= 20 - < 25
	265-199-0	STOT SE 3; H336	
	UK-20-	(Central nervous	
	0537843089-5-	system)	
	0000	STOT SE 3; H335	
		(Respiratory	
		system)	
		Asp. Tox. 1; H304	
		Aquatic	
		Chronic 2; H411	
isobutyl alcohol	78-83-1	Flam. Liq. 3; H226	>= 20 - < 25
	201-148-0	Skin Irrit. 2; H315	
	603-108-00-1	Eye Dam. 1; H318	
	UK-20-	STOT SE 3; H335	
	9702550300-0- 0000	(Respiratory	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

	UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	system) STOT SE 3; H336 (Central nervous system)	
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 7 - < 10

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

n-butanol	71-36-3	Flam. Liq. 3; H226	>= 1 - < 2
	200-751-6	Skin Irrit. 2; H315	
	603-004-00-6	Eye Dam. 1; H318	
	UK-20-	STOT SE 3; H335	
	9702550300-0- 0000	(Respiratory system)	
	UK-20- 0537843089-5-	STOT SE 3; H336	
	0000	(Central nervous	
	UK-20-	system)	
	9642318150-0-		
	0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own

safety.

Immediately remove contaminated clothing.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or

the label of the product.

Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48

hours after the accident.

Never give anything by mouth to an unconscious person.

Keep patient warm and at rest.

If inhaled : If breathed in, move person into fresh air.

Call a physician or poison control center immediately.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : If symptoms persist, call a physician.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Do NOT use solvents or thinners.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

In case of eye contact : Immediately wash affected eyes for at least 15 minutes

under running water with eyelids held open, consult an

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control

Center immediately.

Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms

and effects may be included in the GHS labeling phrases

available in Section 2 and in the Toxicological

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

assessments available in Section 11.

Risks : May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.

When inhaled (e.g. during vomiting) risk of pulmonary

oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after

ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.

Treat symptomatically.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing

fighting hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.

equipment for fire-fighters

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water

must be disposed of in accordance with local

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7

and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Use personal protective equipment.

Ensure adequate ventilation, especially in confined

areas.

6.2 Environmental precautions

Environmental precautions: Do not allow uncontrolled discharge of product into the

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

section 13).

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735 049 Date of first issue: 09.05.2023

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures

: Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions

: Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.

Advice on common storage:

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further

information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
isobutyl alcohol	78-83-1	STEL	75 ppm 231 mg/m3	GB EH40
		TWA	50 ppm 154 mg/m3	GB EH40
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/ EU

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Further information: Indicative TWA 2019/1831/ 50 ppm EU 241 mg/m3 Further information: Indicative n-butanol 71-36-3 STEL 50 ppm GB EH40 154 mg/m3 Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN

166)

Required when there is a risk of eye contact.

Hand protection

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

index 1, corresponding > 10 minutes of permeation

time according to EN ISO 374-1)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant

synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits,

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Color : colorless

Odor : of petroleum distillate (e.g. gasoline, kerosene)

pH : substance/mixture is non-polar/aprotic

Melting point/ range : not determined

Boiling point/boiling range : 106 - 179 °CMethod: calculated

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version SDS Number: Date of last issue: 10.05.2024 **Revision Date:**

2.0 05.02.2025 00000000050735

Date of first issue: 09.05.2023 049

: > 28 °C Flash point

Method: ISO 3679

Upper explosion limit / : not determined

Upper flammability limit

Lower explosion limit / Lower flammability limit

: > 35 g/m3

Vapor pressure

not determined

Relative vapor density : Heavier than air.

Density : 0.801 g/cm3 (20 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition : No decomposition if stored and handled as

temperature prescribed/indicated.

Viscosity

Viscosity, kinematic : 6.0 mm2/s (23 °C)

(40 °C)

not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Flow time : < 30 s at 23 °C

Cross section: 3 mm

Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Particle size : The substance / product is marketed or used in a non

solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C9, aromatics:

Partition coefficient: n- : log Pow: 3.17

octanol/water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

GLP: no

isobutyl alcohol:

Partition coefficient: n- : Pow: 10 (25 °C)

octanol/water

log Pow: 1 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)

octanol/water

log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

n-butanol:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Partition coefficient: n-

octanol/water

: log Pow: 1 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface

waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be

disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed

of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1993

ADR : UN 1993

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

RID : UN 1993

IMDG : UN 1993

IATA : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)

ADR : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)

RID : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)

IMDG : FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)

IATA : FLAMMABLE LIQUID, N.O.S.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

(NAPHTHA (PETROLEUM), LIGHT HYDROCRACKED)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 0000000050735

049 Date of first issue: 09.05.2023

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

IMDG

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Packing group : III

Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355

(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable liquid

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

14.5 Environmental hazards

ADN

Environmentally : yes

hazardous

ADR

Environmentally : yes

hazardous

RID

Environmentally : yes

hazardous

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered:

Number on list 72, 5, 3

Number on list 3

Number on list 72, 5, 29, 28

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations : Not applicable

(retained Regulation (EU) 2019/1021 as amended

for Great Britain)

Regulation (EC) on substances that deplete the : Not applicable

ozone layer

UK REACH List of substances subject to : Not applicable

authorisation (Annex XIV)

Control of Major Accident Hazards P5c FLAMMABLE LIQUIDS

P5c

Regulations 2015 (COMAH)

34 Petroleum products: (a)

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

SDS Number: Date of last issue: 10.05.2024 Version Revision Date:

00000000050735 2.0 05.02.2025 Date of first issue: 09.05.2023

049

heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points

(a) to (d)

Volatile organic compounds

: Volatile organic compounds (VOC) content: 803 g/l

Directive 2010/75/EU of 24 November 2010 on

industrial emissions (integrated pollution prevention and

control)

Volatile organic compounds (VOC) content: 100 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Date of last issue: 10.05.2024 Version Revision Date: SDS Number:

00000000050735 2.0 05.02.2025

Date of first issue: 09.05.2023 049

16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

Limit value for maximum VOC content as specified in Annex IIB: VOC content of the ready-for-use product according to ISO 11890-2: 850 g/l

805 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

May be fatal if swallowed and enters airways. H304

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

H335 : May cause respiratory irritation.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Dam. : Serious eye damage

Flam. Liq. : Flammable liquids

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2019/1831/EU : Europe. Commission Directive 2019/1831/EU

establishing a fifth list of indicative occupational

exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

2019/1831/EU / TWA : Limit Value - eight hours

2019/1831/EU / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

(EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data

sheets of all components.

Restricted to professional users.

Classification of the mixture:		Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Dam. 1	H318	Calculation method	
STOT SE 3	Н336	Calculation method	
STOT SE 3	H335	Calculation method	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



P-P-11 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 05.02.2025 00000000050735

049 Date of first issue: 09.05.2023

Asp. Tox. 1 H304 Calculation method

Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN