

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	000000000507362 11	Date of first issue: 13.07.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : G-H-110CL 0,055KG 0,055KG Tubes

Product code : 00000000050736211

Unique Formula Identifier (UFI) : 3AF5-80VX-E004-91H6

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Putty

#### 1.3 Details of the supplier of the safety data sheet

**Company:**

BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

Telephone: +44 161 475 3000  
E-mail address: product-safety-uk-and-ireland@basf.com

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Organic peroxides, Type E  
Eye irritation, Category 2

H242: Heating may cause a fire.  
H319: Causes serious eye irritation.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes





Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

Skin sensitization, Category 1  
Specific target organ toxicity - repeated exposure, Category 2  
Short-term (acute) aquatic hazard, Category 1  
Long-term (chronic) aquatic hazard, Category 1

H317: May cause an allergic skin reaction.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms :    

Signal Word : Warning

Hazard Statements : H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P234 Keep only in original packaging.  
P260 Do not breathe dust.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

Hazardous ingredients which must be listed on the label:

Benzoyl peroxide  
maleic acid dibutyl ester

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 0000000000507362      Date of last issue: 23.08.2025  
11      Date of first issue: 13.07.2024

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : organic peroxide  
polyether  
fillers  
Water  
cellulose ester

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Benzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 25 - < 50
maleic acid dibutyl ester	105-76-0 203-328-4 UK-20-0537843089-5-0000	Skin Sens. 1; H317 STOT RE 2; H373	>= 20 - < 25
Substances with a workplace exposure limit :			
calcium carbonate	471-34-1 207-439-9 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000		>= 1 - < 2
Magnesium carbonate	546-93-0 208-915-9		>= 1 - < 2

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 0000000000507362-11      Date of last issue: 23.08.2025      Date of first issue: 13.07.2024

	UK-20-0537843089-5-0000		
--	-------------------------	--	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person. First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area.
- If inhaled : If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician immediately.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
- If swallowed : Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362 11	Date of first issue: 13.07.2024

### Section 11.

Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause damage to organs through prolonged or repeated exposure.

Dusts may cause mechanical irritation to eyes.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet  
Dry powder  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Has a fire-promoting effect due to release of oxygen.  
Fire will produce dense black smoke containing hazardous combustion products (see section 10).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Cool containers/tanks with water spray.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	000000000507362	Date of first issue: 13.07.2024
		11	

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing dust.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

#### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Avoid dust formation.  
Contain and collect mechanically and dispose of in accordance with local regulations.  
Ensure adequate ventilation.

#### 6.4 Reference to other sections

For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 000000000507362      Date of last issue: 23.08.2025  
11      Date of first issue: 13.07.2024

- Protect from moisture.  
Avoid creating dust.
- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted. Avoid dust formation.
- Hygiene measures : Remove contaminated clothing immediately and dispose of safely.  
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. The product may have contact with suitable materials only, e.g. unpigmented polyethylene or steel to material code St 4571. Always keep in containers of same material as the original one. Observe label precautions. Protect from moisture. Keep in a dry, cool and well-ventilated place.
- Advice on common storage : Reducing agents, heavy metal compounds, acids, alkalis, contamination.  
Oxidizing agents  
Organic materials
- Recommended storage temperature : 5.00 - 25.00 °C
- Packaging material : Suitable material: Polypropylene, Low density polyethylene (LDPE), High density polyethylene (HDPE), Polyethylenetherephthalate (PET)

### 7.3 Specific end use(s)

- Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Benzoyl peroxide	94-36-0	TWA	5 mg/m <sup>3</sup>	GB EH40
calcium carbonate	471-34-1	TWA (inhalable)	10 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 000000000507362      Date of last issue: 23.08.2025  
Date of first issue: 13.07.2024  
11

		dust)		
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Magnesium carbonate	546-93-0	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
tight-fitting protective goggles with face screen

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Preventive skin protection  
chemical-resistant disposable coveralls  
Care should be taken in the selection of protective clothing to ensure that inflammation of the skin at neck and wrists through contact with the powder is avoided.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

Protective measures : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Wear respiratory protection if ventilation is inadequate. Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: paste
Color	: red
Odor	: characteristic
pH	: substance/mixture is non-soluble (in water)
Melting point/ range	: not determined
Boiling point/boiling range	: Study technically not feasible.
Flash point	: not applicable, the product is a solid
Flammability (solid, gas)	: Will not burn
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapor pressure	: not determined (50 °C) not determined (20 °C) The product is a non-volatile solid.
Relative vapor density	: The product is a non-volatile solid.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

---

Density : 1.001 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : not determined  
Partition coefficient: n-octanol/water : not applicable for mixtures  
Autoignition temperature : > 200 °C

Decomposition temperature : The product is capable of self-sustaining progressive thermal decomposition.

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : not determined (40 °C)  
not determined (23 °C)

Flow time : > 670 s at 23 °C  
Cross section: 6 mm  
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Self-Accelerating decomposition temperature (SADT) : 50 °C  
Self-heating substances : The substance or mixture is not classified as self heating.  
Metal corrosion rate : Not corrosive to metals.  
Particle size : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Dust can form an explosive mixture in air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat.  
Avoid direct sunlight.  
Avoid impact, friction and electrostatic loading.  
Avoid dust formation.

### 10.5 Incompatible materials

Materials to avoid : Organic materials  
Oxidizing agents  
Reducing agents, heavy metal compounds, acids, alkalis, contamination.

### 10.6 Hazardous decomposition products

Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

Based on available data, the classification criteria are not met.

##### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 0000000000507362      Date of last issue: 23.08.2025  
Date of first issue: 13.07.2024  
11

### **Carcinogenicity**

Based on available data, the classification criteria are not met.

### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

### **STOT-single exposure**

Based on available data, the classification criteria are not met.

### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

No data available

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

#### **Components:**

#### **Benzoyl peroxide:**

Partition coefficient: n-octanol/water : log Pow: 3.2 (22 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

#### **maleic acid dibutyl ester:**

Partition coefficient: n-octanol/water : log Pow: 3.39 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 3108

ADR : UN 3108

RID : UN 3108

IMDG : UN 3108

IATA : UN 3108

### 14.2 UN proper shipping name

ADN : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

ADR : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

RID : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

IMDG : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 0000000000507362      Date of last issue: 23.08.2025  
Date of first issue: 13.07.2024  
11

**IATA** : PEROXIDE)  
(DIBENZOYL PEROXIDE)  
: ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 5.2	
<b>ADR</b>	: 5.2	
<b>RID</b>	: 5.2	
<b>IMDG</b>	: 5.2	
<b>IATA</b>	: 5.2	HEAT

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : P1  
Labels : 5.2

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : P1  
Labels : 5.2  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : P1  
Hazard Identification Number : 539  
Labels : 5.2

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 5.2  
EmS Code : F-J, S-R

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxide, Keep Away From Heat

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 570

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

Packing group : Not assigned by regulation  
Labels : Organic Peroxide, Keep Away From Heat

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : yes

**ADR**  
Environmentally hazardous : yes

**RID**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
	E1	ENVIRONMENTAL HAZARDS

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Not applicable

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

## SECTION 16: Other information

### Full text of H-Statements

H241 : Heating may cause a fire or explosion.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Irrit. : Eye irritation  
Org. Perox. : Organic peroxides  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA -

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version 4.0      Revision Date: 13.10.2025      SDS Number: 0000000000507362      Date of last issue: 23.08.2025  
Date of first issue: 13.07.2024  
11

European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : Restricted to professional users.  
For multi-pack systems observe material safety data sheets of all components.

#### Classification of the mixture:

Org. Perox. E	H242
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## G-H-110CL 0,055KG 0,055KG Tubes

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
4.0	13.10.2025	0000000000507362	Date of first issue: 13.07.2024
		11	

---

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN