

# Safety data sheet

Page: 1/14

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2024 Version: 2.1

Product: **P-B-14 1,4KG** 

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

# 1. Identification

**Product identifier** 

# P-B-14 1,4KG

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Putty

# Details of the supplier of the safety data sheet

Company:
BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland

Telephone: +49/2501/143688

E-mail address: product-safety-coatings@basf.com

# **Emergency telephone number**

International emergency number: Telephone: +49 180 2273-112

## 2. Hazards Identification

# Classification of the substance or mixture

According to UN GHS criteria

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

Skin Corr./Irrit. 2 Eye Dam./Irrit. 2A Skin Sens. 1A Repr. 2 (unborn child) STOT RE 1 Aquatic Acute 3 Flam. Liq. 3

For the classifications not written out in full in this section the full text can be found in section 16.

#### Label elements

# Globally Harmonized System, UN (GHS)

#### Pictogram:







# Signal Word: Danger

### Hazard Statement:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eve irritation.

H361 Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

# Precautionary Statements (Prevention):

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P260 Do not breathe dust or mist.

P270 Do not eat, drink or smoke when using this product.

P202 Do not handle until all safety precautions have been read and

understood.

P240 Ground and bond container and receiving equipment.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P264 Wash contaminated body parts thoroughly after handling.

# Precautionary Statements (Response):

Date / Revised: 08.10.2024 Version: 2.1

Product: **P-B-14 1,4KG** 

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

	Date of plint 12.10.202
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P314	Get medical advice/attention if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

#### Other hazards

# According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# 3. Composition/Information on Ingredients

# **Substances**

Not applicable

# **Mixtures**

# Chemical nature

fillers, organic compounds, pigment, unsaturated polyester resin

Hazardous ingredients (GHS)

According to UN GHS criteria

Styrene

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

Content (W/W): >= 15 % - < 20 % Asp. Tox. 1 CAS Number: 100-42-5 Flam. Lig. 3

EC-Number: 202-851-5 Acute Tox. 4 (Inhalation - vapour)

Skin Irrit. 2 Eve Irrit. 2A

Repr. 2 (unborn child)

STOT SE 3 (irr. to respiratory syst.)

STOT RE (Auditory organ) 1

Aquatic Acute 2 Aquatic Chronic 3

H226, H319, H315, H332, H304, H335, H361,

H372, H412, H401

Maleic anhydride

Content (W/W): > 0 % - < 0,1 % Acute Tox. 4 (oral)
CAS Number: 108-31-6 Skin Corr. 1B
EC-Number: 203-571-6 Eye Dam. 1
Skin Sens. 1A
Resp. Sens. 1

STOT RE (Respiratory system) 1 (by inhalation)

Aquatic Acute 3

H302, H334, H317, H314, H372, H402

EUH071

Specific concentration limit: Skin Sens. 1A: >= 0,001 %

For the classifications not written out in full in this section the full text can be found in section 16.

#### 4. First-Aid Measures

# Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

# If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

# On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

#### On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

# Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, allergic symptoms, skin irritation, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Antidote: No known specific antidote.

# 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media: carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

### Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

# Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

#### Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

#### 6. Accidental Release Measures

#### Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

# **Environmental precautions**

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

# Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

# 7. Handling and Storage

# Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

#### Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

# Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)
Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

### Specific end use(s)

Please refer to the technical leaflet for further information.

# 8. Exposure Controls/Personal Protection

#### **Control parameters**

Components with occupational exposure limits

No occupational exposure limits known.

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

# **Exposure controls**

#### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. full face mask with AB2P3 class combination filter

#### Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

#### Eye protection:

Eye protection not required., Required when there is a risk of eye contact.

# Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

# General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

# 9. Physical and Chemical Properties

# 9.1. Information on basic physical and chemical properties

State of matter: liquid
Form: liquid
Colour: yellow
Odour: of styrene

Melting point:

not determined

onset of boiling:

not determined

Flammability: Flammable liquid and vapour.

Lower explosion limit: 36 g/m3 Flash point: 30 °C

30 °C (ISO 3679)

Auto-ignition temperature: > 200 °C

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

pH value:

substance/mixture is non-soluble (in

water)

Viscosity, kinematic: 411,6 mm2/s

(23 °C)

(40 °C)

No data available.

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Vapour pressure:

(20 °C)

not determined

(50 °C)

not determined 1,760 g/cm3

(20 °C)

Relative vapour density (air):

Heavier than air.

#### 9.2. Other information

# Information with regard to physical hazard classes

**Explosives** 

Density:

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Flammable solids

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready

specified in paragraph 33.2.4.4 of UN combustible solids))

manual of tests and criteria.

Self-heating substances and mixtures

Self heating ability: It is not a material capable of

spontaneous heating

#### Other safety characteristics

Miscibility with water:

immiscible

Flow time: > 60 s (DIN EN ISO 2431; 6 mm)

(23 °C)

# 10. Stability and Reactivity

# Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

# **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

Date / Revised: 08.10.2024 Version: 2.1

Product: **P-B-14 1,4KG** 

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

# Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

### Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

# Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

# Hazardous decomposition products

:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

# 11. Toxicological Information

# Information on toxicological effects

# Acute toxicity

Assessment of acute toxicity:

Based on available data, the classification criteria are not met.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

# **Irritation**

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

# Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

#### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies suggest a fertility impairing effect.

### **Developmental toxicity**

Assessment of teratogenicity:

Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

# Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure to small quantities may affect certain organs.

#### Aspiration hazard

No aspiration hazard expected.

# 12. Ecological Information

# **Toxicity**

Assessment of aquatic toxicity:

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

### Persistence and degradability

Assessment biodegradation and elimination (H2O):

Biological degradability of hazardous substances mentioned in section 3:

Information on: Styrene Elimination information:

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

70,9 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic)

Information on: Maleic anhydride

Elimination information:

93 % DOC reduction (21 d) (OECD 301E/92/69/EWG, C.4-B) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable (according to OECD criteria).

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

\_\_\_\_\_

# Bioaccumulative potential

Bioaccumulation potential:

No data available.

# Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

# 13. Disposal Considerations

#### Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

# 14. Transport Information

#### **Land transport**

**ADR** 

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

**RID** 

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for

user:

None known

#### **Inland waterway transport**

ADN

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for

user:

None known

# Transport in inland waterway vessel

Not evaluated

# Sea transport

**IMDG** 

UN number or ID number: UN 1263 UN proper shipping name: PAINT

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Marine pollutant: NO

Special precautions for

user:

EmS: F-E; S-E

### Air transport

IATA/ICAO

UN number or ID number: UN 1263 UN proper shipping name: PAINT

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for

user:

None known

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

# Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

#### **Further information**

Not dangerous goods of class 3 in packages up to 450 litres capacity (valid for ADR, ADNR, RID, TDG and USDOT).

# 15. Regulatory Information

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

# 16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Sens. Skin sensitization
Repr. Reproductive toxicity

STOT RE Specific target organ toxicity — repeated exposure Aquatic Acute Hazardous to the aquatic environment - acute

Flam. Liq. Flammable liquids
Asp. Tox. Aspiration hazard
Acute Tox. Acute toxicity
Skin Irrit. Skin irritation
Eye Irrit. Eye irritation

STOT SE Specific target organ toxicity — single exposure Aquatic Chronic Hazardous to the aquatic environment - chronic

Skin Corr.

Eye Dam.

Resp. Sens.

H226

H319

Skin corrosion

Serious eye damage

Respiratory sensitization

Flammable liquid and vapour.

Causes serious eye irritation.

H315 Causes skin irritation. H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H361 Suspected of damaging the unborn child.

H372 Causes damage to organs (Auditory organ) through prolonged or

repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H401 Toxic to aquatic life. H302 Harmful if swallowed.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H314 Causes severe skin burns and eye damage.

Page: 14/14

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2024 Version: 2.1

Product: P-B-14 1,4KG

(ID no. 50742682/SDS\_GEN\_00/EN)

Date of print 12.10.2024

H372 Causes damage to organs (Respiratory system) through prolonged or

repeated exposure (inhalation).

H402 Harmful to aquatic life.

EUH071 Corrosive to the respiratory tract.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.