

Safety data sheet

Page: 1/16

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

1. Identification

Product identifier

922-180 PRO/330 30L

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: hardener

Details of the supplier of the safety data sheet

Company:BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland

Telephone: +49/2501/143688

E-mail address: product-safety-coatings@basf.com

Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Acute Tox. 5 (Inhalation - vapour)
 Skin Corr./Irrit. 3
 Eye Dam./Irrit. 2A
 Asp. Tox. 1
 Skin Sens. 1
 STOT SE 3 (irritating to respiratory system)
 STOT SE 3 (May cause drowsiness and dizziness.)
 Aquatic Acute 3
 Aquatic Chronic 3
 Flam. Liq. 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System, UN (GHS)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304 + P312	IF INHALED: Call a POISON CENTER or physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P331	Do NOT induce vomiting.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

polyisocyanate, organic solvent

Hazardous ingredients (GHS)

According to UN GHS criteria

n-Butyl acetate

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

Content (W/W): $\geq 30\%$ - $< 50\%$ CAS Number: 123-86-4 EC-Number: 204-658-1 INDEX-Number: 607-025-00-1	Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) Aquatic Acute 3 H226, H336, H402 EUH066
HDI-Oligomer(Trimer) Content (W/W): $\geq 20\%$ - $< 25\%$ CAS Number: 28182-81-2 REACH registration number: 01-2119485796-17	Acute Tox. 4 (Inhalation - dust) Acute Tox. 4 (Inhalation - vapour) Skin Sens. 1 STOT SE 3 (irr. to respiratory syst.) H332, H317, H335 EUH204
2-Methoxy-1-methylethyl acetate Content (W/W): $\geq 12,5\%$ - $< 15\%$ CAS Number: 108-65-6 EC-Number: 203-603-9 INDEX-Number: 607-195-00-7	Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) H226, H336
3-Methoxybutyl acetate Content (W/W): $\geq 7\%$ - $< 10\%$ CAS Number: 4435-53-4 EC-Number: 224-644-9	Flam. Liq. 4 Acute Tox. 5 (oral) Aquatic Acute 2 H227, H303, H401
Solventnaphtha (petroleum), light aromatic Content (W/W): $\geq 7\%$ - $< 10\%$ CAS Number: 64742-95-6 REACH registration number: 01-2119455851-35	Asp. Tox. 1 Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) STOT SE 3 (irr. to respiratory syst.) Aquatic Chronic 2 H411, H226, H304, H336, H335 EUH066
IPDI Homopolymer Content (W/W): $\geq 5\%$ - $< 7\%$ CAS Number: 53880-05-0 REACH registration number: 01-2119980716-25	Acute Tox. 4 (Inhalation - dust) Acute Tox. 4 (Inhalation - vapour) Skin Sens. 1 STOT SE 3 (irr. to respiratory syst.) H332, H317, H335 EUH204
2-Butoxyethyl acetate	

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

	Content (W/W): $\geq 3\%$ - $< 5\%$	Flam. Liq. 4
	CAS Number: 112-07-2	Acute Tox. 4 (oral)
	EC-Number: 203-933-3	Acute Tox. 4 (dermal)
	INDEX-Number: 607-038-00-2	Aquatic Acute 3
		H227, H302 + H312, H402
Xylene	Content (W/W): $\geq 2,5\%$ - $< 3\%$	Asp. Tox. 1
	CAS Number: 1330-20-7	Flam. Liq. 3
	EC-Number: 215-535-7	Acute Tox. 5 (Inhalation - vapour)
	INDEX-Number: 601-022-00-9	Acute Tox. 5 (oral)
		Skin Irrit. 2
		Eye Irrit. 2B
		STOT SE 3 (irr. to respiratory syst.)
		Aquatic Chronic 3
		STOT RE (Central nervous system, Liver, Kidney) 2
		Aquatic Acute 2
		H226, H320, H315, H304, H335, H373, H303 + H333, H412, H401
(3-glycidoxypropyl) trimethoxysilane	Content (W/W): $\geq 2\%$ - $< 2,5\%$	Eye Dam./Irrit. 1
	CAS Number: 2530-83-8	Acute Tox. 5 (dermal)
	EC-Number: 219-784-2	H318, H313
	REACH registration number: 01-2119513212-58	
Ethyl 3-ethoxypropionate	Content (W/W): $\geq 1\%$ - $< 2\%$	Flam. Liq. 3
	CAS Number: 763-69-9	Acute Tox. 5 (oral)
	EC-Number: 212-112-9	Aquatic Acute 3
	REACH registration number: 01-2119463267-34	Acute Tox. 5 (dermal)
		H226, H303 + H313, H402

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Flush with copious amounts of water for at least 15 minutes. Immediate medical attention required.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Keep at rest. Rinse mouth immediately with water.

Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, aspiration pneumonia, allergic symptoms, dazed state, irritation of respiratory tract, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Indication of any immediate medical attention and special treatment needed

Treatment: Symptoms: After contact with bodyfluids in the gastrointestinal tract, the product can hydrolyse and form additional methanol. Therefore, carefully observe if you experience any signs/symptoms of methanol intoxication, taking into account the period of latency of several days.

5. Fire-Fighting Measures**Extinguishing media**

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

nitrogen oxides

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13). Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Care should be taken when reopening partly used containers (pressurization!). Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from strongly acid and strongly alkaline materials, from oxidizing agents, amines, alcohols and water.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

Specific end use(s)

Please refer to the technical leaflet for further information.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

108-65-6: 2-Methoxy-1-methylethyl acetate

112-07-2: 2-Butoxyethyl acetate

123-86-4: n-Butyl acetate

1330-20-7: Xylene

Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. full face mask with AB2P3 class combination filter

Hand protection:

Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Eye protection:

Eye protection not required., Required when there is a risk of eye contact.

Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application. Avoid contact with the skin, eyes and clothing. Handle in accordance

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. Respiratory protective equipment should be worn by spray booth operatives. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid
Form:	liquid
Colour:	colourless
Odour:	pungent
Melting point:	not determined
onset of boiling:	not determined
Flammability:	Flammable liquid and vapour.
Lower explosion limit:	36 g/m ³
Flash point:	29 °C (ISO 3679)
Auto-ignition temperature:	> 200 °C
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
pH value:	substance/mixture reacts violently with water
Viscosity, kinematic:	7,3 mm ² /s (23 °C)
	(40 °C)
	No data available.
Solubility in water:	Reacts with water.
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures
Vapour pressure:	(20 °C)
	not determined
	(50 °C)
	not determined
Density:	0,966 g/cm ³ (20 °C)
Relative vapour density (air):	Heavier than air.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Flammable solids

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready specified in paragraph 33.2.4.4 of UN manual of tests and criteria. combustible solids))

Self-heating substances and mixtures

Self heating ability: It is not a material capable of spontaneous heating

Other safety characteristics

Miscibility with water:

immiscible

Flow time:

> 30 s

(DIN EN ISO 2431; 3 mm)

(23 °C)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

Conditions to avoid

Avoid direct contact with water. Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

Substances to avoid:

Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

Hazardous decomposition products

:

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic by inhalation.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Information on: 2-Butoxyethyl acetate

Experimental/calculated data:

LC50 rat (by inhalation): > 400 ppm 4 h (OECD Guideline 403)

No mortality was observed. Highest concentration technically achievable. The vapour was tested.

Information on: IPDI Homopolymer

Experimental/calculated data:

LC50 rat (by inhalation): 3,500 mg/l 4,0 h (OECD Guideline 403)

An aerosol was tested.

Irritation

Assessment of irritating effects:
The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes slight irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

Other relevant toxicity information

The product/substance will be cleaved in the body after uptake, thereby methanol will be formed. The toxicity of methanol has to be considered. Based on the properties of the isocyanate components and considering toxicological data on similar product, this product may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.

The product/substance will be cleaved in the body after uptake, thereby methanol will be formed. The toxicity of methanol has to be considered. Based on the properties of the isocyanate components and considering toxicological data on similar product, this product may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Biological degradability of hazardous substances mentioned in section 3:

Information on: 2-Butoxyethyl acetate

Elimination information:

88 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic)

Information on: n-Butyl acetate

Elimination information:

80 % BOD of the ThOD (5 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: Ethyl 3-ethoxypropionate

Elimination information:

100 % CO₂ formation relative to the theoretical value (28 d) (Directive 84/449/EEC, C.5) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable.

100 % CO₂ formation relative to the theoretical value (18 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic)

Information on: Xylene

Elimination information:

87,8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: 3-Methoxybutyl acetate

Elimination information:

90 - 100 % DOC reduction (12 d) (OECD 301E; 84/449/EWG, C.3) (aerobic, other)

Bioaccumulative potential

Bioaccumulation potential:

No data available.

Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

13. Disposal Considerations

Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Residues in empty containers should be neutralised with decontaminant (see section 6).

14. Transport Information

Land transport

ADR

UN number or ID number: UN1263

UN proper shipping name: PAINT

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1263

UN proper shipping name: PAINT

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

Inland waterway transport

ADN

UN number or ID number: UN1263

UN proper shipping name: PAINT

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

IMDG

UN number or ID number: UN 1263

UN proper shipping name: PAINT

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-E; S-E

Air transport

IATA/ICAO

UN number or ID number: UN 1263

UN proper shipping name: PAINT

Transport hazard class(es): 3

Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: None known

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Asp. Tox.	Aspiration hazard
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation

 Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 18.07.2024

Version: 6.1

Product: **922-180 PRO/330 30L**

(ID no. 50784398/SDS_GEN_00/EN)

Date of print 19.07.2024

Eye Irrit.	Eye irritation
STOT RE	Specific target organ toxicity — repeated exposure
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H227	Combustible liquid.
H303	May be harmful if swallowed.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H304	May be fatal if swallowed and enters airways.
H302 + H312	Harmful if swallowed or in contact with skin.
H320	Causes eye irritation.
H315	Causes skin irritation.
H373	May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
H303 + H333	May be harmful if swallowed or if inhaled.
H412	Harmful to aquatic life with long lasting effects.
H318	Causes serious eye damage.
H313	May be harmful in contact with skin.
H303 + H313	May be harmful if swallowed or in contact with skin.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

 Vertical lines in the left hand margin indicate an amendment from the previous version.