

Safety data sheet

Page: 1/15

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

1. Identification

Product identifier

22-A 105 1L HS REDUCED OCHRE BASE

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monocoat product

Details of the supplier of the safety data sheet

Company:
BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland

Telephone: +49/2501/143688

E-mail address: product-safety-coatings@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Skin Sens. 1A

STOT SE 3 (irritating to respiratory system)

STOT SE 3 (May cause drowsiness and dizziness.)

Aquatic Acute 3 Aquatic Chronic 2 Flam. Liq. 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System, UN (GHS)

Pictogram:







Signal Word: Warning

Hazard Statement:

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P240 Ground and bond container and receiving equipment.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P271 Use only outdoors or in a well-ventilated area.

Precautionary Statements (Response):

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

P312	Call a POISON CENTER or	physician if v	ou feel unwell.

P391 Collect spillage.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray for extinction.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

acrylic resin, organic solvent, pigment

Hazardous ingredients (GHS)

According to UN GHS criteria

Solventaphtha (petroleum), light aromatic

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Content (W/W): >= 25 % - < 30 % Asp. Tox. 1 CAS Number: 64742-95-6 Flam. Liq. 3

REACH registration number: 01- S

2119455851-35

STOT SE 3 (drowsiness and dizziness) STOT SE 3 (irr. to respiratory syst.)

Aquatic Chronic 2

H411, H226, H304, H336, H335

EUH066

n-Butyl acetate

Content (W/W): >= 10 % - < 12,5 Flam. Liq. 3

%

STOT SE 3 (drowsiness and dizziness)

CAS Number: 123-86-4 Aquatic Acute 3 EC-Number: 204-658-1 H226, H336, H402

INDEX-Number: 607-025-00-1 EUH066

Heptan-2-one

Content (W/W): >= 3 % - < 5 % Flam. Liq. 3

CAS Number: 110-43-0 Acute Tox. 4 (Inhalation - vapour)

EC-Number: 203-767-1 Acute Tox. 4 (oral)

INDEX-Number: 606-024-00-3 Skin Irrit. 3

STOT SE 3 (drowsiness and dizziness)

Aquatic Acute 3

H226, H316, H336, H302 + H332, H402

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

Content (W/W): >= 0,5 % - < 1 % Acute Tox. 5 (oral) CAS Number: 41556-26-7 Skin Sens. 1A EC-Number: 255-437-1 Repr. 2 (fertility)

Repr. 2 (fertility) Aquatic Acute 1 Aquatic Chronic 1 M-factor acute: 1

H303, H317, H361, H400, H410

Methyl methacrylate

Content (W/W): >= 0,3 % - < 0,5 % Flam. Liq. 2

CAS Number: 80-62-6 Acute Tox. 5 (Inhalation - vapour)

EC-Number: 201-297-1 Skin Irrit. 2

INDEX-Number: 607-035-00-6 STOT SE 3 (irr. to respiratory syst.)

Aquatic Acute 3 Skin Sens. 1B

H225, H315, H333, H317, H335, H402

2-Hydroxyethyl methacrylate

Content (W/W): >= 0,3 % - < 0,5 % Eye Irrit. 2B CAS Number: 868-77-9 Skin Sens. 1B EC-Number: 212-782-2 H320, H317

INDEX-Number: 607-124-00-X

Isodecyl methacrylate

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Content (W/W): >= 0,3 % - < 0,5 % Skin Corr./Irrit. 2

CAS Number: 29964-84-9 STOT SE 3 (irr. to respiratory syst.)

EC-Number: 249-978-2 Aquatic Chronic 1
REACH registration number: 012119894925-17 Eye Dam./Irrit. 2A
M-factor acute: 1

M-factor chronic: 1 H319, H315, H410, H335

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Content (W/W): >= 0,2 % - < 0,3 % Acute Tox. 5 (oral)
CAS Number: 82919-37-7 Skin Sens. 1A
EC-Number: 280-060-4 Repr. 2 (fertility)
Aquatic Acute 1
Aquatic Chronic 1

Aquatic Chronic 1
M-factor acute: 1
M-factor chronic: 1

H303, H317, H361, H400, H410

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: allergic symptoms, dazed state, irritation of respiratory tract, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Antidote: No known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)
Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Specific end use(s)

Please refer to the technical leaflet for further information.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

80-62-6: Methyl methacrylate 110-43-0: Heptan-2-one 123-86-4: n-Butyl acetate

Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Eye protection:

Eye protection not required., Required when there is a risk of eye contact.

Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid Form: liquid Colour: yellow

Odour: of hydrocarbons

Odour threshold:

not determined

Melting point:

not determined

onset of boiling:

not determined

Flammability: Flammable liquid and vapour.

Lower explosion limit: 36 g/m3

Upper explosion limit:

not determined

Flash point: 31 °C (ISO 3679)

Auto-ignition temperature: > 200 °C

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

pH value:

substance/mixture is non-

polar/aprotic

Viscosity, kinematic: 297,8 mm2/s

(23 °C)

(40 °C)

No data available.

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

(DIN EN ISO 2431; 6 mm)

Date of print 14.06.2024

Solubility in water: not determined

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Vapour pressure:

(20 °C)

not determined

(50 °C)

not determined

Density: 1,015 g/cm3

(20 °C)

Relative vapour density (air):

Heavier than air.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Flammable solids

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready

specified in paragraph 33.2.4.4 of UN combustible solids))

manual of tests and criteria.

Self-heating substances and mixtures

Self heating ability: It is not a material capable of

spontaneous heating

Other safety characteristics

Miscibility with water:

immiscible

Flow time: > 44 s

(23 °C)

Evaporation rate:

not determined

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

Page: 10/15

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

.

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Based on available data, the classification criteria are not met.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Based on available data, the classification criteria are not met.

Respiratory/Skin sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Toxic to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Biological degradability of hazardous substances mentioned in section 3:

Information on: Methyl methacrylate

Elimination information:

94 % BOD of the ThOD (14 d) (OECD 301C; ISO 9408; 92/69/EWG, C.4-F) (aerobic, activated sludge) Readily biodegradable.

Information on: Heptan-2-one

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Elimination information:

69 % DOC reduction (28 d) (OECD Guideline 310) (aerobic, activated sludge, domestic, non-adapted)

Information on: n-Butyl acetate

Elimination information:

80 % BOD of the ThOD (5 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, municipal sewage

treatment plant effluent)

Bioaccumulative potential

Bioaccumulation potential:

No data available.

Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

13. Disposal Considerations

Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

ADR

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3, EHSM

Packing group: III Environmental hazards: yes

Special precautions for Tunnel code: D/E

user:

RID

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3, EHSM

Packing group:

Environmental hazards: yes

Special precautions for

user:

None known

Inland waterway transport

ADN

UN number or ID number: UN1263 UN proper shipping name: PAINT

Transport hazard class(es): 3, EHSM

Packing group:

Environmental hazards: yes

Special precautions for

None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 1263

UN proper shipping name: PAINT (Solventaphtha (petroleum), light aromatic)

Transport hazard class(es): 3, EHSM Packing group: III

Environmental hazards: yes

Marine pollutant: YES

Special precautions for

user:

EmS: F-E; S-E

Air transport

IATA/ICAO

UN number or ID number: UN 1263 UN proper shipping name: PAINT

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for

user:

None known

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Sens. Skin sensitization

STOT SE Specific target organ toxicity — single exposure
Aquatic Acute Hazardous to the aquatic environment - acute
Aquatic Chronic Hazardous to the aquatic environment - chronic

Flam. Liq. Flammable liquids
Asp. Tox. Aspiration hazard
Acute Tox. Acute toxicity
Skin Irrit. Skin irritation

Repr. Reproductive toxicity

Eye Irrit. Eye irritation

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

H411 Toxic to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness. H335 May cause respiratory irritation.

H402 Harmful to aquatic life.
H316 Causes mild skin irritation.
H302 + H332 Harmful if swallowed or if inhaled.
H303 May be harmful if swallowed.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility.

H361 Suspected of damaging to Wery toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.
H333 May be harmful if inhaled.
H320 Causes eye irritation.
H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the

Page: 15/15

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 13.06.2024 Version: 5.0

Product: 22-A 105 1L HS REDUCED OCHRE BASE

(ID no. 50794198/SDS_GEN_00/EN)

Date of print 14.06.2024

corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.