

# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b> Trade name	: C-C-30 5L 5L Steel jerricans C-C-30 5L 5L Steel jerricans		
Product code	: 0000000050794559		
1.2 Relevant identified uses of the Use of the Substance/Mixture	e substance or mixture and uses advised against : Spraying Clearcoat product		
1.3 Details of the supplier of the safety data sheetContact address:Company:Contact address:BASF Coatings GmbHBASF plcPostfach 61234th and 5th Floors, 2 Stockport Exchange48136 MünsterRailway Road, Stockport, SK1 3GGDeutschlandUnited Kingdom			

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



## C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

**1.4 Emergency telephone** 

International emergency number: Telephone: +49 180 2273-112

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794	Date of first issue: 25.04.2025
		559	Dute of mot 1550c. 25.0 1.2025

#### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H226	Flammable liquid and vapor.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H373	May cause damage to organs through prolonged or repeated exposure.
		H412	Harmful to aquatic life with long lasting effects.



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Precautionary : Statements	<b>Preventio</b> P210	n: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe mist or vapors.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	<b>Response</b> P303 + P3	e: 361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P370 + P3	378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label: Benzoic acid



### C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

#### bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : acrylic resin

organic solvent

#### Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	number		
2-heptanone	110-43-0	Flam. Liq. 3; H226	>= 12.5 - < 15
	203-767-1	Acute Tox. 4;	
	606-024-00-3	H302	
	UK-20- 0537843089-5-	Acute Tox. 4; H332	
	0000	STOT SE 3; H336	
		(Central nervous system)	
n-Butyl acetate	123-86-4	Flam. Liq. 3; H226	>= 2 - < 2.5
	204-658-1	STOT SE 3; H336	
	607-025-00-1	(Central nervous	
	UK-20-	system)	
	9702550300-0-		
	0000		
	UK-20- 0537843089-5-		



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	0000		
	UK-20- 9642318150-0- 0000		
xylene	1330-20-7	Flam. Liq. 3; H226	>= 1 - < 2
	215-535-7 601-022-00-9	Acute Tox. 4; H332 Acute Tox. 4;	
	UK-20- 2749242067-7- 0000	H312 Skin Irrit. 2; H315	
	UK-20- 9702550300-0- 0000	Eye Irrit. 2; H319 STOT SE 3; H335	
	UK-20- 0537843089-5-	(Respiratory system)	
	0000	STOT RE 2; H373	
	UK-20- 9642318150-0-	(Kidney, Liver, Central nervous	



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	0000	system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
Benzenepropanoic acid, 3-(2H- benzotriazol-2-yl)-5-(1,1- dimethylethyl)-4-hydroxy-, C7-9- branched and linear alkyl esters	127519-17-9 407-000-3 607-281-00-4 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Aquatic Chronic 2; H411	>= 1 - < 2
Benzoic acid	65-85-0 200-618-2 607-705-00-8 UK-20-	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 1; H372 (lung)	>= 1 - < 2



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	9702550300-0- 0000		
	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		
bis(1,2,2,6,6-pentamethyl-4- piperidyl)sebacate	41556-26-7 255-437-1 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.5 - < 1
Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7 280-060-4	Skin Sens. 1A; H317	>= 0.2 - < 0.25



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410
--	--

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first-aid measures

General advice	: First aid personnel should pay attention to their own safety.
	If the patient is likely to become unconscious, place and
	transport in stable sideways position (recovery position).
	Immediately remove contaminated clothing.
	In all cases of doubt, or when symptoms persist, seek
	medical attention.
	Move out of dangerous area.
	Never give anything by mouth to an unconscious person.



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

If inhaled	:	If symptoms persist, call a physician.
		If breathed in, move person into fresh air.
		If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact	:	If symptoms persist, call a physician.
		Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
		Do NOT use solvents or thinners.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
		Call a physician immediately.
		If easy to do, remove contact lens, if worn.



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

If swallowed	: If symptoms persist, call a physician.
	Do NOT induce vomiting.
	Rinse mouth.
4.2 Most important symptom	s and effects, both acute and delayed
Symptoms	: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Risks	: May cause an allergic skin reaction.
	Causes serious eye irritation.
	May cause damage to organs through prolonged or repeated exposure.

Treatment	: No known specific antidot	e.
-----------	-----------------------------	----



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794	Date of first issue: 25.04.2025
		559	Date of first 155de: 25.0 1.2025

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing	: Water spray jet
media	Dry powder
	Alcohol-resistant foam
	Carbon dioxide (CO2)

Unsuitable extinguishing : High volume water jet media

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire :	Fire will produce dense black smoke containing
fighting	hazardous combustion products (see section 10).



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

5.3 Advice for firefighters		
Special protective	:	Approp

Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Further information	:	In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Avoid breathing vapours.
		Keep away from sources of ignition.
		Advice on product handling can be found in sections 7
		and 8 of this safety data sheet.



### C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

For non-emergency personnel: For emergency responders: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Ensure adequate ventilation.	
-------------------------	---	------------------------------	--

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

<b>7.1 Precautions for safe handling</b> Advice on safe handling :	Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
	The workplace should be equipped with an emergency shower and eye-rinsing facility.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.
	Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	<ul> <li>Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.</li> </ul>



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Hygiene measures	:	Remove contaminated clothing immediately and dispose
		of safely. Wash hands before breaks and at the end of
		workday. Keep away from food, drink and animal
		feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on : storage conditions	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Advice on common storage :	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage : 35.00 °C temperature



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Packaging material	: Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)
7.3 Specific end use(s)	
Specific use(s)	: Please refer to the technical leaflet for further
	information.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal			



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	absorption will lead to systemic toxicity.					
		TWA 50 ppm GB EH40				
			237 mg/m3			
	Further infor	rmation: Can be ab	sorbed through the skin. T	The assigned		
	substances a	are those for which	there are concerns that d	ermal		
	absorption v	vill lead to systemic	c toxicity.			
	TWA         50 ppm         2000/39/EC					
			238 mg/m3			
	Further information: Identifies the possibility of significant uptake					
	through the skin, Indicative					
		STEL	100 ppm	2000/39/EC		
			475 mg/m3			
	Further information: Identifies the possibility of significant uptake					
	through the skin, Indicative					
n-Butyl acetate	123-86-4	TWA	150 ppm	GB EH40		
			724 mg/m3			



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

		STEL	200 ppm	GB EH40
			966 mg/m3	
		STEL	150 ppm	2019/1831/
			723 mg/m3	EU
	Further info	rmation: Indicative		
		TWA	50 ppm	2019/1831/
			241 mg/m3	EU
	Further info	rmation: Indicative		1
xylene	1330-20-7	TWA	50 ppm	GB EH40
			220 mg/m3	
	Further info	rmation: Can be ab	sorbed through the skin.	The assigned
	substances a	are those for which	there are concerns that d	ermal
	absorption v	will lead to systemi	c toxicity.	
		STEL	100 ppm	GB EH40
			441 mg/m3	
	Further info	rmation: Can be ab	sorbed through the skin.	The assigned



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
	TWA	50 ppm 221 mg/m3	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative			
	STEL	100 ppm 442 mg/m3	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative			

### **Biological occupational exposure limits**

Substance name	CAS-No.	Control	Sampling time	Basis
		parameters		
xylene	1330-20-7	methyl hippuric	After shift	GB EH40
		acid: 650		BAT
		Millimoles per		
		mole creatinine		



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

		(Urine)		
8.2 Exposure controls				
Engineering measures Ensure adequate ventilatior	۱.			
Personal protective equip	ment			
Eye/face protection	: Tight 166)	ly fitting safety goggle	es (splash goggles) (e	e.g. EN
	Requ	ired when there is a r	isk of eye contact.	
Hand protection				
Remarks	certif rubbe inforr manu inforr mate produ work	protective gloves. An ied according to EN IS er gloves - material thi nation on penetration facturer of the glove. nation from the glove rial manufacturer or a fuct components. The so place should be discus rotective gloves. Requ	O 374-1 is suitable: ickness: 0.5 mm Furt time is available fro Data are based on manufacturer, the r iccording to specifics suitability for a speci	e.g. butyl ther om the raw s of the ific cers of



## C-C-30 5L 5L Steel jerricans

Version Revision 1.0 25.04.

 Revision Date:
 SDS

 25.04.2025
 0000

 559

SDS Number:Date of last issue: -00000000050794Date of first issue: 25.04.2025

		permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short- term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Skin and body protection	:	chemical-resistant disposable coveralls
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the



## C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	exposure limit they must use appropriate certified respirators.
	In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures :	Do not breathe vapour/spray.
	Eye wash fountains and safety showers must be easily accessible.
	If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: colorless
Odor	: ketone-like



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

рН	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	37 °C Method: ISO 3679
Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	5.0000 hPa (20 °C)
		not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.016 g/cm3 (20 °C)
Solubility(ies) Water solubility Partition coefficient: n-	:	not determined not applicable for mixtures



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

octanol/water Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	340.7 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	> 50 s Cross section: 6 mm
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
<b>9.2 Other information</b> Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.



### C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794	
		559	Date of first issue: 25.04.2025

Particle size : The substance / product is marketed or used in a non solid or granular form.

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Protect from frost.

Heat, flames and sparks.

Heat.

#### **10.5 Incompatible materials**



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and
		strongly acid materials in order to avoid exothermic
		reactions.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
<u>Components:</u>		
2-heptanone:		
Acute oral toxicity	:	LD50 (Rat): 1,600 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 16.7 mg/l Exposure time: 4 h
		Test atmosphere: vapor
Skin corrosion/irritation		
Based on available data, the	clas	sification criteria are not met.
Components:		
n-Butyl acetate:		
Result	:	Repeated exposure may cause skin dryness or cracking.



### C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration toxicity

Based on available data, the classification criteria are not met.

#### Product:

No aspiration toxicity classification



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

### **SECTION 12: Ecological information**

12.1	<b>Toxicity</b> No data available	
12.2	Persistence and degradability No data available	
12.3	Bioaccumulative potential	
	Components:	
	2-heptanone:	
	Partition coefficient: n- : octanol/water	log Pow: 2.26 (30 °C)
		рН: 7
		Method: Regulation (EC) No. 440/2008, Annex, A.8
		GLP: yes
	n-Butyl acetate:	
Partition coefficient: n- : octanol/water	Pow: 200 (25 °C)	
	log Pow: 2.3 (25 °C)	
		рН: 7

Method: OECD Test Guideline 117



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

GLP: yes

xylene:	
	log Pow: 3.12 - 3.20 (25 °C)
octanol/water	GLP: no
	Remarks: Information taken from reference works and the literature.

Benzenepropanoic acid, 3-(2H-benzotriazol-2-yl)-5-(1,1- dimethylethyl)-4-hydroxy-, C7-9branched and linear alkyl esters:

Partition coefficient: n- : log Pow: 9.2

octanol/water

Benzoic acid:

Partition coefficient: n- : log Pow: 1.88 octanol/water

### bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:

Partition coefficient: n- : Remarks: No data available



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

octanol/water

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:			
Partition coefficient: n- : octanol/water	Remarks: No data available		
12.4 Mobility in soil			
No data available			
12.5 Results of PBT and vPvB asse	ssment		
Product:			
Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.		
12.6 Other adverse effects			
Product:			
Endocrine disrupting : potential	This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).		



## C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods		
Product	:	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information			
14.1 UN number			
ADN	: UN 1263		
ADR	: UN 1263		



# C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
ΙΑΤΑ	:	PAINT
14.3 Transport hazard class(es)		
		Class
ADN	:	3
ADR	:	3

Subsidiary risks



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

RID	:	3
IMDG	:	3
ΙΑΤΑ	:	3
14.4 Packing group		
ADN		
Packing group	:	Ш
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
ADR		
Packing group	:	Ш
Classification Code	:	F1
Hazard Identification Number	:	30



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

	Packing instruction (LQ)	:	Y344
	Packing group	:	Ш
	Labels	:	Flammable Liquids
	IATA (Passenger)		
	Packing instruction (passenger aircraft)	:	355
	Packing instruction (LQ)	:	Y344
	Packing group	:	ш
	Labels	:	Flammable liquid
14.5	5 Environmental hazards		
	ADN		
	Environmentally hazardous	:	no
	ADR		
	Environmentally	:	no



### C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

### hazardous

### RID

Environmentally	:	no
hazardous		
IMDG		

Marine pollutant : no

#### 14.6 Special precautions for user

Remarks: ADR: Packages smaller than or equal to 450 liters, not<br/>goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law



# C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

UK REACH List of restrictions (Annex 17)

: Conditions of restriction for the following entries should be considered:

Number on list 3, 20

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to	:	Not applicable



### C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

authorisation (Annex XI	V)			
Control of Major Accide Regulations 2015 (COM		s P5c	FLAMMABLE	LIQUIDS
Volatile organic compounds	in co	dustrial emissic ontrol)		nber 2010 on ollution prevention and content: 38.35 %
	V	platile organic c	ompounds (VOC)	content: 389.63 g/l

VOC content excluding water

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999



## C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

(requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	d
Limit value for maximum VOC content as specified in Annex IIB:	420 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	418 g/l

#### **15.2 Chemical Safety Assessment**

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

### **SECTION 16: Other information**

Full text of H-Statements		
H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361f	:	Suspected of damaging fertility.



Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a
		fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours



### C-C-30 5L 5L Steel jerricans

Version	<b>Revision Date:</b>	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition



### C-C-30 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050794 559	Date of first issue: 25.04.2025

Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information Other information	: For multi-pack systems all components. Restricted to profession	observe material safety data sheets of al users.
Classification of the mixtur	e:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN