

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 68-RAL 9016 mat 10L M124 10L Steel drums 68-RAL
9016 mat 10L M124 10L Steel drums

Product code : 000000000050795922

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying
Substance/Mixture Monocoat product

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Specific target organ toxicity -
repeated exposure, Category 2

H373: May cause damage to organs through
prolonged or repeated exposure.

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Warning

Hazard Statements	:	H226	Flammable liquid and vapor.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H336	May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

H373 May cause damage to organs through
prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting
effects.

Supplemental Hazard : EUH066 Repeated exposure may cause skin dryness or
Statements cracking.

Precautionary : **Prevention:**
Statements

P210 Keep away from heat, hot surfaces, sparks,
open flames and other ignition sources. No
smoking.

P260 Do not breathe mist or vapors.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/
eye protection/ face protection/ hearing
protection.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off
immediately all contaminated clothing. Rinse
skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical
or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate

Benzoic acid

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

polyaminoamide salt

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : acrylic resin
saturated polyester resin
organic solvent
cellulose ester
pigment

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 20 - < 25
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6 918-668-5 UK-20- 0537843089-5- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335	>= 7 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

		(Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
2-heptanone	110-43-0 203-767-1 606-024-00-3 UK-20- 0537843089-5- 0000	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5
xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4;	>= 3 - < 5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

**68-RAL 9016 mat 10L M124 10L
Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous	>= 2 - < 2.5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	system)	
Benzoic acid	65-85-0 200-618-2 607-705-00-8 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 1; H372 (lung)	>= 1 - < 2

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	UK-20- 9642318150-0- 0000		
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7 255-437-1 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7 280-060-4 UK-20- 0537843089-5- 0000 UK-20-	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic	>= 0.3 - < 0.5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

**68-RAL 9016 mat 10L M124 10L
Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	9642318150-0-0000	Chronic 1; H410	
polyaminoamide salt	162627-17-0 01-2119970640-38	Skin Sens. 1; H317	>= 0.2 - < 0.3
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4 UK-20- 0537843089-5-0000 UK-20- 9642318150-0-0000	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT SE 3; H336 (Central nervous system)	>= 0.2 - < 0.3

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Substances with a workplace exposure limit :

Titanium dioxide	13463-67-7		>= 25 - < 50
	236-675-5		
	UK-20- 2749242067-7- 0000		
	UK-20- 9702550300-0- 0000		
	UK-20- 0537843089-5- 0000		
Silica gel, precipitated, crystalline free	UK-20- 9642318150-0- 0000		>= 3 - < 5
	112926-00-8		

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000		
--	---------------------------------	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
In all cases of doubt, or when symptoms persist, seek medical attention.
Move out of dangerous area.
Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.
If breathed in, move person into fresh air.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

If breathing is irregular or stopped, administer artificial respiration.

- In case of skin contact : If symptoms persist, call a physician.
- Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
- Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- Call a physician immediately.
- If easy to do, remove contact lens, if worn.
- If swallowed : If symptoms persist, call a physician.
- Do NOT induce vomiting.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Advice on product handling can be found in sections 7
and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined
areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the
environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains
inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection : Avoid all sources of ignition: heat, sparks, open flame.
against fire and explosion : Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

operators should wear antistatic clothing and footwear.
The relevant fire protection measures should be noted.
Use explosion-proof equipment. Vapors are heavier than
air and may spread along floors. Vapors may form
explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose
of safely. Wash hands before breaks and at the end of
workday. Keep away from food, drink and animal
feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Avoid direct sunlight. Close containers carefully once
opened and store them upright in order to prevent any
leakage. No smoking. No admission for unauthorised
personnel. Always keep in containers of same material
as the original one. Observe label precautions. Keep in a
dry, cool and well-ventilated place.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Packaging material : Suitable material: Polyethylenetherephtalate (PET), Polypropylene, Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm	2019/1831/ EU

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

			723 mg/m3	
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
Silica gel, precipitated, crystalline free	112926-00- 8	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m3 (Silica)	GB EH40
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

		TWA	50 ppm 237 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 238 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 475 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned			

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-	108-65-6	TWA	50 ppm	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

propylacetate			274 mg/m3	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake			

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L**Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

	through the skin, Indicative			
4-methylpentan-2-one	108-10-1	STEL	100 ppm 416 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 208 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 83 mg/m3	2000/39/EC
	Further information: Indicative			
		STEL	50 ppm	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

			208 mg/m3	
	Further information: Indicative			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
4-methylpentan-2-one	108-10-1	4-methylpentan-2-one: 20 micromol per litre (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Protective measures : personal respiratory protection and protective suit.

: Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: white
Odor	: ester-like
pH	: substance/mixture is non-polar/aprotic
Melting point/ range	: not determined

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Boiling point/boiling range : not determined

Flash point : 26 °C
Method: ISO 3679

Evaporation rate : not determined

Upper explosion limit / Upper
flammability limit : not determined

Lower explosion limit / Lower
flammability limit : > 35 g/m³

Vapor pressure : not determined (20 °C)
not determined (50 °C)

Relative vapor density : Heavier than air.

Density : 1.255 g/cm³ (20 °C)

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-
octanol/water : not applicable for mixtures

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, kinematic : 411.6 mm²/s (23 °C)
67.0 mm²/s (40 °C)

Flow time : > 60 s at 23 °C
Cross section: 6 mm
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)
octanol/water
log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n- : log Pow: 3.17
octanol/water
GLP: no

2-heptanone:

Partition coefficient: n- : log Pow: 2.26 (30 °C)
octanol/water
pH: 7

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Method: Regulation (EC) No. 440/2008, Annex, A.8

GLP: yes

xylene:

Partition coefficient: n-
octanol/water : log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and
the literature.

1-methoxy-2-propylacetate:

Partition coefficient: n-
octanol/water : log Pow: 1.2 (20 °C)

pH: 6.8

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Benzoic acid:

Partition coefficient: n- : log Pow: 1.88
octanol/water

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:

Partition coefficient: n- : Remarks: No data available
octanol/water

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n- : Remarks: No data available
octanol/water

polyaminoamide salt:

Partition coefficient: n- : log Pow: > 5.5 (20 °C)
octanol/water

Method: Regulation (EC) No. 440/2008, Annex, A.8

GLP: no

4-methylpentan-2-one:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Partition coefficient: n-
octanol/water : Pow: 79 (20 °C)
log Pow: 1.9 (20 °C)
pH: 6.7
Method: OECD Test Guideline 117
GLP: no

Titanium dioxide:

Partition coefficient: n-
octanol/water : Remarks: Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components
considered to be either persistent, bioaccumulative and
toxic (PBT), or very persistent and very bioaccumulative
(vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed of as the unused product.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

IMDG : PAINT

IATA : PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Hazard Identification
Number : 30

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification
Number : 30

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification
Number : 30

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366
aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355
(passenger aircraft)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable liquid

14.5 Environmental hazards

ADN

Environmentally : no
hazardous

ADR

Environmentally : no
hazardous

RID

Environmentally : no
hazardous

IMDG

Marine pollutant : no

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not
goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the following entries should be considered: Number on list 72, 3, 20
--	---

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Number on list 3

Number on list 20

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

P5c

Control of Major Accident Hazards
Regulations 2015 (COMAH)

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a)
gasolines and naphthas, (b)
kerosenes (including jet fuels),
(c) gas oils (including diesel
fuels, home heating oils and
gas oil blending streams),(d)
heavy fuel oils (e) alternative
fuels serving the same
purposes and with similar
properties as regards
flammability and
environmental hazards as the
products referred to in points
(a) to (d)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 39.86 %

Volatile organic compounds (VOC) content: 500.24 g/l

VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

d

Limit value for maximum VOC content as specified in Annex IIB:

420 g/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

VOC content of the ready-for-use product according to ISO 11890-2: 420 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer.
H361f	: Suspected of damaging fertility.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

exposure.

H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L

Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Flam. Liq. 3	H226
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

68-RAL 9016 mat 10L M124 10L **Steel drums**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050795 922	Date of first issue: 25.04.2025

GB / EN