

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name					
Product code	: 00000000050811972				
1.2 Relevant identified uses of the	substance or mixture and us	ses advised against			
Use of the	Use of the : Spraying				
Substance/Mixture	. , .				
Substance/wixture	Monocoat product				
1.3 Details of the supplier of the safety data sheet					
Company:		act address:			
BASF Coatings GmbH Postfach 6123	BASF 4th a	- pic nd 5th Floors, 2 Stockport Exchange			
48136 Münster		vay Road, Stockport, SK1 3GG			
Deutschland		d Kingdom			

Telephone: +44 161 475 3000



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H225 H317 H336 H412	Highly flammable liquid and vapor. May cause an allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
			3 / 57



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

smoking.

P233	Keep container tightly closed.
P261	Avoid breathing mist or vapors.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:	

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label: n-Butyl acetate

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

methyl methacrylate



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

2-hydroxyethyl methacrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : acrylic resin saturated polyester resin

. .

organic solvent

pigment

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	Index-No. Registration number		
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 15 - < 20
1-methoxy-2-propylacetate	108-65-6	Flam. Liq. 3; H226	>= 3 - < 5



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
	UK-20- 9702550300-0- 0000	system)	
	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		
Solvent naphtha (petroleum),	64742-95-6	Flam. Liq. 3; H226	>= 3 - < 5
light arom. (CAS EU: 128601-23-0)	918-668-5	STOT SE 3; H336	
	UK-20- 0537843089-5- 0000	(Central nervous system) STOT SE 3; H335	
		(Respiratory	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

		system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
2-heptanone	110-43-0 203-767-1 606-024-00-3 UK-20- 0537843089-5- 0000	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5
xylene	1330-20-7 215-535-7 601-022-00-9 UK-20-	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4;	>= 2.5 - < 3



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
2,4-pentanedione	123-54-6 204-634-0 606-029-00-0	Flam. Liq. 3; H226 Acute Tox. 4; H302	>= 1 - < 2



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000	Acute Tox. 3; H331 Acute Tox. 3; H311	
bis(1,2,2,6,6-pentamethyl-4-	41556-26-7	Skin Sens. 1A;	>= 0.5 - < 1
piperidyl)sebacate	255-437-1	H317	
	UK-20-	Repr. 2; H361f	
	0537843089-5-	Aquatic Acute 1;	
	0000	H400	
	UK-20-	Aquatic	
	9642318150-0- 0000	Chronic 1; H410	
Methyl 1,2,2,6,6-pentamethyl-4-	82919-37-7	Skin Sens. 1A;	>= 0.25 - < 0.3
piperidyl sebacate	280-060-4	H317	
	UK-20-	Repr. 2; H361f	
	0537843089-5-	Aquatic Acute 1;	
	0000	H400	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	UK-20- 9642318150-0- 0000	Aquatic Chronic 1; H410	
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT SE 3; H336 (Central nervous system)	>= 0.2 - < 0.3
methyl methacrylate	80-62-6 201-297-1	Flam. Liq. 2; H225 Skin Irrit. 2; H315	>= 0.1 - < 0.2



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	607-035-00-6 UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 0537843089-5- 0000	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	
	0000		
2-hydroxyethyl methacrylate	868-77-9	Eye Irrit. 2; H319	>= 0.1 - < 0.2
	212-782-2	Skin Sens. 1B;	
	607-124-00-X	H317	



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

UK-20-	
0537843089-5-	
0000	
UK-20-	
9642318150-0-	
0000	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	: First aid personnel should pay attention to their own
	safety.
	If the patient is likely to become unconscious, place and
	transport in stable sideways position (recovery position).
	Immediately remove contaminated clothing.
	In all cases of doubt, or when symptoms persist, seek
	medical attention.
	Move out of dangerous area.
	Never give anything by mouth to an unconscious person.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

If inhaled	:	If symptoms persist, call a physician.	
		If breathed in, move person into fresh air.	
		If breathing is irregular or stopped, administer artificial respiration.	
In case of skin contact	:	If symptoms persist, call a physician.	
		Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
		Do NOT use solvents or thinners.	
In case of eye contact	:	If symptoms persist, call a physician.	
		In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.	
If swallowed	:	If symptoms persist, call a physician.	
14 / 57			



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Do NOT induce vomiting.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Risks	: May cause an allergic skin reaction. May cause drowsiness or dizziness.
4.3 Indication of any immedia	ate medical attention and special treatment needed
Treatment	: No known specific antidote.

Treat symptomatically.



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media	
	Water spray jet
media	Dry powder
	Alcohol-resistant foam
	Carbon dioxide (CO2)
Unsuitable extinguishing : media	High volume water jet
5.2 Special hazards arising from the	e substance or mixture
Specific hazards during fire :	Fire will produce dense black smoke containing
fighting	hazardous combustion products (see section 10).
5.3 Advice for firefighters	
Special protective :	Appropriate breathing apparatus may be required.
	16 / 57



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

equipment for fire-fighters

Further information	:	In the event of fire, cool tanks with water spray.
		Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
Personal precautions	:	Avoid breathing vapours.	
		Keep away from sources of ignition.	
		Advice on product handling can be found in sections 7 and 8 of this safety data sheet.	
		For non-emergency personnel:	



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Ensure adequate ventilation.	
		Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling :	Provide good ventilation of working area (local exhaust ventilation if necessary).
	Do not return residues to the storage containers.
	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
	The workplace should be equipped with an emergency shower and eye-rinsing facility.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.
	Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	: Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Hygiene measures	:	Remove contaminated clothing immediately and dispose
		of safely. Wash hands before breaks and at the end of
		workday. Keep away from food, drink and animal
		feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on	:	Avoid direct sunlight. Close containers carefully once
storage conditions		opened and store them upright in order to prevent any
		leakage. No smoking. No admission for unauthorised
		personnel. Always keep in containers of same material
		as the original one. Observe label precautions. Keep in a
		dry, cool and well-ventilated place.

Advice on common storage :	Keep away from oxidizing agents, strongly alkaline and
	strongly acid materials in order to avoid exothermic
	reactions.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Packaging material	: Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)
7.3 Specific end use(s)	
Specific use(s)	: Please refer to the technical leaflet for further
	information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	Further infor	STEL	150 ppm 723 mg/m3	2019/1831/ EU		
		TWA	50 ppm 241 mg/m3	2019/1831/ EU		
	Further infor	Further information: Indicative				
1-methoxy-2- propylacetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40		
	Further information: Can be absorbed substances are those for which there a absorption will lead to systemic toxicity					
		STEL	100 ppm 548 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The a substances are those for which there are concerns that derma			-		



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	absorption v	absorption will lead to systemic toxicity.			
		STEL	100 ppm	2000/39/EC	
			550 mg/m3		
	Further infor	mation: Identifies	the possibility of significar	nt uptake	
	through the	skin, Indicative			
		TWA	50 ppm	2000/39/EC	
			275 mg/m3		
	Further information: Identifies the possibility of significant uptake			nt uptake	
	through the	through the skin, Indicative			
2-heptanone	110-43-0	STEL	100 ppm	GB EH40	
			475 mg/m3		
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal			The assigned	
	absorption v	vill lead to systemi	c toxicity.		
		TWA	50 ppm	GB EH40	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

			237 mg/m3		
	Further infor	mation: Can be ab	sorbed through the skin. T	he assigned	
	substances a	are those for which	there are concerns that d	ermal	
	absorption v	vill lead to systemic	c toxicity.		
		TWA	50 ppm	2000/39/EC	
			238 mg/m3		
	Further infor	mation: Identifies	the possibility of significar	nt uptake	
	through the	through the skin, Indicative			
		STEL 100 ppm 200		2000/39/EC	
			475 mg/m3		
	Further infor	Further information: Identifies the possibility of significant uptake			
	through the	through the skin, Indicative			
xylene	1330-20-7	TWA	50 ppm	GB EH40	
			220 mg/m3		
	Further infor	mation: Can be ab	sorbed through the skin. T	he assigned	
	substances a	are those for which	there are concerns that d	ermal	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

	absorption will lead to systemic toxicity.			
		STEL	100 ppm	GB EH40
			441 mg/m3	
	Further infor	mation: Can be ab	sorbed through the skin. T	he assigned
	substances a	re those for which	there are concerns that d	ermal
	absorption w	vill lead to systemic	c toxicity.	
		TWA	50 ppm	2000/39/EC
			221 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
		STEL	100 ppm	2000/39/EC
			442 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
4-methylpentan- 2-one	108-10-1	STEL	100 ppm	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

		416 mg/m3			
Further infor	Further information: Can be absorbed through the skin. The assigned				
substances a	re those for which	there are concerns that d	ermal		
absorption w	vill lead to systemic	c toxicity.			
	TWA	50 ppm	GB EH40		
		208 mg/m3			
Further infor	mation: Can be ab	sorbed through the skin. T	he assigned		
substances a	re those for which	there are concerns that d	ermal		
absorption w	absorption will lead to systemic toxicity.				
	TWA	20 ppm	2000/39/EC		
		83 mg/m3			
Further infor	Further information: Indicative				
	STEL	50 ppm	2000/39/EC		
		208 mg/m3			
Further infor	Further information: Indicative				



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

methyl	80-62-6	TWA	50 ppm	GB EH40	
methacrylate			208 mg/m3		
		STEL	100 ppm	GB EH40	
			416 mg/m3		
		TWA	50 ppm	2009/161/E	
				U	
	Further information: Indicative				
		STEL	100 ppm	2009/161/E	
				U	
	Further info	rmation: Indicativ	e		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per	After shift	GB EH40 BAT



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

		mole creatinine (Urine)		
4-methylpentan-2-one	108-10-1	4-methylpentan- 2-one: 20 micromol per litre (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove



68-RAL 1007 M135 20L 20L Steel drums

VersionRevision Date:SDS Number:Date of last issue: -1.025.04.202500000000050811Date of first issue: 25.04.2025972Date of first issue: 25.04.2025

certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

		time according to EN ISO 374-1)
Skin and body protection	:	chemical-resistant disposable coveralls
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily accessible.
		If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits,



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	yellow
Odor	:	ester-like
рН	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	22 °C
		Method: ISO 3679
Evaporation rate	:	not determined
·		
Lower explosion limit / Lower	:	> 35 g/m3



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

flammability limit

Vapor pressure	:	not determined (20 °C)
		not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.060 g/cm3 (20 °C)
Solubility(ies) Water solubility Partition coefficient: n- octanol/water Autoignition temperature Decomposition temperature	::	not determined not applicable for mixtures > 200 °C No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	269.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	> 40 s at 23 °C Cross section: 6 mm Method: ISO 2431



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
9.2 Other information Flammability (liquids)	:	Highly flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Conditions to avoid	: Avoid direct sunlight.	
	Heat, flames and sparks.	

10.5 Incompatible materials		
Materials to avoid : Keep away from oxidiz		Keep away from oxidizing agents, strongly alkaline and
		strongly acid materials in order to avoid exothermic
		reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Acute inhalation toxicity		Acute toxicity estimate: > 20 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
Components:		
2-heptanone:		
Acute oral toxicity	:	LD50 (Rat): 1,600 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 16.7 mg/l Exposure time: 4 h
		Test atmosphere: vapor



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Result

: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

STOT-single exposure May cause drowsiness or dizziness. **STOT-repeated exposure** Based on available data, the classification criteria are not met. Aspiration toxicity Based on available data, the classification criteria are not met. **Product:** No aspiration toxicity classification **SECTION 12: Ecological information** 12.1 Toxicity No data available 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential **Components:** n-Butyl acetate: Partition coefficient: n-: Pow: 200 (25 °C) octanol/water log Pow: 2.3 (25 °C) pH: 7



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Method:	OECD	Test	Guideline	117
meenou.	OLCD	1000	Galacinic	

GLP: yes

1-methoxy-2-propylacetate:

Partition coefficient: n- octanol/water	:	log Pow: 1.2 (20 °C)
		рН: 6.8
		Method: OECD Test Guideline 117
		GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-	:	log Pow: 3.17
octanol/water		GLP: no

2-heptanone:

Partition coefficient: n- : log Pow: 2.26 (30 °C)



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

octanol/water	pH: 7		
	Method: Regulation (EC) No. 440/2008, Annex, A.8		
	GLP: yes		
xylene:			
	log Pow: 3.12 - 3.20 (25 °C)		
octanol/water	GLP: no		
	Remarks: Information taken from reference works and the literature.		
2,4-pentanedione:			
Partition coefficient: n- :	log Pow: 0.4 (25 °C)		
octanol/water	Remarks: Information taken from reference works and the literature.		

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Partition coefficient: n- octanol/water	:	Remarks: No data available
Methyl 1,2,2,6,6-pentamethy	·I-4·	piperidyl sebacate:
Partition coefficient: n- octanol/water	:	Remarks: No data available
4-methylpentan-2-one:		
Partition coefficient: n-	:	Pow: 79 (20 °C)
octanol/water		log Pow: 1.9 (20 °C)
		рН: 6.7
		Method: OECD Test Guideline 117
		GLP: no
methyl methacrylate:		
Partition coefficient: n-	:	log Pow: 1.38 (20 °C)
octanol/water		GLP: No information available.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

2-hydroxyethyl methacrylate:	
Partition coefficient: n- :	log Pow: 0.42 (25 °C)
octanol/water	pH: 5.9 - 6.1
	Method: OECD Test Guideline 107
	GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

12.6 Other adverse effects

Product:		
Endocrine disrupting	:	This substance/mixture does not contain components
potential		considered to have endocrine disrupting properties for
		environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

ATA	:	PAINT	
ATA	:		

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	3	
ADR	:	3	
RID	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADN			
Packing group	:	П	
Classification Code	:	F1	
Hazard Identification	:	33	



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Ν	u	m	ber
1 1	u		DCI

Labels	: 3
Remarks	: Special Provision 640D
ADR	
Packing group	: 11
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Tunnel restriction code	: (D/E)
Remarks	: Special Provision 640D
RID	
Packing group	: 11
Classification Code	: F1



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Hazard Identification Number	:	33
Labels	:	3
Remarks	:	Special Provision 640D
IMDG		
Packing group	:	Ш
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	364
Packing instruction (LQ)	:	Y341
Packing group	:	Ш
Labels	:	Flammable Liquids



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

IATA (Passenger)

Packing instruction (passenger aircraft)	:	353
Packing instruction (LQ)	:	Y341
Packing group	:	II
Labels	:	Flammable liquid

14.5 Environmental hazards

ADN

Environmentally	:	no
hazardous		
ADR		

Environmentally	:	no
hazardous		
RID		

Environmentally : no



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

hazardous

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

: Conditions of restriction for the following entries should be considered:

Number on list 72, 3, 20



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Number on list 3

Number on list 20

UK REACH Candidate list of substances of very high	:	Not applicable
concern (SVHC) for Authorisation		
The Persistent Organic Pollutants Regulations	:	Not applicable
(retained Regulation (EU) 2019/1021 as amended		
for Great Britain)		



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Regulation (EC) on substances that deplete the ozone layer		: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)		: Not applicable
	P5c	
Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS
	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
	Volatile organic compounds (VOC) content: 34.51 %
	Volatile organic compounds (VOC) content: 365.80 g/l VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

(requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

I un text of II-Statements		
H225	:	Highly flammable liquid and vapor.
H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H351	:	Suspected of causing cancer.
H361f	:	Suspected of damaging fertility.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
2009/161/EU	:	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing
		a third list of indicative occupational exposure limit values in
		implementation of Council Directive 98/24/EC and amending
		Commission Directive 2000/39/EC
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a
		fifth list of indicative occupational exposure limit values



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information Other information	all compone	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.	
		•	
Classification of the mixture:		Classification procedure:	
Flam. Liq. 2	H225	Based on product data or assessment	
Skin Sens. 1	H317	Calculation method	
STOT SE 3	H336	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a



68-RAL 1007 M135 20L 20L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050811 972	Date of first issue: 25.04.2025

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN