

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	0000000000508176	Date of first issue: 25.04.2025
		56	

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : 68-RAL 1007 airl. 10/20L  
Product code : 000000000050817656

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Spraying  
stance/Mixture Monocoat product

#### 1.3 Details of the supplier of the safety data sheet

**Company:**

BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms	:	 
Signal Word	:	Warning
Hazard Statements	:	H226      Flammable liquid and vapor. H317      May cause an allergic skin reaction. H336      May cause drowsiness or dizziness. H412      Harmful to aquatic life with long lasting effects.
Precautionary Statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261      Avoid breathing mist or vapors. P273      Avoid release to the environment. P280      Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate  
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
methyl methacrylate  
2-hydroxyethyl methacrylate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
56      Date of first issue: 25.04.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : acrylic resin  
saturated polyester resin  
pigment  
organic solvent  
amines

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 15 - < 20
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6 918-668-5 UK-20-0537843089-5-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 3 - < 5
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5
xylene	1330-20-7 215-535-7 601-022-00-9 UK-20-2749242067-	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 2 - < 2.5

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

	7-0000 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
2,4-pentanedione	123-54-6 204-634-0 606-029-00-0 UK-20-0537843089-5-0000	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311	$\geq 1 - < 2$
2-heptanone	110-43-0 203-767-1 606-024-00-3 UK-20-0537843089-5-0000	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous system)	$\geq 1 - < 2$
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 UK-20-9642318150-0-0000	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.5 - < 1$
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	$\geq 0.5 - < 1$
methyl methacrylate	80-62-6 201-297-1 607-035-00-6 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	$\geq 0.1 - < 0.2$

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
56      Date of first issue: 25.04.2025

	UK-20-9642318150-0-0000		
2-hydroxyethyl methacrylate	868-77-9 212-782-2 607-124-00-X UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Eye Irrit. 2; H319 Skin Sens. 1B; H317	$\geq 0.1 - < 0.2$

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
Move out of dangerous area.  
In all cases of doubt, or when symptoms persist, seek medical attention.  
Immediately remove contaminated clothing.  
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).  
First aid personnel should pay attention to their own safety.
- If inhaled : If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Do NOT use solvents or thinners.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If symptoms persist, call a physician.
- If swallowed : Rinse mouth.  
Do NOT induce vomiting.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

---

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
No known specific antidote.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry powder  
Carbon dioxide (CO<sub>2</sub>)  
Water spray  
Foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	000000000508176	Date of first issue: 25.04.2025

56

For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airt. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

- practice.  
Do not breathe vapors or spray mist.
- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.
- The relevant fire protection measures should be noted. Use explosion-proof equipment.
- Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

### 7.3 Specific end use(s)

- Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
1-methoxy-2-propylacetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
xylene	1330-20-7	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 237 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub-			

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

		stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	50 ppm 238 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 475 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
4-methylpentan-2-one	108-10-1	STEL	100 ppm 416 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 208 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 83 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
		STEL	50 ppm 208 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
methyl methacrylate	80-62-6	TWA	50 ppm 208 mg/m <sup>3</sup>	GB EH40
		STEL	100 ppm 416 mg/m <sup>3</sup>	GB EH40
		TWA	50 ppm	2009/161/EU
	Further information: Indicative			
		STEL	100 ppm	2009/161/EU
	Further information: Indicative			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
4-methylpentan-2-one	108-10-1	4-methylpentan-2-one: 20 micromol per litre (Urine)	After shift	GB EH40 BAT

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

### Derived No Effect Level (DNEL)

Substance name	End Use	Routes of exposure	Potential health effects	Value
Ethyl 3-ethoxypropionate	Workers	Skin contact	Long-term systemic effects	102 mg/kg
	Workers	Inhalation	Long-term systemic effects	610 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term local effects	102 mg/cm <sup>2</sup>
	Workers	Inhalation	Long-term local effects	610 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	24.2 mg/kg
	Consumers	Inhalation	Long-term systemic effects	72.6 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	1.2 mg/kg

### Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
Ethyl 3-ethoxypropionate	Sewage treatment plant	50 mg/l
	Fresh water	0.061 mg/l
	Sea water	0.006 mg/l
	Fresh water sediment	0.419 mg/kg
	Sea sediment	0.042 mg/kg
	Soil	0.048 mg/kg

## 8.2 Exposure controls

### Engineering measures

Ensure adequate ventilation.

### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certi-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

fied according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm  
Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Request information on glove permeation properties from the glove supplier.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

### Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	0000000000508176	Date of first issue: 25.04.2025
		56	

---

Color	:	yellow
Odor	:	ester-like
Odor Threshold	:	not determined
pH	:	substance/mixture is non-polar/aprotic
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	125 - 135 °C Method: calculated
Flash point	:	23 °C Method: ISO 3679
Evaporation rate	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m <sup>3</sup>
Vapor pressure	:	10 hPa (20 °C) Method: calculated  51 hPa (50 °C) Method: calculated
Density	:	1.070 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	269.0 mm <sup>2</sup> /s (23 °C)  not determined (40 °C)
Flow time	:	> 40 s at 23 °C Cross section: 6 mm Method: ISO 2431

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	000000000508176	Date of first issue: 25.04.2025
		56	

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Avoid direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

---

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

### Components:

#### **2-heptanone:**

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

### Components:

#### **n-Butyl acetate:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **4-methylpentan-2-one:**

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

### Product:

No aspiration toxicity classification

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)  
log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

##### **Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):**

Partition coefficient: n-octanol/water : log Pow: 3.17  
GLP: no

##### **1-methoxy-2-propylacetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)  
pH: 6.8  
Method: OECD Test Guideline 117  
GLP: yes

##### **xylene:**

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

octanol/water	GLP: no Remarks: Information taken from reference works and the literature.
<b>2,4-pentanedione:</b>	
Partition coefficient: n-octanol/water	: log Pow: 0.4 (25 °C) Remarks: Information taken from reference works and the literature.
<b>2-heptanone:</b>	
Partition coefficient: n-octanol/water	: log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8 GLP: yes
<b>Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:</b>	
Partition coefficient: n-octanol/water	: log Pow: 2.3 - 2.8 (25 °C) pH: 7 Method: OECD Test Guideline 107
<b>4-methylpentan-2-one:</b>	
Partition coefficient: n-octanol/water	: Pow: 79 (20 °C) log Pow: 1.9 (20 °C) pH: 6.7 Method: OECD Test Guideline 117 GLP: no
<b>methyl methacrylate:</b>	
Partition coefficient: n-octanol/water	: log Pow: 1.38 (20 °C) GLP: No information available.
<b>2-hydroxyethyl methacrylate:</b>	
Partition coefficient: n-octanol/water	: log Pow: 0.42 (25 °C) pH: 5.9 - 6.1 Method: OECD Test Guideline 107 GLP: yes

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADN : PAINT  
ADR : PAINT  
RID : PAINT  
IMDG : PAINT

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

**IATA** : PAINT

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

Labels : Flammable liquid

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3  
IMDG: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:  
Number on list 72, 3, 20

Number on list 3

Number on list 20

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	000000000508176 56	Date of first issue: 25.04.2025

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable  
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable  
Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable  
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

P5c

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

34

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 33.62 %

Volatile organic compounds (VOC) content: 359.73 g/l  
VOC content excluding water

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

d

Limit value for maximum VOC content as specified in Annex IIB:

420 g/l

VOC content of the ready-for-use product according to ISO 11890-2:

419 g/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapor.  
H226 : Flammable liquid and vapor.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H331 : Toxic if inhaled.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H351 : Suspected of causing cancer.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version 2.0      Revision Date: 22.12.2025      SDS Number: 000000000508176      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
56

2019/1831/EU : implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC  
GB EH40 : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
GB EH40 BAT : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : UK. Biological monitoring guidance values  
2000/39/EC / STEL : Limit Value - eight hours  
2009/161/EU / TWA : Short term exposure limit  
2009/161/EU / STEL : Limit Value - eight hours  
2019/1831/EU / TWA : Short term exposure limit  
2019/1831/EU / STEL : Limit Value - eight hours  
GB EH40 / TWA : Short term exposure limit  
GB EH40 / STEL : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 68-RAL 1007 airl. 10/20L

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.0	22.12.2025	000000000508176	Date of first issue: 25.04.2025
		56	

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN