

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050818 202	Date of first issue: 25.04.2025

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : P-R-120 5L F 5L Steel jerricans

Product code : 00000000050818202

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture : Thinner

### 1.3 Details of the supplier of the safety data sheet

**Company:**

BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

---

Telephone: +44 161 475 3000  
E-mail address: product-safety-uk-and-ireland@basf.com

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single	H336: May cause drowsiness or dizziness.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

exposure, Category 3, Central nervous system

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

Hazard Statements	:	H226	Flammable liquid and vapor.
		H304	May be fatal if swallowed and enters airways.
		H315	Causes skin irritation.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

#### Precautionary Statements

- Prevention:**
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P261 Avoid breathing mist or vapors.
  - P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
- Response:**
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical  
or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate

o-xylene

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)

Hydrocarbons, by-products with terpene processing

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

---

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : organic solvent

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20-	Flam. Liq. 3; H226  STOT SE 3; H336  (Central nervous system)	>= 50 - < 75

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

	9642318150-0-0000		
o-xylene	95-47-6 202-422-2 601-022-00-9 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 15 - < 20
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6 918-668-5	Flam. Liq. 3; H226 STOT SE 3; H336	>= 12.5 - < 15

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

	UK-20-0537843089-5-0000	(Central nervous system) STOT SE 3; H335  (Respiratory system) Asp. Tox. 1; H304  Aquatic Chronic 2; H411	
aliphatic hydrocarbons	64741-69-1 265-071-4 649-348-00-0 01-2119480158-34	Flam. Liq. 3; H226 STOT SE 3; H336  (Central nervous system) Asp. Tox. 1; H304  Aquatic Chronic 2; H411	>= 7 - < 10
1-methoxy-2-propylacetate	108-65-6 203-603-9	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 7

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

	607-195-00-7 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	(Central nervous system)	
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0-	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 3 - < 5

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050818 202      Date of last issue: -  
Date of first issue: 25.04.2025

	0000		
Hydrocarbons, by-products with terpene processing	68956-56-9	Flam. Liq. 3; H226	>= 2 - < 2.5
	273-309-3	Skin Irrit. 2; H315	
	01-2119980606-28	Eye Irrit. 2; H319	
		Skin Sens. 1; H317	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2; H411	

For explanation of abbreviations see section 16.

#### SECTION 4: First aid measures

##### 4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.  
Immediately remove contaminated clothing.  
In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.  
Never give anything by mouth to an unconscious person.  
Keep patient warm and at rest.

- If inhaled : If breathed in, move person into fresh air.  
Call a physician or poison control center immediately.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : If symptoms persist, call a physician.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control  
Center immediately.

Rinse mouth with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms  
and effects may be included in the GHS labeling phrases  
available in Section 2 and in the Toxicological  
assessments available in Section 11.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050818 202	Date of first issue: 25.04.2025

---

Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.  
Treat symptomatically.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

---

#### SECTION 5: Firefighting measures

##### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet  
Dry powder  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

##### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

##### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

#### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

#### 6.4 Reference to other sections

For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5 - 35 °C

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## P-R-120 5L F 5L Steel jerricans

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050818202      Date of last issue: -  
Date of first issue: 25.04.2025

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm	2019/1831/

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

			723 mg/m <sup>3</sup>	EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/ EU
Further information: Indicative				
o-xylene	95-47-6	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	50 ppm	2000/39/EC

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

			221 mg/m <sup>3</sup>	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-propylacetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**P-R-120 5L F 5L Steel jerricans**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 332 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal			

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050818  
202      Date of last issue: -      Date of first issue: 25.04.2025

	absorption will lead to systemic toxicity.			
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 133 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

#### 8.2 Exposure controls

##### Engineering measures

Ensure adequate ventilation.

##### Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

index 1, corresponding > 10 minutes of permeation  
time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant  
clothing made of natural fibres and/or heat-resistant  
synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the  
exposure limit they must use appropriate certified  
respirators.

In case of mist, spray or aerosol exposure wear suitable  
personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily  
accessible.

If these are not sufficient to maintain concentrations at  
the workplace below the occupational exposure limits,

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	hydrocarbon-like
Odor Threshold	:	not determined
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	126 - 190 °C
Flash point	:	27 °C Method: ISO 3679
Evaporation rate	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Lower explosion limit / Lower  
flammability limit : > 35 g/m<sup>3</sup>

Vapor pressure : 5.0000 hPa (20 °C)  
not determined (50 °C)

Relative vapor density : Heavier than air.

Density : 0.867 g/cm<sup>3</sup> (20 °C)

#### Solubility(ies)

Water solubility : not determined  
Partition coefficient: n-  
octanol/water : not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as  
prescribed/indicated.

#### Viscosity

Viscosity, kinematic : 6.0 mm<sup>2</sup>/s (23 °C)  
not determined (40 °C)

Flow time : < 30 s at 23 °C  
Cross section: 3 mm

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

#### 9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.  
Protect from frost.  
Heat, flames and sparks.  
Heat.

#### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

---

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

#### **Components:**

##### **2-butoxyethyl acetate:**

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Components:**

##### **n-Butyl acetate:**

Result : Repeated exposure may cause skin dryness or cracking.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

##### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

##### **Carcinogenicity**

Based on available data, the classification criteria are not met.

##### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

#### STOT-single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration toxicity

May be fatal if swallowed and enters airways.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)  
octanol/water log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

#### **o-xylene:**

Partition coefficient: n- : log Pow: 3.12 (20 °C)  
octanol/water  
pH: 7

GLP: no

Remarks: Information taken from reference works and  
the literature.

#### **Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):**

Partition coefficient: n- : log Pow: 3.17  
octanol/water  
GLP: no

#### **1-methoxy-2-propylacetate:**

Partition coefficient: n- : log Pow: 1.2 (20 °C)  
octanol/water  
pH: 6.8

Method: OECD Test Guideline 117

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

GLP: yes

#### 2-butoxyethyl acetate:

Partition coefficient: n-  
octanol/water : log Pow: 1.51 (25 °C)  
pH: 7

Method: OECD Test Guideline 107

GLP: no

#### Hydrocarbons, by-products with terpene processing:

Partition coefficient: n-  
octanol/water : Pow: 31,770 (25 °C)  
log Pow: 4.5 (25 °C)

Method: OECD Test Guideline 107

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

Product:

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater.  
Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed  
of as the unused product.

#### SECTION 14: Transport information

##### 14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

##### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

**ADR** : PAINT RELATED MATERIAL

**RID** : PAINT RELATED MATERIAL

**IMDG** : PAINT RELATED MATERIAL

**IATA** : PAINT RELATED MATERIAL

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

#### 14.4 Packing group

**ADN**

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Packing group : III  
Classification Code : F1  
Hazard Identification : 30  
Number  
Labels : 3

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification : 30  
Number  
Labels : 3  
Tunnel restriction code : (D/E)

#### RID

Packing group : III  
Classification Code : F1

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Hazard Identification : 30  
Number

Labels : 3

#### IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo : 366  
aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction : 355

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

(passenger aircraft)

Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable liquid

#### 14.5 Environmental hazards

##### ADN

Environmentally hazardous : no

##### ADR

Environmentally hazardous : no

##### RID

Environmentally hazardous : no

##### IMDG

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Marine pollutant : no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:

Number on list 3

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

properties as regards  
flammability and  
environmental hazards as the  
products referred to in points  
(a) to (d)

Volatile organic compounds : Volatile organic compounds (VOC) content: 870 g/l

Directive 2010/75/EU of 24 November 2010 on  
industrial emissions (integrated pollution prevention and  
control)

Volatile organic compounds (VOC) content: 99.98 %

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999  
(requirements relating to new and expectant mothers at work contained in Regulation  
16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

(requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped

#### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

### SECTION 16: Other information

#### Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first  
list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a  
fifth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315

#### Classification procedure:

Based on product data or assessment
Calculation method

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### P-R-120 5L F 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050818 202	Date of first issue: 25.04.2025

---

Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN