According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : P-H-930 WB primer HDR 2,5L Steel jerricans

Product code : 00000000050836186

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture

hardener

1.3 Details of the supplier of the safety data sheet

Company: Contact address:

BASF Coatings GmbH BASF plc
Postfach 6123 4th and 5t

Postfach 6123 4th and 5th Floors, 2 Stockport Exchange 48136 Münster Railway Road, Stockport, SK1 3GG

Deutschland United Kingdom

Telephone: +44 161 475 3000

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

E-mail address: product-safety-uk-and-ireland@basf.com

#### 1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single H335: May cause respiratory irritation. exposure, Category 3, Respiratory

system

#### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Hazard pictograms

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary

Statements

Prevention:

P261 Avoid breathing mist or vapors.

P280 Wear protective gloves.

Response:

P304 + P340 + P312 IF INHALED: Remove person to

fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel

unwell.

P333 + P313 If skin irritation or rash occurs: Get

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous ingredients which must be listed on the label:

HDI-Oligomer(Trimer)

IPDI polymere

4-toluenesulphonyl isocyanate

# **Additional Labeling**

EUH204 Contains isocyanates. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : polyisocyanate

organic solvent

### Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
HDI-Oligomer(Trimer)	28182-81-2	Acute Tox. 4;	>= 25 - < 50
		H332	
		Skin Sens. 1;	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

	01-2119485796-17	H317	
		STOT SE 3; H335	
		(Respiratory system)	
IPDI polymere	191427-71-1	Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 3 - < 5
4-toluenesulphonyl isocyanate	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 STOT SE 3; H335 (Respiratory system)	>= 0.2 - < 0.3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

specific concentration limit

Eye Irrit. 2; H319

>= 5 %

STOT SE 3; H335

>= 5 %

Skin Irrit. 2; H315

>= 5 %

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own

safety.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek

medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.

If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Call a physician immediately.

In case of contact, immediately flush skin with plenty of

water for at least 15 minutes while removing

contaminated clothing and shoes.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

In case of eye contact : Immediately wash affected eyes for at least 15 minutes

under running water with eyelids held open, consult an

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control

Center immediately.

Rinse mouth with water.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms

and effects may be included in the GHS labeling phrases

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

available in Section 2 and in the Toxicological

assessments available in Section 11.

Risks : May cause an allergic skin reaction.

May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing : Water spray jet

media

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Date of last issue: -Version **Revision Date:** SDS Number:

1.0 25.04.2025 00000000050836

Date of first issue: 25.04.2025 186

Unsuitable extinguishing : High volume water jet

media

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing

fighting hazardous combustion products (see section 10).

Hazardous combustion : Nitrogen oxides (NOx)

products

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.

equipment for fire-fighters

Further information : In the event of fire, cool tanks with water spray.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7

and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

areas.

### 6.2 Environmental precautions

Environmental precautions: Do not allow uncontrolled discharge of product into the

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible

absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately

with a suitable decontaminant. One possible

(flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts);

concentrated ammonia solution (5 parts). A non-

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

### 6.4 Reference to other sections

For disposal considerations see section 13.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in

application area. For personal protection see section 8.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Open drum carefully as content may be under pressure.

Do not breathe vapors or spray mist.

Protect from moisture.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Advice on protection against fire and explosion

: Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures

: Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions

: Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

release. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

Advice on common storage:

Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Packaging material : Suitable material: tinned carbon steel (Tinplate), Carbon

steel (Iron), Stainless steel 1.4301 (V2), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-

lacquer RDL 50, glass, Aluminum

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further

information.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
HDI-	28182-81-2	TWA	0.02 mg/m3	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

**Biological occupational exposure limits** 

CAS-No.

Substance name

186 Date of first issue: 25.04.2025

Oligomer(Trimer)			(NCO)	
	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m3	GB EH40
			(NCO)	
	Further information: Capable of causing occupational asthma.			
4-	4083-64-1	TWA	0.02 mg/m3	GB EH40
toluenesulphonyl isocyanate			(NCO)	
	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m3	GB EH40
			(NCO)	
	Further information: Capable of causing occupational asthma.			

Control

parameters

Sampling time

Basis

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

HDI-Oligomer(Trimer)	28182-81-2	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creatinine	At the end of the period of exposure	GB EH40 BAT
	1002 64 4	(Urine)	AI	CD FILIA
4-toluenesulphonyl	4083-64-1	isocyanate-	At the end of the	GB EH40
isocyanate		derived diamine	period of	BAT
		(Isocyanates): 1	exposure	
		μmol/mol		
		creatinine		
		(Urine)		

# 8.2 Exposure controls

# **Engineering measures**

Ensure adequate ventilation.

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Required when there is a risk of eye contact.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

# Hand protection

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation

time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant

synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

full face mask with AB2P3 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : If these are not sufficient to maintain concentrations at

the workplace below the occupational exposure limits,

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

appropriate certified respirators must be worn.

Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

Persons with a history of allergies, asthma, recurrent or chronic respiratory disease must not be employed in any process in which this product is used. Persons using this product should undergo lung function tests at regular intervals.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application.

Respiratory protective equipment should be worn by spray booth operatives.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Date of last issue: -Version **Revision Date:** SDS Number:

1.0 25.04.2025 00000000050836

Date of first issue: 25.04.2025 186

safety practice.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance liquid Color colorless Odor ether-like Odor Threshold : not determined

рΗ : 5.0 - 6.0

Melting point/ range : not determined

Boiling point/boiling range : not determined

Flash point : 65 °C

Method: ISO 3679

Evaporation rate : not determined

Upper explosion limit / Upper : not determined

flammability limit

Lower explosion limit / Lower : > 35 g/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Date of last issue: -Version **Revision Date:** SDS Number:

1.0 25.04.2025 00000000050836

Date of first issue: 25.04.2025 186

flammability limit

Vapor pressure not determined (20 °C)

not determined (50 °C)

Relative vapor density : Heavier than air.

: 1.050 g/cm3 (20 °C) Density

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as

prescribed/indicated.

not applicable for mixtures

Viscosity

Viscosity, kinematic : 6 mm2/s (23 °C)

not determined (40 °C)

< 30 s at 23 °C Flow time

> Cross section: 3 mm Method: ISO 2431

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Combustible liquid.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or

granular form.

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct contact with water.

Avoid direct sunlight.

Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and

strongly acidic materials, amines, alcohols and water.
Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in

evolution of carbon dioxide. In closed containers,

pressure build up could result in distortion, blowing and

in extreme cases bursting of the container.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

### 10.6 Hazardous decomposition products

Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Isocyanates

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.

# **Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

## Respiratory or skin sensitization

### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration toxicity**

Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

### 12.3 Bioaccumulative potential

### **Components:**

**HDI-Oligomer(Trimer):** 

Partition coefficient: n- : log Pow: 9.81 (25 °C)

octanol/water

4-toluenesulphonyl isocyanate:

Partition coefficient: n- : log Pow: 0.6 (30 °C)

octanol/water

Method: OECD Test Guideline 117

GLP: no

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

### 12.6 Other adverse effects

### Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of isocyanate waste in dry containers and never

mix together with other wastes (reaction, dangerous

pressure build up).

Do not discharge into drains/surface

waters/groundwater.

Observe national and local legal requirements.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Contaminated packaging : Containers which are not properly emptied must be

disposed pursuant to Directive 2008/98/EC

Residues in empty containers should be neutralised with

decontaminant (see section 6).

Packaging that is not properly emptied must be disposed

of as the unused product.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

**ADN** : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

# **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered:

Number on list 3

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations : Not applicable

(retained Regulation (EU) 2019/1021 as amended

for Great Britain)

Regulation (EC) on substances that deplete the : Not applicable

ozone layer

UK REACH List of substances subject to : Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

authorisation (Annex XIV)

Control of Major Accident Hazards Not applicable

Regulations 2015 (COMAH)

Volatile organic compounds

: Directive 2010/75/EU of 24 November 2010 on

industrial emissions (integrated pollution prevention and

control)

Volatile organic compounds (VOC) content: 46.95 %

Volatile organic compounds (VOC) content: 492.97 g/l

VOC content excluding water

# Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### **15.2 Chemical Safety Assessment**

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

### **SECTION 16: Other information**

### **Full text of H-Statements**

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 : May cause respiratory irritation.

### Full text of other abbreviations

Acute Tox. : Acute toxicity
Eye Irrit. : Eye irritation

Resp. Sens. : Respiratory sensitization

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits GB EH40 BAT : UK. Biological monitoring guidance values

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# P-H-930 WB primer HDR 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: -

1.0 25.04.2025 00000000050836

186 Date of first issue: 25.04.2025

Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Other information : For multi-pack systems observe material safety data sheets of

all components.

Restricted to professional users.

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method STOT SE 3 H335 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN