

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : A-U-88 1L 1L Steel drums

Product code : 000000000050857923

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying  
Substance/Mixture : Coatings and related products

### 1.3 Details of the supplier of the safety data sheet

**Company:**  
BASF Coatings GmbH  
Postfach 6123  
48136 Münster  
Deutschland

**Contact address:**  
BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

---

Telephone: +44 161 475 3000  
E-mail address: product-safety-uk-and-ireland@basf.com

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard,	H411: Toxic to aquatic life with long lasting

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

Category 2

effects.

### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

Hazard Statements	:	H225	Highly flammable liquid and vapor.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H336	May cause drowsiness or dizziness.
		H411	Toxic to aquatic life with long lasting effects.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Precautionary  
Statements

:

#### Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P391 Collect spillage.

Hazardous ingredients which must be listed on the label:  
acetone

tripropylene glycol diacrylate

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reactionproducts with 1-

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

chloro-2,3-epoxypropane, esters with acrylic acid

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-

Neopentyl glycol, propoxylated, esters with acrylic acid

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p

2-hydroxyethyl acrylate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : unsaturated acrylic resin  
fillers  
pigment

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

organic solvent

inorganic compounds

organic compounds

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
polymeric urethane acrylate	123904-10-9	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 15 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 UK-20-	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous	>= 15 - < 20

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

	9702550300-0-0000 UK-20-0537843089-5-0000	system)	
Methylethylketone	78-93-3 201-159-0 606-002-00-3 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 7 - < 10
tripropylene glycol diacrylate	42978-66-5	Eye Irrit. 2; H319	>= 7 - < 10

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

	256-032-2 607-249-00-X UK-20- 0537843089-5- 0000	Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411  specific concentration limit STOT SE 3; H335 >= 10 %	
(OLIGOMER) 4,4'- Isopropylidenediphenol, oligomeric reactionproducts with 1-chloro-2,3-epoxypropane,	55818-57-0 500-130-2	Skin Sens. 1; H317 Aquatic	>= 5 - < 7

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

esters with acrylic acid		Chronic 2; H411	
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-	162881-26-7 423-340-5 015-189-00-5 UK-20-0537843089-5-0000	Skin Sens. 1A; H317  Aquatic Chronic 4; H413	>= 3 - < 5
Neopentyl glycol, propoxylated, esters with acrylic acid	84170-74-1  01-2119970213-43	Skin Sens. 1; H317  Aquatic Chronic 2; H411	>= 3 - < 5
zinc phosphate	7779-90-0 231-944-3 030-011-00-6 UK-20-9702550300-0-0000	Aquatic Acute 1; H400  Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity):	>= 3 - < 5

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

	UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	1 M-Factor (Chronic aquatic toxicity): 1	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction	1187441-10-6	Eye Dam. 1; H318 Skin Sens. 1; H317	>= 1 - < 2
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p	28961-43-5 500-066-5 01-2119489900-30	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 2
2-hydroxyethyl acrylate	818-61-1 212-454-9 607-072-00-8 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314	>= 0.025 - < 0.1

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

	UK-20-0537843089-5-0000	Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	
<p>specific concentration limit</p> <p>Skin Sens. 1; H317</p> <p>&gt;= 0.2 %</p>			
Substances with a workplace exposure limit :			
talc	14807-96-6		>= 10 - < 12.5

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 00000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

	238-877-9 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000		
Kaolin	1332-58-7 310-194-1		$\geq 5 - < 7$
Silicon dioxide	7631-86-9 231-545-4 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000		$\geq 2.5 - < 3$

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

- If inhaled : If symptoms persist, call a physician.  
If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : In case of skin contact avoid direct exposure to sunlight or other UV radiation since this would increase sensitisation of the skin.  
If symptoms persist, call a physician.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.  
Call a physician immediately.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

If easy to do, remove contact lens, if worn.

In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.

If swallowed : If symptoms persist, call a physician.

Do NOT induce vomiting.

Rinse mouth.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : Causes skin irritation.

May cause an allergic skin reaction.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	00000000050857 923	Date of first issue: 25.04.2025

---

Causes serious eye irritation.

May cause drowsiness or dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.  
Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet  
Dry powder  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Hazardous combustion products : Oxides of phosphorus

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately.  
This must not be discharged into drains.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

---

#### SECTION 6: Accidental release measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

##### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

application area. For personal protection see section 8.  
Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.  
Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Advice on common storage : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5.00 °C

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate), Polypropylene, Polyethylenetherephtalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857  
923      Date of last issue: -      Date of first issue: 25.04.2025

#### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	GB EH40
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40
		TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

talca	14807-96-6	TWA (Respirable dust)	1 mg/m <sup>3</sup>	GB EH40
Methylethylketone	78-93-3	TWA	200 ppm 600 mg/m <sup>3</sup>	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	300 ppm 899 mg/m <sup>3</sup>	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	300 ppm 900 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				
		TWA	200 ppm	2000/39/EC

**SAFETY DATA SHEET**

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

**A-U-88 1L 1L Steel drums**

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857  
923      Date of last issue: -      Date of first issue: 25.04.2025

			600 mg/m3	
Further information: Indicative				
Kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m3	GB EH40
		TWA (Respirable dust)	0.1 mg/m3	2004/37/EC
Further information: Carcinogens or mutagens				
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m3 (Silica)	GB EH40

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## A-U-88 1L 1L Steel drums

Version 1.0      Revision Date: 25.04.2025      SDS Number: 000000000050857923      Date of last issue: -  
Date of first issue: 25.04.2025

---

Methylethylketone	78-93-3	butan-2-one: 70 micromol per litre  (Urine)	After shift	GB EH40 BAT
-------------------	---------	---	-------------	----------------

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Wear chemical-resistant disposable coverall and boots.

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Respiratory protection : Suitable respiratory equipment:  
half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	gray
Odor	:	ketone-like
Odor Threshold	:	not determined
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	not determined
Flash point	:	56.00 °C -12 °C Method: ISO 3679
Evaporation rate	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m <sup>3</sup>
Vapor pressure	:	203.0000 hPa (20 °C) 682.0000 hPa (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.220 g/cm <sup>3</sup> (20 °C)

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### Solubility(ies)

Water solubility : not determined  
Partition coefficient: n-  
octanol/water : not applicable for mixtures  
Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as  
prescribed/indicated.

#### Viscosity

Viscosity, kinematic : not determined (40 °C)  
36.0 mm<sup>2</sup>/s (23 °C)

Flow time : > 30 s  
Cross section: 4 mm

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

#### 9.2 Other information

Flammability (liquids) : Highly flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Particle size : The substance / product is marketed or used in a non solid or granular form.

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.  
Protect from frost.  
Ultraviolet rays  
Heat, flames and sparks.  
Heat.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### 10.5 Incompatible materials

Materials to avoid : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### Skin corrosion/irritation

Causes skin irritation.

##### Components:

acetone:

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Methylethylketone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

##### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

##### **Carcinogenicity**

Based on available data, the classification criteria are not met.

##### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

May cause drowsiness or dizziness.

##### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

#### Aspiration toxicity

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### zinc phosphate:

M-Factor (Acute aquatic : 1  
toxicity)

M-Factor (Chronic aquatic : 1  
toxicity)

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### acetone:

Partition coefficient: n- : log Pow: -0.24 (25 °C)  
octanol/water

##### Methylethylketone:

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

Partition coefficient: n-  
octanol/water : log Pow: 0.29

GLP: No information available.

Remarks: Information taken from reference works and  
the literature.

#### tripropylene glycol diacrylate:

Partition coefficient: n-  
octanol/water : log Pow: 2.0 (25 °C)

GLP: no

log Pow: 2 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.77 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

log Pow: 2.1 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.5 - 2.7 (23 °C)

pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

#### **(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid:**

Partition coefficient: n- : log Pow: ca. 1.6 - 3.8 (23 °C)  
octanol/water

Method: OECD Test Guideline 117

GLP: yes

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

log Pow: 1.6 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

log Pow: 1.6 - 3 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

log Pow: 3 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### **Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-:**

Partition coefficient: n-  
octanol/water : log Pow: 5.8 (22 °C)

pH: 8.3

Method: OECD Test Guideline 117

GLP: yes

#### **2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction:**

Partition coefficient: n-  
octanol/water : Pow: 2 - 5,200 (23.3 °C)

log Pow: 0.3 - 3.7 (23.3 °C)

Method: OECD Test Guideline 117

GLP: yes

#### **Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2- p:**

Partition coefficient: n-  
octanol/water : log Pow: 2.89 (23 °C)

pH: 8.1

Method: OECD Test Guideline 107

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

GLP: no

#### **2-hydroxyethyl acrylate:**

Partition coefficient: n-  
octanol/water : log Pow: -0.17 (25 °C)  
Method: OECD Test Guideline 107  
GLP: no

#### **talc:**

Partition coefficient: n-  
octanol/water : log Pow: -9.4 (25 °C)  
pH: 7  
GLP: no

#### **Silicon dioxide:**

Partition coefficient: n-  
octanol/water : Remarks: Not applicable

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed of as the unused product.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### 14.2 UN proper shipping name

**ADN** : PAINT

**ADR** : PAINT

**RID** : PAINT

**IMDG** : PAINT

(ZINC PHOSPHATE, TRIPROPYLENEGLYCOL DIACRYLATE)

**IATA** : PAINT

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

**IATA** : 3

#### 14.4 Packing group

##### ADN

Packing group : II  
Classification Code : F1  
Hazard Identification : 33  
Number  
Labels : 3  
Remarks : Special Provision 640D

##### ADR

Packing group : II  
Classification Code : F1  
Hazard Identification : 33  
Number  
Labels : 3

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Tunnel restriction code : (D/E)  
Remarks : Special Provision 640D

#### RID

Packing group : II  
Classification Code : F1  
Hazard Identification : 33  
Number  
Labels : 3  
Remarks : Special Provision 640D

#### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo) : 364

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

aircraft)

Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction : 353  
(passenger aircraft)  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable liquid

#### 14.5 Environmental hazards

##### ADN

Environmentally : yes  
hazardous

##### ADR

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Environmentally : yes  
hazardous

#### RID

Environmentally : yes  
hazardous

#### IMDG

Marine pollutant : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:

Number on list 72, 3

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 27.39 %

Volatile organic compounds (VOC) content: 334.15 g/l

VOC content excluding water

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

c

Limit value for maximum VOC content as specified in Annex IIB:

540 g/l

VOC content of the ready-for-use product according to ISO 11890-2:

539 g/l

#### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

---

### SECTION 16: Other information

#### Full text of H-Statements

H225	:	Highly flammable liquid and vapor.
H302	:	Harmful if swallowed.

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

at work

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and

## SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

#### Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment  
Calculation method  
Calculation method  
Calculation method  
Calculation method  
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

## SAFETY DATA SHEET

According to REACH Regulation (EC) No  
1907/2006, as amended by UK REACH  
Regulations SI 2019/758



We create chemistry

### A-U-88 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 923	Date of first issue: 25.04.2025

---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN