

Safety data sheet

Page: 1/12

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

1. Identification

Product identifier

1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Coatings and related products

Details of the supplier of the safety data sheet

Company:
BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland

Telephone: +49/2501/143688

E-mail address: product-safety-coatings@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

According to UN GHS criteria

Skin Corr./Irrit. 3 Aquatic Acute 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System, UN (GHS)

Signal Word: Warning

Hazard Statement:

H316 Causes mild skin irritation. H402 Harmful to aquatic life.

Precautionary Statements (Prevention):

P273 Avoid release to the environment.

Precautionary Statements (Response):

P332 + P313 If skin irritation occurs: Get medical attention.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

fillers, Synthetic rubber derivative, Water, organic solvent, pigment

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Hazardous ingredients (GHS) According to UN GHS criteria

2-Butoxyethanol

Content (W/W): >= 1 % - < 2 % Flam. Liq. 4
CAS Number: 111-76-2 Eye Irrit. 2A
EC-Number: 203-905-0 Acute Tox. 4 (oral)
INDEX-Number: 603-014-00-0 Skin Irrit. 2

H227, H319, H315, H302

Ammonia, anhydrous

Content (W/W): >= 0,2 % - < 0,3 % Press. Gas Liquef. Gas CAS Number: 7664-41-7 Acute Tox. 3 (Inhalation - gas) EC-Number: 231-635-3 Flam. Gas 2

INDEX-Number: 007-001-00-5

Skin Corr. 1B

Eye Dam. 1

Aquatic Acute 1

Aquatic Chronic 2

M-factor acute: 1

H280, H221, H331, H314, H411, H400

1,2-Benzisothiazol-3(2H)-one

Content (W/W): > 0 % - < 0,1 % Acute Tox. 4 (oral)
CAS Number: 2634-33-5 Skin Corr./Irrit. 2
EC-Number: 220-120-9 Skin Sens. 1
Aquatic Acute 1

Aquatic Acute 1
Aquatic Chronic 1
M-factor acute: 1
M-factor chronic: 1

H318, H315, H302, H317, H400, H410

Specific concentration limit: Skin Sens. 1: >= 0,05 %

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: allergic symptoms, No data available.

Antidote: No known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eyerinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Stove-lacquer RDL 50, Stove-lacquer R 78433, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer EHD0022, Stove-lacquer KNS L-5X, Stove-lacquer C222A/C221A, Stove-lacquer NOVOCAN S-G 500, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability:

Storage temperature: 5 - 35 °C

Specific end use(s)

Please refer to the technical leaflet for further information.

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

111-76-2: 2-Butoxyethanol 7664-41-7: Ammonia, anhydrous

Exposure controls

Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

Eye protection:

Eye protection not required.

Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid
Form: liquid
Colour: black
Odour: odourless

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Melting point:

Flammability:

not determined

onset of boiling:

not determined hardly combustible

Lower explosion limit: 36 g/m3 Flash point: > 99 °C

(ISO 3679)

Auto-ignition temperature: > 99 °C

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

pH value: 7,0 - 8,0

Viscosity, kinematic:

(40 °C)

No data available. 411,6 mm2/s (23 °C)

Viscosity, dynamic:

No applicable information available.

Solubility in water: not determined

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Vapour pressure:

(20 °C)

not determined

(50 °C)

not determined

Density: 1,256 g/cm3

(20 °C)

Relative vapour density (air):

Lighter than air.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Flammable solids

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready

specified in paragraph 33.2.4.4 of UN combustible solids))

manual of tests and criteria.

Self-heating substances and mixtures

Self heating ability: It is not a material capable of

spontaneous heating

Other safety characteristics

Miscibility with water:

miscible

Flow time: > 60 s (DIN EN ISO 2431; 6 mm)

(23 °C)

Evaporation rate:

not determined

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid freezing.

Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

.

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Based on available data, the classification criteria are not met.

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Irritation

Assessment of irritating effects:

Not irritating to the eyes. Skin contact causes slight irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H2O): No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential: No data available.

Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: No data available.

13. Disposal Considerations

Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

RID

Not classified as a dangerous good under transport regulations

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Environmental hazards: Not applicable Special precautions for None known

user

Maritime transport in bulk according to IMO instruments

Date / Revised: 12.06.2024 Version: 5.0

Product: 1109-1240-4 0,8L Stone chip/ Underbody-Protection, s

(ID no. 53757623/SDS_GEN_00/EN)

Date of print 13.06.2024

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit. Skin corrosion/irritation

Aquatic Acute Hazardous to the aquatic environment - acute

Flam. Liq. Flammable liquids
Eye Irrit. Eye irritation
Acute Tox. Acute toxicity
Skin Irrit. Skin irritation

Press. Gas
Flam. Gas
Skin Corr.
Eye Dam.
Gases under pressure
Flammable gases
Skin corrosion
Serious eye damage

Aquatic Chronic Hazardous to the aquatic environment - chronic

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Sens. Skin sensitization H227 Combustible liquid.

H319 Causes serious eye irritation.

H315 Causes skin irritation. H302 Harmful if swallowed.

H280 Contains gas under pressure; may explode if heated.

H221 Flammable gas. H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.
H411 Toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.