

# Safety data sheet

Page: 1/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11
Product: **700-1 5L CLEANING THINNER** 

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

# 700-1 5L CLEANING THINNER

UFI: YGMM-12FK-W00D-JMNH

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Thinner

# 1.3. Details of the supplier of the safety data sheet

Company:
BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland

Contact address:

BASF plc

4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG

**UNITED KINGDOM** 

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

# 1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

# **SECTION 2: Hazards Identification**

#### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

#### According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Eye Dam./Irrit. 1 H318 Causes serious eye damage. Flam. Liq. 3 H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

# 2.2. Label elements

# According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:





Signal Word:

Danger

Hazard Statement:

H226 Flammable liquid and vapour. H318 Causes serious eye damage.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Precautionary Statements (Response):

P310 Immediately call a POISON CENTER or physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazard determining component(s) for labelling: propan-1-ol

#### 2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

# **SECTION 3: Composition/Information on Ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

#### Chemical nature

Water, organic solvent

# Hazardous ingredients (GHS)

#### propan-1-ol

Content (W/W): >= 15 % - < 20 % Flam. Liq. 2 CAS Number: 71-23-8 Eve Dam./Irrit. 1

EC-Number: 200-746-9 STOT SE 3 (drowsiness and dizziness)

REACH registration number: 01- H225, H318, H336

2119486761-29

INDEX-Number: 603-003-00-0

# 1-methoxy-2-propanol

Content (W/W): >= 3 % - < 5 % Flam. Lig. 3

CAS Number: 107-98-2 STOT SE 3 (drowsiness and dizziness)

EC-Number: 203-539-1 H226, H336

REACH registration number: 01-

2119457435-35

INDEX-Number: 603-064-00-3

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

# **SECTION 4: First-Aid Measures**

# 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

#### On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

#### On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

#### On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

# **4.3.** Indication of any immediate medical attention and special treatment needed Antidote: No known specific antidote.

# **SECTION 5: Fire-Fighting Measures**

# 5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

# 5.2. Special hazards arising from the substance or mixture

Advice: Hazardous decomposition products formed under fire conditions.

# 5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

#### Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

#### **SECTION 6: Accidental Release Measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

# 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

# 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

#### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

# **SECTION 7: Handling and Storage**

# 7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eyerinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

#### Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials. Segregate from acids and acid forming substances.

Suitable materials for containers: Stainless steel 1.4301 (V2), Polypropylene (PP), Polyethylenetherephtalate (PET), Low density polyethylene (LDPE), High density polyethylene

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

(HDPE), Stove-lacquer C222A/C221A, Stove-lacquer NOVOCAN S-G 500, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50 Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability:

Storage temperature: 5.00 - 35.00 °C

# 7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

# **SECTION 8: Exposure Controls/Personal Protection**

# 8.1. Control parameters

Components with occupational exposure limits

71-23-8: propan-1-ol

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin. TWA value 500 mg/m3; 200 ppm (WEL/EH 40 (UK)) STEL value 625 mg/m3; 250 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

107-98-2: 1-methoxy-2-propanol

TWA value 375 mg/m3; 100 ppm (WEL/EH 40 (UK))

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin. STEL value 568 mg/m3; 150 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin. TWA value 375 mg/m3; 100 ppm (OEL (EU))

indicative

STEL value 560 mg/m3; 150 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

Biological limit values (BLV)

No data available.

Components with PNEC

71-23-8: propan-1-ol

freshwater: 6.83 mg/l STP: 96 mg/l

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

soil: 1.49 mg/kg

sediment (marine water): 2.75 mg/kg sediment (freshwater): 27.5 mg/kg intermittent release: 10 mg/l marine water: 0.683 mg/l oral (secondary poisoning):

No PNEC oral derived, as accumulation in organisms is not to be expected.

107-98-2: 1-methoxy-2-propanol

freshwater: 10 mg/l marine water: 1 mg/l

intermittent release: 100 mg/l

STP: 100 mg/l

sediment (freshwater): 41.6 mg/kg

soil: 2.47 mg/kg

sediment (marine water): 4.17 mg/kg

#### Components with DNEL

71-23-8: propan-1-ol

worker: Short-term exposure - systemic effects, Inhalation: 522 mg/m3 consumer: Short-term exposure - systemic effects, Inhalation: 93 mg/m3 consumer: Long-term exposure- systemic effects, oral: 16 mg/kg

107-98-2: 1-methoxy-2-propanol

worker: Short-term exposure - systemic and local effects, Inhalation: 553.5

mg/m3

worker: Long-term exposure- systemic effects, dermal: 183 mg/kg worker: Long-term exposure- systemic effects, Inhalation: 369 mg/m3 consumer: Long-term exposure- systemic effects, dermal: 78 mg/kg consumer: Long-term exposure- systemic effects, Inhalation: 43.9 mg/m3

consumer: Long-term exposure- systemic effects, oral: 33 mg/kg

# 8.2. Exposure controls

# Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

#### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter

Hand protection:

Hand protection not required.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

# Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

#### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

#### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

# **SECTION 9: Physical and Chemical Properties**

# 9.1. Information on basic physical and chemical properties

Form: liquid
Colour: colourless
Odour: alcohol-like
pH value: 10.0 - 11.0

Melting point:

not determined

onset of boiling:  $86 \, ^{\circ}\text{C}$  (calculated) Flash point:  $> 35 \, ^{\circ}\text{C}$  (ISO 3679)

Flammability: Flammable liquid and vapour.

Lower explosion limit: 36 g/m3 lgnition temperature: > 200.00 °C

Vapour pressure: 32.00 hPa (calculated)

(20 °C)

170.00 hPa (calculated)

(50 °C) 0.975 g/cm3

Density: 0.975 g/c (20 °C)

Relative vapour density (air):

Lighter than air.

Solubility in water: miscible

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Self ignition: Unspecified

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Viscosity, kinematic: 6.0 mm2/s (23 °C)

(40.00)

(40 °C)

No data available. not explosive

Explosion hazard: not explorate promoting properties: not fine

not fire-propagating

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

(DIN EN ISO 2431; 3 mm)

Date of print 10.08.2024

#### 9.2. Other information

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready

specified in paragraph 33.2.4.4 of UN combustible solids))

manual of tests and criteria.

Self heating ability: It is not a material capable of

spontaneous heating

Miscibility with water:

miscible

Flow time: < 30 s

(23 °C)

# **SECTION 10: Stability and Reactivity**

# 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

#### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### 10.3. Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

#### 10.4. Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid freezing.

# 10.5. Incompatible materials

Substances to avoid:

acid forming substances, Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions., acids

# 10.6. Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

# **SECTION 11: Toxicological Information**

# 11.1. Information on toxicological effects

#### Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Based on available data, the classification criteria are not met.

#### **Irritation**

Assessment of irritating effects:

Not irritating to the skin. May cause severe damage to the eyes.

# Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

# Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

# Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

#### **Developmental toxicity**

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

# **SECTION 12: Ecological Information**

# 12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

# 12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

No data available concerning biodegradation and elimination.

# 12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

# 12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

# 12.6. Other adverse effects

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

# **SECTION 13: Disposal Considerations**

#### 13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

07 07 01¤ aqueous washing liquids and mother liquors

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

# **SECTION 14: Transport Information**

#### **Land transport**

**ADR** 

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains PROPAN-1-OL/N-

PROPANOL)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

RID

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains PROPAN-1-OL/N-

PROPANOL)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

#### **Inland waterway transport**

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

ADN

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains PROPAN-1-OL/N-

PROPANOL)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

#### Sea transport

**IMDG** 

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains PROPAN-1-OL/N-

PROPANOL)

Transport hazard class(es): 3

Packing group: III Environmental hazards: no

Marine pollutant: NO

Special precautions for

user:

# Air transport

IATA/ICAO

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains PROPAN-1-OL/N-

PROPANOL)

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

# 14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

# 14.2. UN proper shipping name

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

# 14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

# 14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### 14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

# 14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

# 14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

# **SECTION 15: Regulatory Information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 19.9 % organic solvents VOC content: 19.9 % calculated

VOC content: 198.0 g/l

# Prohibitions, Restrictions and Authorizations

UK REACH SI, Annex XVII, Marketing and Use Restrictions

Number on List: 3

UK REACH SI, Annex XVII, Marketing and Use Restrictions

Number on List: 40

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

Limit value for maximum VOC content as specified in Annex IIB:

200 g/l

VOC content of the ready-for-use product according to ISO 11890-2: 198 g/l

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

# 15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

#### **SECTION 16: Other Information**

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Eye Dam./Irrit. Serious eye damage/eye irritation

Flam. Liq. Flammable liquids

STOT SE Specific target organ toxicity — single exposure

H226 Flammable liquid and vapour.
 H318 Causes serious eye damage.
 H225 Highly flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.

# Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the

Page: 16/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from

time to time.

Date / Revised: 09.08.2024 Version: 6.12

Date / Previous version: 25.07.2024 Previous version: 6.11

Product: 700-1 5L CLEANING THINNER

(ID no. 54784657/SDS\_GEN\_GB/EN)

Date of print 10.08.2024

corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.